#### 2. Soldering the headers

3

Before using your click<sup>™</sup> board, make sure to solder 1x8 male headers to both left and right side of the board. Two 1x8 male headers are included with the board in the package.



1



#### 4. Application and features

PROTO click<sup>™</sup> board is a cheap and effective solution for creating click board of your own design. Add sensors, drivers, passive components and make the click board which suits your project needs. You can use it with all your favorite development boards with mikroBUS<sup>™</sup> sockets.





# PROTO click<sup>™</sup>

#### 1. Introduction

ie 
mikroe.com HW REV 1 80

PROTO click<sup>™</sup> is an accessory board in **mikroBUS**<sup>™</sup> form factor. It features 10x11 prototyping area as well as additional power pads. It can be used to assemble custom electronics thus creating a custom click<sup>™</sup> board. PROTO click<sup>™</sup> contains **mikroBUS<sup>™</sup>** I<sup>2</sup>C (SDA, SCL), SPI (MISO, MOSI, SCK, CS), UART (TX, RX), PWM, INT, AN and RST lines from the target board microcontroller. The board provides 3.3 V and 5 V power supply.



Turn the board upside down so that bottom side is facing you upwards. Place shorter pins of the header into the appropriate soldering pads. Turn the board upward again. Make sure to align the headers so that they are perpendicular to the board, then solder the pins carefully.




### 3. Plugging the board in

Once you have soldered the headers your board is ready to be placed into desired mikroBUS<sup>™</sup> socket. Make sure to align the cut in the lower-right part of the board with the markings on the silkscreen at the mikroBUS<sup>™</sup> socket. If all of the pins are aligned correctly, push the board all the way into the socket.

#### 5. PROTO click<sup>®</sup> Board Schematic

#### 6. Board Dimensions



#### Legend

mm mils

#### 7. Support

MikroElektronika offers **Free Tech Support** (www.mikroe.com/support) until the end of product lifetime, so if something goes wrong, we are ready and willing to help!



⊊ 3.3V T			5V
AN		0000	PWM
RST	0000	0000	INT
CS	0000	0000	TX
SCK	0000	0-0-0-0	RX
MISO	0000	0000	SCL
MOSI	0000	0000	SDA
+3.3V	0000	0000	+5V
GND	0000	0-0-0-0	GND
MIKROBUS DEVICE CONN.			

MikroElektronika assumes no responsibility or liability for any errors or inaccuracies that may appear in the present document. Specification and information contained in the present schematic are subject to change at any time without notice. Copyright © 2013 MikroElektronika. All rights reserved.

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mikroe: MIKROE-1507