

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0621000700

Status:

Active

Overview:

Application Tooling

Description:

IDT Discrete Handtool Module

Documents:

RoHS Certificate of Compliance (PDF)

General	
Product Family	Application Tooling
Series	207129
Comments	Module for 2.54mm
Function	Insulation Displacement (IDT)
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Overview	Application Tooling
Product Name	N/A
Tool Type	Hand Crimp Tool
UPC	800753879324
Warranty Disclaimer	CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.
Physical	
Net Weight	0.001/g
Material Info	
Reference - Drawing Numbers	
Application Tooling Documents	ATS-621000799-001



Series image - Reference only

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per - ED/30/2017 (7 July 2017)	
Halogen-Free	
Status	
Not Relevant	
For more information, please visit Contact US	
China ROHS	Not Relevant
ELV	Not Relevant
RoHS Phthalates	Not Reviewed

Search Parts in this Series

207129 Series

Use With

636000478 , 11311570

Application Tooling Description	FAQ Product #
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 2 Circuits	14562021
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24	14562022

AWG, 0.38μm Gold
(Au), 2 Circuits
2.54mm Pitch 14562023
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38μm
Gold (Au), 2 Circuits
2.54mm Pitch 14562024
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38μm Gold
(Au), 2 Circuits
2.54mm Pitch 14562025
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38μm
Gold (Au), 2 Circuits
2.54mm Pitch 14562026
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38μm Gold
(Au), 2 Circuits
2.54mm Pitch 14562027
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76μm
Gold (Au), 2 Circuits
2.54mm Pitch 14562028
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76μm Gold
(Au), 2 Circuits
2.54mm Pitch 14562029
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76μm
Gold (Au), 2 Circuits

	2.54mm Pitch	<u>14562031</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	24 AWG, 0.38μm	
	Gold (Au), 3 Circuits	
	2.54mm Pitch	<u>14562032</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 3 Circuits	
	2.54mm Pitch	<u>14562033</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	26 AWG, 0.38μm	
	Gold (Au), 3 Circuits	
	2.54mm Pitch	<u>14562034</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 3 Circuits	
	2.54mm Pitch	<u>14562035</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	28 AWG, 0.38μm	
	Gold (Au), 3 Circuits	
	2.54mm Pitch	<u>14562036</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 3 Circuits	
	2.54mm Pitch	<u>14562037</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	24 AWG, 0.76μm	
	Gold (Au), 3 Circuits	
	2.54mm Pitch	<u>14562038</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14562039
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76µm
Gold (Au), 3 Circuits
2.54mm Pitch 14562041
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562042
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 4 Circuits
2.54mm Pitch 14562043
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562044
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 4 Circuits
2.54mm Pitch 14562049
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562051
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38µm
Gold (Au), 5 Circuits
2.54mm Pitch 14562052
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14562053
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38µm
Gold (Au), 5 Circuits
2.54mm Pitch 14562054
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14562055
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38µm
Gold (Au), 5 Circuits
2.54mm Pitch 14562056
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14562057
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76µm
Gold (Au), 5 Circuits
2.54mm Pitch 14562058
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive

	Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch14562059 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch14562061 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 6 Circuits 2.54mm Pitch14562062 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 6 Circuits 2.54mm Pitch14562063 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 6 Circuits 2.54mm Pitch14562064 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 6 Circuits 2.54mm Pitch14562065 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 6 Circuits 2.54mm Pitch14562066 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28
--	--

	AWG, 0.38μm Gold (Au), 6 Circuits 2.54mm Pitch14562067 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 6 Circuits 2.54mm Pitch14562068 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 6 Circuits 2.54mm Pitch14562069 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 6 Circuits 2.54mm Pitch14562071 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14562072 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14562073 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14562074 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 7 Circuits
--	--

	2.54mm Pitch	<u>14562075</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	28 AWG, 0.38μm	
	Gold (Au), 7 Circuits	
	2.54mm Pitch	<u>14562076</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 7 Circuits	
	2.54mm Pitch	<u>14562077</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	24 AWG, 0.76μm	
	Gold (Au), 7 Circuits	
	2.54mm Pitch	<u>14562078</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 7 Circuits	
	2.54mm Pitch	<u>14562079</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	26 AWG, 0.76μm	
	Gold (Au), 7 Circuits	
	2.54mm Pitch	<u>14562081</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	24 AWG, 0.38μm	
	Gold (Au), 8 Circuits	
	2.54mm Pitch	<u>14562082</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14562083</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38μm
Gold (Au), 8 Circuits
2.54mm Pitch 14562084
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38μm Gold
(Au), 8 Circuits
2.54mm Pitch 14562085
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38μm
Gold (Au), 8 Circuits
2.54mm Pitch 14562086
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38μm Gold
(Au), 8 Circuits
2.54mm Pitch 14562087
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76μm
Gold (Au), 8 Circuits
2.54mm Pitch 14562088
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76μm Gold
(Au), 8 Circuits
2.54mm Pitch 14562089
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76μm
Gold (Au), 8 Circuits
2.54mm Pitch 14562091
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38μm
Gold (Au), 9 Circuits
2.54mm Pitch [14562092](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38μm Gold
(Au), 9 Circuits
2.54mm Pitch [14562093](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38μm
Gold (Au), 9 Circuits
2.54mm Pitch [14562094](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38μm Gold
(Au), 9 Circuits
2.54mm Pitch [14562095](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38μm
Gold (Au), 9 Circuits
2.54mm Pitch [14562096](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38μm Gold
(Au), 9 Circuits
2.54mm Pitch [14562097](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76μm
Gold (Au), 9 Circuits
2.54mm Pitch [14562098](#)
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive

	Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 9 Circuits 2.54mm Pitch14562099 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 9 Circuits 2.54mm Pitch14562101 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 10 Circuits 2.54mm Pitch14562102 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 10 Circuits 2.54mm Pitch14562103 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 10 Circuits 2.54mm Pitch14562104 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 10 Circuits 2.54mm Pitch14562105 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 10 Circuits 2.54mm Pitch14562106 SL Insulation Displacement Connector Assembly, Female, Single Row,
--	--

	Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 10 Circuits 2.54mm Pitch14562107 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 10 Circuits 2.54mm Pitch14562108 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 10 Circuits 2.54mm Pitch14562109 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 10 Circuits 2.54mm Pitch14562111 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch14562113 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch14562114 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch14562115 SL Insulation Displacement
--	---

	Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14562116</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14562117</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14562118</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14562119</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14562121</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14562122</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 12 Circuits	

	2.54mm Pitch	<u>14562123</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.38μm Gold (Au),	
	12 Circuits	
	2.54mm Pitch	<u>14562124</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 12 Circuits	
	2.54mm Pitch	<u>14562125</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.38μm Gold (Au),	
	12 Circuits	
	2.54mm Pitch	<u>14562126</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 12 Circuits	
	2.54mm Pitch	<u>14562127</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.76μm Gold (Au),	
	12 Circuits	
	2.54mm Pitch	<u>14562128</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 12 Circuits	
	2.54mm Pitch	<u>14562129</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	

	0.76µm Gold (Au), 12 Circuits 2.54mm Pitch <u>14562131</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562132</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562133</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562134</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562135</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562136</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562137</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A,	
--	--	--

	Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14562138 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14562139 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14562141 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562142 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562143 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562144 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562145 SL Insulation Displacement Connector Assembly,	
--	--	--

Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562146</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562147</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562148</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562149</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562151</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562152</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562153</u>
SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14562154</u> SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14562155</u> SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14562156</u> SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14562157</u> SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14562158</u> SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14562159</u> SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 15 Circuits

	2.54mm Pitch	<u>14562161</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.38μm Gold (Au),	
	16 Circuits	
	2.54mm Pitch	<u>14562162</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14562163</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.38μm Gold (Au),	
	16 Circuits	
	2.54mm Pitch	<u>14562164</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14562165</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.38μm Gold (Au),	
	16 Circuits	
	2.54mm Pitch	<u>14562166</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14562167</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	

	0.76µm Gold (Au), 16 Circuits 2.54mm Pitch <u>14562168</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 16 Circuits 2.54mm Pitch <u>14562169</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 16 Circuits 2.54mm Pitch <u>14562171</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562172</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562173</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562174</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562175</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A,	
--	--	--

	Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562176</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562177</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562178</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562179</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562181</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 18 Circuits 2.54mm Pitch <u>14562182</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 18 Circuits 2.54mm Pitch <u>14562183</u> SL Insulation Displacement Connector Assembly,	
--	--	--

Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562184</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562185</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562186</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562187</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562188</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562189</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 18 Circuits	
2.54mm Pitch	<u>14562191</u>
SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14562192 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14562193 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14562194 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14562195 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14562196 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14562197 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 19 Circuits

	2.54mm Pitch	<u>14562198</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14562199</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.76µm Gold (Au),	
	19 Circuits	
	2.54mm Pitch	<u>14562201</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.38µm Gold (Au),	
	20 Circuits	
	2.54mm Pitch	<u>14562202</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14562203</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.38µm Gold (Au),	
	20 Circuits	
	2.54mm Pitch	<u>14562204</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14562205</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	

	0.38μm Gold (Au), 20 Circuits 2.54mm Pitch <u>14562206</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 20 Circuits 2.54mm Pitch <u>14562207</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 20 Circuits 2.54mm Pitch <u>14562208</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 20 Circuits 2.54mm Pitch <u>14562209</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 20 Circuits 2.54mm Pitch <u>14562211</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562212</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562213</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A,	
--	--	--

	Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562214</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562215</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562216</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562217</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562218</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562219</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14562221</u> SL Insulation Displacement Connector Assembly,	
--	--	--

Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562222</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562223</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562224</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562225</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562226</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562227</u>
SL Insulation	
Displacement	
Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 22 Circuits	
2.54mm Pitch	<u>14562228</u>
SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch14562229 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch14562231 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 23 Circuits 2.54mm Pitch14562232 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 23 Circuits 2.54mm Pitch14562233 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 23 Circuits 2.54mm Pitch14562234 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 23 Circuits 2.54mm Pitch14562235 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 23 Circuits

	2.54mm Pitch	<u>14562236</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 23 Circuits	
	2.54mm Pitch	<u>14562237</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.76μm Gold (Au),	
	23 Circuits	
	2.54mm Pitch	<u>14562238</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 23 Circuits	
	2.54mm Pitch	<u>14562239</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.76μm Gold (Au),	
	23 Circuits	
	2.54mm Pitch	<u>14562241</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.38μm Gold (Au),	
	24 Circuits	
	2.54mm Pitch	<u>14562242</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14562243</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	

	0.38μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562244</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562245</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562246</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562247</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562248</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562249</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562251</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A,	
--	--	--

	Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562252</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562253</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562254</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562255</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562256</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562257</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 25 Circuits 2.54mm Pitch <u>14562258</u> SL Insulation Displacement Connector Assembly,	
--	--	--

Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 25 Circuits
2.54mm Pitch 14562259
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.76µm Gold (Au),
25 Circuits
2.54mm Pitch 14563021
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 2 Circuits
2.54mm Pitch 14563022
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.76µm
Gold (Au), 2 Circuits
2.54mm Pitch 14563023
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 2 Circuits
2.54mm Pitch 14563024
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 2 Circuits
2.54mm Pitch 14563025
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 2 Circuits
2.54mm Pitch 14563026
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,

	Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 2 Circuits 2.54mm Pitch14563027 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 2 Circuits 2.54mm Pitch14563028 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 2 Circuits 2.54mm Pitch14563029 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 2 Circuits 2.54mm Pitch14563031 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 3 Circuits 2.54mm Pitch14563032 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 3 Circuits 2.54mm Pitch14563033 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 3 Circuits 2.54mm Pitch14563034 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24
--	--

	AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch14563035 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch14563036 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch14563037 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch14563038 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch14563039 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch14563041 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 4 Circuits 2.54mm Pitch14563042 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 4 Circuits
--	--

	2.54mm Pitch	<u>14563043</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563044</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563045</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563046</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563047</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563048</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563049</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14563051</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563052
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.76µm
Gold (Au), 5 Circuits
2.54mm Pitch 14563053
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563054
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563055
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563056
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563057
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563058
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563059
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14563061
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563062
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.76µm
Gold (Au), 6 Circuits
2.54mm Pitch 14563063
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563064
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563065
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563066
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front

Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14563067</u>
Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14563068</u>
Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14563069</u>
Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 7 Circuits	<u>14563071</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 7 Circuits	<u>14563072</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 7 Circuits	<u>14563073</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14563074</u>
Ribs, Wire Size 24	

	AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14563075 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14563076 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14563077 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14563078 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch14563081 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch14563082 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch14563083 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 8 Circuits
--	--

	2.54mm Pitch	<u>14563084</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14563085</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14563086</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14563087</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14563088</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14563089</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14563091</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14563092</u>
	SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76µm Gold (Au), 9 Circuits 2.54mm Pitch14563093 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 9 Circuits 2.54mm Pitch14563094 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 9 Circuits 2.54mm Pitch14563095 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 9 Circuits 2.54mm Pitch14563096 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 9 Circuits 2.54mm Pitch14563097 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 9 Circuits 2.54mm Pitch14563098 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 9 Circuits 2.54mm Pitch14563099 SL Insulation
	Displacement Connector Assembly,

Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 9 Circuits
2.54mm Pitch 14563101
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14563102
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.76µm Gold (Au),
10 Circuits
2.54mm Pitch 14563103
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14563104
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 10 Circuits
2.54mm Pitch 14563105
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 10 Circuits
2.54mm Pitch 14563106
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 10 Circuits
2.54mm Pitch 14563107
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,

	Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 10 Circuits 2.54mm Pitch14563108 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 10 Circuits 2.54mm Pitch14563109 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 10 Circuits 2.54mm Pitch14563111 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 11 Circuits 2.54mm Pitch14563112 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 11 Circuits 2.54mm Pitch14563113 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 11 Circuits 2.54mm Pitch14563114 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 11 Circuits 2.54mm Pitch14563115 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front
--	---

Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14563116</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14563117</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14563118</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14563119</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 11 Circuits 2.54mm Pitch	<u>14563121</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14563122</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14563123</u>

	AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch14563124 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch14563125 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch14563126 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch14563127 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch14563128 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch14563129 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 12 Circuits 2.54mm Pitch14563131 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76µm Gold (Au), 13 Circuits
--	---

	2.54mm Pitch	<u>14563132</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76µm Gold (Au),	
	13 Circuits	
	2.54mm Pitch	<u>14563133</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14563134</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14563135</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14563136</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14563137</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14563138</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 13 Circuits	

	2.54mm Pitch	<u>14563139</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14563141</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563142</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	14 Circuits	
	2.54mm Pitch	<u>14563143</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563144</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563145</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563146</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 14 Circuits	

	2.54mm Pitch	<u>14563147</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563148</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563149</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14563151</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563152</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	15 Circuits	
	2.54mm Pitch	<u>14563153</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563154</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 15 Circuits	

	2.54mm Pitch	<u>14563155</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563156</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563157</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563158</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563159</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 15 Circuits	
	2.54mm Pitch	<u>14563161</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563162</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	16 Circuits	

	2.54mm Pitch	<u>14563163</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563164</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563165</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563166</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563167</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563168</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563169</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14563171</u>
	SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76µm Gold (Au), 17 Circuits 2.54mm Pitch14563172 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76µm Gold (Au), 17 Circuits 2.54mm Pitch14563173 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 17 Circuits 2.54mm Pitch14563174 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch14563175 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch14563176 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch14563177 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 17 Circuits 2.54mm Pitch14563178 SL Insulation
	Displacement

Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563179
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563181
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 18 Circuits
2.54mm Pitch 14563182
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.76µm Gold (Au),
18 Circuits
2.54mm Pitch 14563183
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 18 Circuits
2.54mm Pitch 14563184
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 18 Circuits
2.54mm Pitch 14563185
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 18 Circuits
2.54mm Pitch 14563186
SL Insulation
Displacement
Connector Assembly,

Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14563187</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14563188</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14563189</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14563191</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 19 Circuits 2.54mm Pitch	<u>14563192</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 19 Circuits 2.54mm Pitch	<u>14563193</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 19 Circuits 2.54mm Pitch	<u>14563194</u>

	Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14563195 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14563196 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14563197 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14563198 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14563199 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 19 Circuits 2.54mm Pitch14563201 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 20 Circuits 2.54mm Pitch14563202 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized,
--	--

	Wire Size 28 AWG, 0.76µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563203</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563204</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563205</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563206</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563207</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563208</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563209</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28
--	--

	AWG, 0.38μm Gold (Au), 20 Circuits 2.54mm Pitch <u>14563211</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14563212</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14563213</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14563214</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14563215</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14563216</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch <u>14563217</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26
--	--

	AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch14563218 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch14563219 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 21 Circuits 2.54mm Pitch14563221 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 22 Circuits 2.54mm Pitch14563222 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 22 Circuits 2.54mm Pitch14563223 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 22 Circuits 2.54mm Pitch14563224 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 22 Circuits 2.54mm Pitch14563225 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24
--	--

	AWG, 0.38μm Gold (Au), 22 Circuits 2.54mm Pitch14563226 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 22 Circuits 2.54mm Pitch14563227 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 22 Circuits 2.54mm Pitch14563228 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 22 Circuits 2.54mm Pitch14563229 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 22 Circuits 2.54mm Pitch14563231 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 23 Circuits 2.54mm Pitch14563232 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 23 Circuits 2.54mm Pitch14563233 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28
--	--

AWG, 0.76µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563234
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563235
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563236
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563237
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563238
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563239
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563241
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 24 Circuits

	2.54mm Pitch	<u>14563242</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76µm Gold (Au),	
	24 Circuits	
	2.54mm Pitch	<u>14563243</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14563244</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14563245</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14563246</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14563247</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14563248</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 24 Circuits	

	2.54mm Pitch	<u>14563249</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 24 Circuits	
	2.54mm Pitch	<u>14563251</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 25 Circuits	
	2.54mm Pitch	<u>14563252</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	25 Circuits	
	2.54mm Pitch	<u>14563253</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76μm Gold	
	(Au), 25 Circuits	
	2.54mm Pitch	<u>14563254</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 25 Circuits	
	2.54mm Pitch	<u>14563257</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 25 Circuits	
	2.54mm Pitch	<u>14563259</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 25 Circuits	

	2.54mm Pitch	<u>14564020</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14564021</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14564022</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14564023</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14564024</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14564025</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14564030</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 3 Circuits	
	2.54mm Pitch	<u>14564031</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14564032
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14564033
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14564034
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14564035
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14564040
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 4 Circuits
2.54mm Pitch 14564041
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 4 Circuits
2.54mm Pitch 14564042
SL Insulation
Displacement
Connector Assembly,

Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 4 Circuits 2.54mm Pitch	<u>14564043</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 4 Circuits 2.54mm Pitch	<u>14564044</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 4 Circuits 2.54mm Pitch	<u>14564045</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 4 Circuits 2.54mm Pitch	<u>14564050</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch	<u>14564051</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch	<u>14564052</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch	<u>14564053</u>

Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564054</u>
Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564055</u>
Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 5 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564060</u>
Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564061</u>
Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564062</u>
Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564063</u>
Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564064</u>
Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 6 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564065</u>

AWG, 0.76μm Gold
(Au), 6 Circuits
2.54mm Pitch 14564065
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76μm Gold
(Au), 6 Circuits
2.54mm Pitch 14564070
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76μm Gold
(Au), 7 Circuits
2.54mm Pitch 14564071
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76μm Gold
(Au), 7 Circuits
2.54mm Pitch 14564072
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76μm Gold
(Au), 7 Circuits
2.54mm Pitch 14564073
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76μm Gold
(Au), 7 Circuits
2.54mm Pitch 14564074
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76μm Gold
(Au), 7 Circuits
2.54mm Pitch 14564075
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76μm Gold
(Au), 7 Circuits

	2.54mm Pitch	<u>14564080</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14564081</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14564082</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14564083</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14564084</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14564085</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 8 Circuits	
	2.54mm Pitch	<u>14564090</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14564091</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 9 Circuits
2.54mm Pitch 14564092
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 9 Circuits
2.54mm Pitch 14564093
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 9 Circuits
2.54mm Pitch 14564094
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 9 Circuits
2.54mm Pitch 14564095
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 9 Circuits
2.54mm Pitch 14564100
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564101
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564102
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564103
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564104
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564105
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564110
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564111
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564112
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564113
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back

Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564114</u>
Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564115</u>
Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564120</u>
Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564121</u>
Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564122</u>
Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14564123</u>
Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14564124</u>
Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	

	AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch14564125 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch14564130 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14564131 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14564132 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14564133 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14564134 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch14564135 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 13 Circuits
--	---

	2.54mm Pitch	<u>14564140</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14564141</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14564142</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14564143</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 14 Circuits	
	2.54mm Pitch	<u>14564144</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 14 Circuits	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[62100-0700](#)