

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0622024350

Status:

Active

Overview:

Description:

Impact Right-Angle Module Removal Tool (RAM)

General

Product Family

Series

Comments

Function

Geographic Area

Level of Automation

More Detailed Tech Information

Overview

Product Name

Tool Type

UPC

Warranty Disclaimer

Application Tooling

207123

See Tooling Specification (PDF) Above

Removal

Global

Manual

applicationtooling@molex.com

application_tooling

Impact

Press-Fit Extraction Tool

884982909076

CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Reference - Drawing Numbers

Application Tooling Documents

ATS-622024350

EU ELV

Not Relevant

EU RoHS

Not Reviewed

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Relevant

For more information, please visit [Contact US](#)

China RoHS

China ROHS

ELV

RoHS Phthalates

Not Relevant

Not Relevant

Not Reviewed

Search Parts in this Series

207123 Series

Use With

76450 Impact Ram Module Right Angle Headers, standard and orthogonal configurations 2 to 6 pairs

Application Tooling
Description

FAQ
Product #

Impact zX2 95 Ohm

6 Pair Orthogonal

Direct RAM Signal

Module, Unguided,

12 Columns, 288

Circuits, Plated

Through Hole

Dimension 0.36mm,

Lead-Free

Impact 100 Ohm

3 Pair Right-Angle

Male Header,

Unguided, Open

Endwall, 10

Columns, 90 Circuits,

Pin Length 4.90mm,

Plated Through Hole

Dimension 0.46mm,

Lead-Free

Impact 100 Ohm

3 Pair Right-Angle

Male Header,

Unguided, Open

Endwall, 10

Columns, 90 Circuits,

Pin Length 4.90mm,

Plated Through Hole

Dimension 0.39mm,

Lead-Free

1725501207

764101104

764101107

Impact 100 Ohm	<u>764101108</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Open	
Endwall, 10	
Columns, 90 Circuits,	
Pin Length 5.50mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>764101117</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Left	
Endwall, 10	
Columns, 90 Circuits,	
Pin Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>764101127</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Dual	
Endwall, 10	
Columns, 90 Circuits,	
Pin Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>764101134</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Right	
Endwall, 10	
Columns, 90 Circuits,	
Pin Length 4.90mm,	
Plated Through Hole	
Dimension 0.46mm,	
Lead-Free	
Impact 100 Ohm	<u>764101137</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Right	
Endwall, 10	
Columns, 90 Circuits,	
Pin Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>764101604</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Open	
Endwall, 16	
Columns, 144	
Circuits, Pin Length	
4.90mm, Plated	
Through Hole	
Dimension 0.46mm,	
Lead Free	
Impact 100 Ohm	<u>764101607</u>
3 Pair Right-Angle	
Male Header,	
Unguided, Open	

Endwall, 16 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764101608</u>
3 Pair Right-Angle Male Header, Unguided, Open Endwall, 16 Columns, 144 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764101627</u>
3 Pair Right-Angle Male Header, Unguided, Dual Endwall, 16 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764101804</u>
3 Pair Right-Angle Male Header, Unguided, Open Endwall, 8 Columns, 72 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm	<u>764101807</u>
3 Pair Right-Angle Male Header, Unguided, Open Endwall, 8 Columns, 72 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764101808</u>
3 Pair Right-Angle Male Header, Unguided, Open Endwall, 8 Columns, 72 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764101827</u>
3 Pair Right-Angle Male Header, Unguided, Dual Endwall, 8 Columns, 72 Circuits, Pin	

Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free

Impact 100 Ohm 764103104

3 Pair Right-Angle
Male Header,
Left Guide, Open
Endwall, 10

Columns, 90 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.46mm,
Lead-Free

Impact 100 Ohm 764103107

3 Pair Right-Angle
Male Header,
Left Guide, Open
Endwall, 10

Columns, 90 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free

Impact 100 Ohm 764103108

3 Pair Right-Angle
Male Header,
Left Guide, Open
Endwall, 10

Columns, 90 Circuits,
Pin Length 5.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free

Impact 100 Ohm 764103117

3 Pair Right-Angle
Male Header,
Left Guide, Open
Endwall, 10

Columns, 90 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Keying Orientation A,
Lead-Free

Impact 100 Ohm 764103604

3 Pair Right-Angle
Male Header,
Left Guided,
Open Endwall,

16 Columns, 144
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.46mm,
Lead Free

Impact 100 Ohm 764103607

3 Pair Right-Angle
Male Header,
Left Guide, Open
Endwall, 16

Columns, 144
Circuits, Pin Length
4.90mm, Plated
Through Hole

	Impact 100 Ohm	<u>764105107</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide,	
	Open Endwall, 10	
	Columns, 90 Circuits,	
	Pin Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764105108</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide,	
	Open Endwall, 10	
	Columns, 90 Circuits,	
	Pin Length 5.50mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764105607</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide,	
	Open Endwall,	
	16 Columns, 144	
	Circuits, Pin Length	
	4.90mm, Plated	
	Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764105608</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide,	
	Open Endwall,	
	16 Columns, 144	
	Circuits, Pin Length	
	5.50mm, Plated	
	Through Hole	
	Dimension 0.39mm,	
	Tin (Sn)	
	Impact 100 Ohm	<u>764105617</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide,	
	Open Endwall,	
	16 Columns, 144	
	Circuits, Pin Length	
	4.90mm, Plated	
	Through Hole	
	Dimension 0.39mm,	
	Keying Orientation A,	
	Lead-Free	
	Impact 100 Ohm	<u>764105804</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide, Open	
	Endwall, 8 Columns,	
	72 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.46mm,	
	Lead-Free	

	Impact 100 Ohm	<u>764105807</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide, Open	
	Endwall, 8 Columns,	
	72 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764105818</u>
	3 Pair Right-Angle	
	Male Header,	
	Right Guide, Open	
	Endwall, 8 Columns,	
	72 Circuits, Pin	
	Length 5.50mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Keying Orientation A,	
	Lead-Free	
	Impact 100 Ohm	<u>764107107</u>
	3 Pair Right-Angle	
	Male Header,	
	Left Guide, Right	
	Endwall, 10	
	Columns, 90 Circuits,	
	Pin Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764107607</u>
	3 Pair Right-Angle	
	Male Header,	
	Left Guide, Right	
	Endwall, 16	
	Columns, 144	
	Circuits, Pin Length	
	4.90mm, Plated	
	Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764107807</u>
	3 Pair Right-Angle	
	Male Header,	
	Left Guide, Right	
	Endwall, 8 Columns,	
	72 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>764109107</u>
	3 Pair Right-Angle	
	Male Header, Right	
	Guided, Left Endwall,	
	10 Columns, 90	
	Circuits, Pin Length	
	4.90mm, Plated	
	Through Hole	
	Dimension 0.39mm,	
	Lead Free	
	Impact 100 Ohm	<u>764109108</u>
	3 Pair Right-Angle	
	Male Header, Right	

Guide, Left Endwall, 10 Columns, 90 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764109607</u>
3 Pair Right-Angle Male Header, Right Guided, Left Endwall, 16 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm	<u>764109807</u>
3 Pair Right-Angle Male Header, Right Guided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm	<u>764109808</u>
3 Pair Right-Angle Male Header, Right Guided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm	<u>764501104</u>
2 Pair Right-Angle Male Header, Unguided, Open Endwall, 10 Columns, 60 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm	<u>764501107</u>
2 Pair Right-Angle Male Header, Unguided, Open Endwall, 10 Columns, 60 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>764501108</u>
2 Pair Right-Angle Male Header, Unguided, Open Endwall, 10 Columns, 60 Circuits, Pin Length 5.50, Plated Through Hole	

Unguided, Right
Endwall, 16
Columns, 96 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 764503107
2 Pair Right-Angle
Male Header,
Left Guided,
Open Endwall, 10
Columns, 60 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 764503108
2 Pair Right-Angle
Male Header,
Left Guided,
Open Endwall, 10
Columns, 60 Circuits,
Pin Length 5.50mm,,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 764503607
2 Pair Right-Angle
Male Header,
Left Guided,
Open Endwall, 16
Columns, 96 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 764503608
2 Pair Right-Angle
Male Header,
Left Guided,
Open Endwall, 16
Columns, 96 Circuits,
Pin Length 5.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 764505107
2 Pair Right-Angle
Male Header,
Right Guided,
Open Endwall, 10
Columns, 60 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm 764505108
2 Pair Right-Angle
Male Header,
Right Guided,
Open Endwall, 10
Columns, 60 Circuits,
Pin Length 5.50mm,
Plated Through Hole

	Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>764505607</u> 2 Pair Right-Angle Male Header, Right Guided, Open Endwall, 16 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>764505608</u> 2 Pair Right-Angle Male Header, Right Guided, Open Endwall, 16 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>764507107</u> 2 Pair Right-Angle Male Header, Left Guided, Right Endwall, 10 Columns, 60 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>764507108</u> 2 Pair Right-Angle Male Header, Left Guided, Right Endwall, 10 Columns, 60 Circuits, Pin Length 5.50mm,, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>764507607</u> 2 Pair Right-Angle Male Header, Left Guided, Right Endwall, 16 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>764509107</u> 2 Pair Right-Angle Male Header, Right Guided, Left Endwall, 10 Columns, 60 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm <u>764509607</u> 2 Pair Right-Angle Male Header, Right
--	--

Guided, Left Endwall,
16 Columns, 96
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead-Free
Impact 85 Ohm Plus [764951127](#)
4 Pair RAM Signal
Module, Unguided,
Dual Endwalls,
10 Columns, 120
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead Free
Impact 85 Ohm Plus [764951128](#)
4 Pair RAM Signal
Module, Unguided,
Dual Endwalls,
10 Columns, 120
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead Free
Impact 85 Ohm Plus [764951228](#)
4 Pair RAM Signal
Module, Unguided,
Dual Endwalls,
12 Columns, 144
Circuits, Pin Length
5.50mm, Plated
Through Hole
Dimension 0.39mm,
Lead Free
Impact 85 Ohm Plus [764951607](#)
4 Pair RAM Signal
Module, Unguided,
Open Endwalls,
16 Columns, 192
Circuits, Pin Length
4.90mm, Plated
Through Hole
Dimension 0.39mm,
Lead Free
Impact 85 Ohm Plus [764951807](#)
4 Pair RAM Signal
Module, Unguided,
Open Endwalls, 8
Columns, 96 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead Free
Impact 85 Ohm Plus [764951827](#)
4 Pair RAM Signal
Module, Unguided,
Dual Endwalls, 8
Columns, 96 Circuits,
Pin Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead Free

	Impact 100 Ohm	<u>765001104</u>
	4 Pair RAM Right-Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765001105</u>
	4 Pair RAM Right-Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765001107</u>
	4 Pair RAM Right-Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765001108</u>
	4 Pair RAM Right-Angle Header, Unguided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765001115</u>
	4 Pair RAM Right-Angle Header, Unguided, Left Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765001117</u>
	4 Pair RAM Right-Angle Header, Unguided, Left Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole	

	Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001118</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole
	Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001127</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole
	Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001128</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole
	Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001135</u> 4 Pair RAM Right- Angle Header, Unguided, Right Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole
	Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001137</u> 4 Pair RAM Right- Angle Header, Unguided, Right Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole
	Dimension 0.39mm, Lead Free Impact 100 Ohm <u>765001138</u> 4 Pair RAM Right- Angle Header, Unguided, Right Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated

	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001604</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated
	Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001607</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated
	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001608</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated
	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001617</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated
	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001618</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated
	Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001627</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 16 Columns, 192 Circuits, Pin Length

	4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001628</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001805</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765001807</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001808</u> 4 Pair RAM Right- Angle Header, Unguided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm <u>765001817</u> 4 Pair RAM Right- Angle Header, Unguided, Left Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765001827</u> 4 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free
--	---

	Impact 100 Ohm	<u>765001828</u>
	4 Pair RAM Right-Angle Header, Unguided, Dual Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765001838</u>
	4 Pair RAM Right-Angle Header, Unguided, Right Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765003104</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765003105</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765003107</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765003108</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	

	Impact 100 Ohm	<u>765003607</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765003608</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765003805</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765003807</u>
	4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765005104</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead Free	
	Impact 100 Ohm	<u>765005105</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead Free	

	Impact 100 Ohm	<u>765005107</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765005108</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765005607</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765005608</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
	Impact 100 Ohm	<u>765005618</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm , Key Orientation A, Lead-Free	
	Impact 100 Ohm	<u>765005805</u>
	4 Pair RAM Right-Angle Header, Right Guided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole	

	Dimension 0.46mm, Lead Free Impact 100 Ohm <u>765005807</u> 4 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765005808</u> 4 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm <u>765007107</u> 4 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765007607</u> 4 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765007608</u> 4 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765007807</u> 4 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 10 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free
--	--

Impact 100 Ohm 4 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	<u>765007808</u>
Impact 100 Ohm 4 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 10 Columns, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765009108</u>
Impact 100 Ohm 4 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	<u>765009608</u>
Impact 100 Ohm 4 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 8 Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	<u>765009808</u>
Impact 100 Ohm 6 Pair RAM Right- Angle Header, Unguided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead Free	<u>765601104</u>
Impact 100 Ohm 6 Pair RAM Right- Angle Header, Unguided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765601107</u>
Impact 100 Ohm 6 Pair RAM Right- Angle Header,	<u>765601108</u>

	Unguided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765601118 6 Pair RAM Right- Angle Header, Unguided, Left Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm 765601127 6 Pair RAM Right- Angle Header, Unguided, Dual Endwall, 10 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765601138 6 Pair RAM Right- Angle Header, Unguided, Right Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free Impact 100 Ohm 765603107 6 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765603108 6 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm 765603118 6 Pair RAM Right-
--	--

	Angle Header, Left Guided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Polarizing Key Position A, Lead- Free Impact 100 Ohm <u>765603607</u> 6 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 16 Columns, 288 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765603608</u> 6 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 16 Columns, 288 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765603707</u> 6 Pair RAM Right- Angle Header, Left Guided, Open Endwall, 14 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765605108</u> 6 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765605118</u> 6 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm,	
--	---	--

	Polarizing Key Position A, Lead- Free Impact 100 Ohm 6 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 16 Columns, 288 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765605607</u>
	Impact 100 Ohm 6 Pair RAM Right- Angle Header, Right Guided, Open Endwall, 16 Columns, 288 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765605608</u>
	Impact 100 Ohm 6 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 10 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765607107</u>
	Impact 100 Ohm 6 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765607108</u>
	Impact 100 Ohm 6 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 16 Columns, 288 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	<u>765607607</u>
	Impact 100 Ohm 6 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 16 Columns, 288 Circuits, Pin Length	<u>765607608</u>

	5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765607705</u> 6 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 14 Columns, 252 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm <u>765607708</u> 6 Pair RAM Right- Angle Header, Left Guided, Right Endwall, 14 Columns, 252 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765609105</u> 6 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm <u>765609107</u> 6 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 10 Columns, 180 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765609108</u> 6 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 10 Columns, 180 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm <u>765609707</u> 6 Pair RAM Right- Angle Header, Right Guided, Left Endwall, 14 Columns, 252 Circuits, Pin Length 4.90mm, Plated Through Hole
--	--

This document was generated on 02/27/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[62202-4350](#)