

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0623003000

Status:

Active

Overview:

Application Tooling

Description:

Hawk Ribbon Cable Terminator without Break-off

Documents:

RoHS Certificate of Compliance (PDF)

General

Product Family

Series

Function

Geographic Area

Level of Automation

More Detailed Tech Information

Overview

Product Name

Tool Type

UPC

Warranty Disclaimer

Application Tooling

T9999

Insulation Displacement (IDT)

Global

Semi-Automatic

applicationtooling@molex.com

Application Tooling

Hawk

IDT Hand Tool

800753288218

CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Reference - Drawing Numbers

Application Tooling Documents

TM-623002900-001



Series image - Reference only

EU ELV

Not Reviewed

EU RoHS

Not Reviewed

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

For more information, please visit [Contact US](#)

China RoHS

Not Reviewed

China ROHS

Not Reviewed

ELV

Not Reviewed

RoHS Phthalates

Not Reviewed

Search Parts in this Series

T9999 Series

Use With

70400 C-Grid SL IDT Connectors

Application Tooling Description	FAQ Product #
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 2 Circuits	14562021
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 2 Circuits	14562022

	2.54mm Pitch	<u>14562023</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	26 AWG, 0.38μm	
	Gold (Au), 2 Circuits	
	2.54mm Pitch	<u>14562024</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14562025</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	28 AWG, 0.38μm	
	Gold (Au), 2 Circuits	
	2.54mm Pitch	<u>14562026</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14562027</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	24 AWG, 0.76μm	
	Gold (Au), 2 Circuits	
	2.54mm Pitch	<u>14562028</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 2 Circuits	
	2.54mm Pitch	<u>14562029</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	26 AWG, 0.76μm	
	Gold (Au), 2 Circuits	
	2.54mm Pitch	<u>14562031</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38μm
Gold (Au), 3 Circuits
2.54mm Pitch 14562032
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38μm Gold
(Au), 3 Circuits
2.54mm Pitch 14562033
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38μm
Gold (Au), 3 Circuits
2.54mm Pitch 14562034
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38μm Gold
(Au), 3 Circuits
2.54mm Pitch 14562035
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38μm
Gold (Au), 3 Circuits
2.54mm Pitch 14562036
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38μm Gold
(Au), 3 Circuits
2.54mm Pitch 14562037
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76μm
Gold (Au), 3 Circuits
2.54mm Pitch 14562038
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 3 Circuits
2.54mm Pitch 14562039
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76µm
Gold (Au), 3 Circuits
2.54mm Pitch 14562041
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562042
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 4 Circuits
2.54mm Pitch 14562043
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562044
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 4 Circuits
2.54mm Pitch 14562045
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562046
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive

Lock, Wire Size 28
AWG, 0.38µm Gold
(Au), 4 Circuits
2.54mm Pitch 14562047
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562048
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 4 Circuits
2.54mm Pitch 14562049
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76µm
Gold (Au), 4 Circuits
2.54mm Pitch 14562051
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38µm
Gold (Au), 5 Circuits
2.54mm Pitch 14562052
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 5 Circuits
2.54mm Pitch 14562053
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38µm
Gold (Au), 5 Circuits
2.54mm Pitch 14562054
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26

	AWG, 0.38μm Gold (Au), 5 Circuits 2.54mm Pitch14562055 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 5 Circuits 2.54mm Pitch14562056 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 5 Circuits 2.54mm Pitch14562057 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 5 Circuits 2.54mm Pitch14562058 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 5 Circuits 2.54mm Pitch14562059 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 5 Circuits 2.54mm Pitch14562061 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 6 Circuits 2.54mm Pitch14562062 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 6 Circuits
--	--

	2.54mm Pitch	<u>14562063</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	26 AWG, 0.38μm	
	Gold (Au), 6 Circuits	
	2.54mm Pitch	<u>14562064</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 6 Circuits	
	2.54mm Pitch	<u>14562065</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	28 AWG, 0.38μm	
	Gold (Au), 6 Circuits	
	2.54mm Pitch	<u>14562066</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 6 Circuits	
	2.54mm Pitch	<u>14562067</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	24 AWG, 0.76μm	
	Gold (Au), 6 Circuits	
	2.54mm Pitch	<u>14562068</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 6 Circuits	
	2.54mm Pitch	<u>14562069</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version A, Non-	
	polarized, Wire Size	
	26 AWG, 0.76μm	
	Gold (Au), 6 Circuits	
	2.54mm Pitch	<u>14562071</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38μm
Gold (Au), 7 Circuits
2.54mm Pitch 14562072
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38μm Gold
(Au), 7 Circuits
2.54mm Pitch 14562073
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38μm
Gold (Au), 7 Circuits
2.54mm Pitch 14562074
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38μm Gold
(Au), 7 Circuits
2.54mm Pitch 14562075
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38μm
Gold (Au), 7 Circuits
2.54mm Pitch 14562076
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38μm Gold
(Au), 7 Circuits
2.54mm Pitch 14562077
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.76μm
Gold (Au), 7 Circuits
2.54mm Pitch 14562078
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 7 Circuits
2.54mm Pitch 14562079
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.76µm
Gold (Au), 7 Circuits
2.54mm Pitch 14562081
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
24 AWG, 0.38µm
Gold (Au), 8 Circuits
2.54mm Pitch 14562082
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 8 Circuits
2.54mm Pitch 14562083
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
26 AWG, 0.38µm
Gold (Au), 8 Circuits
2.54mm Pitch 14562084
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 8 Circuits
2.54mm Pitch 14562085
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.38µm
Gold (Au), 8 Circuits
2.54mm Pitch 14562086
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive

	Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 8 Circuits 2.54mm Pitch14562087 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch14562088 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch14562089 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch14562091 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 9 Circuits 2.54mm Pitch14562092 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 9 Circuits 2.54mm Pitch14562093 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 9 Circuits 2.54mm Pitch14562094 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26
--	--

	AWG, 0.38μm Gold (Au), 9 Circuits 2.54mm Pitch14562095 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 9 Circuits 2.54mm Pitch14562096 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 9 Circuits 2.54mm Pitch14562097 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 9 Circuits 2.54mm Pitch14562098 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 9 Circuits 2.54mm Pitch14562099 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 9 Circuits 2.54mm Pitch14562101 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38μm Gold (Au), 10 Circuits 2.54mm Pitch14562102 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24
--	---

	AWG, 0.38μm Gold (Au), 10 Circuits 2.54mm Pitch	<u>14562103</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 10 Circuits	
	2.54mm Pitch	<u>14562104</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 10 Circuits	
	2.54mm Pitch	<u>14562105</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 10 Circuits	
	2.54mm Pitch	<u>14562106</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 10 Circuits	
	2.54mm Pitch	<u>14562107</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 10 Circuits	
	2.54mm Pitch	<u>14562108</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 10 Circuits	
	2.54mm Pitch	<u>14562109</u>
	SL Insulation Displacement Connector Assembly, Female, Single Row, Version A,	

	Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 10 Circuits 2.54mm Pitch <u>14562111</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch <u>14562113</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch <u>14562114</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch <u>14562115</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch <u>14562116</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 11 Circuits 2.54mm Pitch <u>14562117</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 11 Circuits 2.54mm Pitch <u>14562118</u> SL Insulation Displacement	
--	--	--

Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14562119
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.76µm Gold (Au),
11 Circuits
2.54mm Pitch 14562121
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.38µm Gold (Au),
12 Circuits
2.54mm Pitch 14562122
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 12 Circuits
2.54mm Pitch 14562123
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.38µm Gold (Au),
12 Circuits
2.54mm Pitch 14562124
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 12 Circuits
2.54mm Pitch 14562125
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.38µm Gold (Au),
12 Circuits

	2.54mm Pitch	<u>14562126</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 12 Circuits	
	2.54mm Pitch	<u>14562127</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.76μm Gold (Au),	
	12 Circuits	
	2.54mm Pitch	<u>14562128</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 12 Circuits	
	2.54mm Pitch	<u>14562129</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.76μm Gold (Au),	
	12 Circuits	
	2.54mm Pitch	<u>14562131</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.38μm Gold (Au),	
	13 Circuits	
	2.54mm Pitch	<u>14562132</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 13 Circuits	
	2.54mm Pitch	<u>14562133</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	

	0.38μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562134</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562135</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562136</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562137</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562138</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562139</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76μm Gold (Au), 13 Circuits 2.54mm Pitch <u>14562141</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A,	
--	--	--

	Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562142 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562143 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562144 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562145 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562146 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch14562147 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 14 Circuits 2.54mm Pitch14562148 SL Insulation Displacement Connector Assembly,	
--	--	--

Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562149</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 14 Circuits 2.54mm Pitch	<u>14562151</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562152</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562153</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562154</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562155</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 15 Circuits 2.54mm Pitch	<u>14562156</u>
SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 15 Circuits 2.54mm Pitch14562157 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 15 Circuits 2.54mm Pitch14562158 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 15 Circuits 2.54mm Pitch14562159 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 15 Circuits 2.54mm Pitch14562161 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 16 Circuits 2.54mm Pitch14562162 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 16 Circuits 2.54mm Pitch14562163 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 16 Circuits

	2.54mm Pitch	<u>14562164</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14562165</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.38μm Gold (Au),	
	16 Circuits	
	2.54mm Pitch	<u>14562166</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14562167</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.76μm Gold (Au),	
	16 Circuits	
	2.54mm Pitch	<u>14562168</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.76μm Gold	
	(Au), 16 Circuits	
	2.54mm Pitch	<u>14562169</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.76μm Gold (Au),	
	16 Circuits	
	2.54mm Pitch	<u>14562171</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	

	0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562172</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562173</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562174</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562175</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562176</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562177</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14562178</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive	
--	---	--

	Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 17 Circuits 2.54mm Pitch14562179 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 17 Circuits 2.54mm Pitch14562181 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 18 Circuits 2.54mm Pitch14562182 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 18 Circuits 2.54mm Pitch14562183 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 18 Circuits 2.54mm Pitch14562184 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 18 Circuits 2.54mm Pitch14562185 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 18 Circuits 2.54mm Pitch14562186 SL Insulation Displacement Connector Assembly,
--	---

Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14562187</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14562188</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14562189</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 18 Circuits 2.54mm Pitch	<u>14562191</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 19 Circuits 2.54mm Pitch	<u>14562192</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 19 Circuits 2.54mm Pitch	<u>14562193</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 19 Circuits 2.54mm Pitch	<u>14562194</u>
SL Insulation	

	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 19 Circuits 2.54mm Pitch14562195 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 19 Circuits 2.54mm Pitch14562196 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 19 Circuits 2.54mm Pitch14562197 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 19 Circuits 2.54mm Pitch14562198 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 19 Circuits 2.54mm Pitch14562199 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 19 Circuits 2.54mm Pitch14562201 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 20 Circuits

	2.54mm Pitch	<u>14562202</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14562203</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.38μm Gold (Au),	
	20 Circuits	
	2.54mm Pitch	<u>14562204</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14562205</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.38μm Gold (Au),	
	20 Circuits	
	2.54mm Pitch	<u>14562206</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14562207</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.76μm Gold (Au),	
	20 Circuits	
	2.54mm Pitch	<u>14562208</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	

AWG, 0.76µm Gold
(Au), 20 Circuits
2.54mm Pitch 14562209
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.76µm Gold (Au),
20 Circuits
2.54mm Pitch 14562211
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.38µm Gold (Au),
21 Circuits
2.54mm Pitch 14562212
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 21 Circuits
2.54mm Pitch 14562213
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.38µm Gold (Au),
21 Circuits
2.54mm Pitch 14562214
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 21 Circuits
2.54mm Pitch 14562215
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.38µm Gold (Au),
21 Circuits
2.54mm Pitch 14562216
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,

Version G, Positive
Lock, Wire Size 28
AWG, 0.38µm Gold
(Au), 21 Circuits
2.54mm Pitch 14562217
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.76µm Gold (Au),
21 Circuits
2.54mm Pitch 14562218
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 21 Circuits
2.54mm Pitch 14562219
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.76µm Gold (Au),
21 Circuits
2.54mm Pitch 14562221
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.38µm Gold (Au),
22 Circuits
2.54mm Pitch 14562222
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 22 Circuits
2.54mm Pitch 14562223
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.38µm Gold (Au),
22 Circuits
2.54mm Pitch 14562224
SL Insulation
Displacement

	Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch14562225 SL Insulation Displacement
	Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch14562226 SL Insulation Displacement
	Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch14562227 SL Insulation Displacement
	Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch14562228 SL Insulation Displacement
	Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch14562229 SL Insulation Displacement
	Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch14562231 SL Insulation Displacement
	Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 23 Circuits

	2.54mm Pitch	<u>14562232</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 23 Circuits	
	2.54mm Pitch	<u>14562233</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 26 AWG,	
	0.38μm Gold (Au),	
	23 Circuits	
	2.54mm Pitch	<u>14562234</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 23 Circuits	
	2.54mm Pitch	<u>14562235</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.38μm Gold (Au),	
	23 Circuits	
	2.54mm Pitch	<u>14562236</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 23 Circuits	
	2.54mm Pitch	<u>14562237</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 24 AWG,	
	0.76μm Gold (Au),	
	23 Circuits	
	2.54mm Pitch	<u>14562238</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 24	

	AWG, 0.76µm Gold (Au), 23 Circuits 2.54mm Pitch <u>14562239</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.76µm Gold (Au), 23 Circuits 2.54mm Pitch <u>14562241</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 24 AWG, 0.38µm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562242</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 0.38µm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562243</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 26 AWG, 0.38µm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562244</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562245</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.38µm Gold (Au), 24 Circuits 2.54mm Pitch <u>14562246</u> SL Insulation Displacement Connector Assembly, Female, Single Row,	
--	--	--

Version G, Positive
Lock, Wire Size 28
AWG, 0.38µm Gold
(Au), 24 Circuits
2.54mm Pitch 14562247
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.76µm Gold (Au),
24 Circuits
2.54mm Pitch 14562248
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 24 Circuits
2.54mm Pitch 14562249
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.76µm Gold (Au),
24 Circuits
2.54mm Pitch 14562251
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.38µm Gold (Au),
25 Circuits
2.54mm Pitch 14562252
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.38µm Gold
(Au), 25 Circuits
2.54mm Pitch 14562253
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.38µm Gold (Au),
25 Circuits
2.54mm Pitch 14562254
SL Insulation
Displacement

Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.38µm Gold
(Au), 25 Circuits
2.54mm Pitch 14562255
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.38µm Gold (Au),
25 Circuits
2.54mm Pitch 14562256
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.38µm Gold
(Au), 25 Circuits
2.54mm Pitch 14562257
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 24 AWG,
0.76µm Gold (Au),
25 Circuits
2.54mm Pitch 14562258
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 24
AWG, 0.76µm Gold
(Au), 25 Circuits
2.54mm Pitch 14562259
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 26 AWG,
0.76µm Gold (Au),
25 Circuits
2.54mm Pitch 14563021
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 2 Circuits
2.54mm Pitch 14563022
SL Insulation

	Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76µm Gold (Au), 2 Circuits 2.54mm Pitch14563023 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 2 Circuits 2.54mm Pitch14563024 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 2 Circuits 2.54mm Pitch14563025 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 2 Circuits 2.54mm Pitch14563026 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 2 Circuits 2.54mm Pitch14563027 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 2 Circuits 2.54mm Pitch14563028 SL Insulation
	Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 2 Circuits 2.54mm Pitch14563029 SL Insulation
	Displacement Connector Assembly,

Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 2 Circuits 2.54mm Pitch	<u>14563031</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 3 Circuits 2.54mm Pitch	<u>14563032</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 3 Circuits 2.54mm Pitch	<u>14563033</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 3 Circuits 2.54mm Pitch	<u>14563034</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch	<u>14563035</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch	<u>14563036</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch	<u>14563037</u>

Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14563038</u>
Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14563039</u>
Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 3 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26	<u>14563041</u>
AWG, 0.76μm Gold (Au), 4 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 4 Circuits	<u>14563042</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 4 Circuits	<u>14563043</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14563044</u>
Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 4 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14563045</u>
Ribs, Wire Size 24	

	AWG, 0.38μm Gold (Au), 4 Circuits 2.54mm Pitch14563046 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 4 Circuits 2.54mm Pitch14563047 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 4 Circuits 2.54mm Pitch14563048 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 4 Circuits 2.54mm Pitch14563049 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 4 Circuits 2.54mm Pitch14563051 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 5 Circuits 2.54mm Pitch14563052 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 5 Circuits 2.54mm Pitch14563053 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 5 Circuits
--	---

	2.54mm Pitch	<u>14563054</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 5 Circuits	
	2.54mm Pitch	<u>14563055</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 5 Circuits	
	2.54mm Pitch	<u>14563056</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 5 Circuits	
	2.54mm Pitch	<u>14563057</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 5 Circuits	
	2.54mm Pitch	<u>14563058</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 5 Circuits	
	2.54mm Pitch	<u>14563059</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 5 Circuits	
	2.54mm Pitch	<u>14563061</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 6 Circuits	
	2.54mm Pitch	<u>14563062</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.76µm
Gold (Au), 6 Circuits
2.54mm Pitch 14563063
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563064
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563065
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563066
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563067
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563068
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563069
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 6 Circuits
2.54mm Pitch 14563071
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 7 Circuits
2.54mm Pitch 14563072
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.76µm
Gold (Au), 7 Circuits
2.54mm Pitch 14563073
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 7 Circuits
2.54mm Pitch 14563074
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 7 Circuits
2.54mm Pitch 14563075
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 7 Circuits
2.54mm Pitch 14563076
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 7 Circuits
2.54mm Pitch 14563077
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back

Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14563078</u>
Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 7 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 8 Circuits	<u>14563081</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non- polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 8 Circuits	<u>14563082</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 8 Circuits	<u>14563083</u>
2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back	<u>14563084</u>
Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 8 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14563085</u>
Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 8 Circuits 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front	<u>14563086</u>
Ribs, Wire Size 26	

AWG, 0.38μm Gold
(Au), 8 Circuits
2.54mm Pitch 14563087
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.38μm Gold
(Au), 8 Circuits
2.54mm Pitch 14563088
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38μm Gold
(Au), 8 Circuits
2.54mm Pitch 14563089
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38μm Gold
(Au), 8 Circuits
2.54mm Pitch 14563091
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76μm Gold
(Au), 9 Circuits
2.54mm Pitch 14563092
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version A, Non-
polarized, Wire Size
28 AWG, 0.76μm
Gold (Au), 9 Circuits
2.54mm Pitch 14563093
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76μm Gold
(Au), 9 Circuits
2.54mm Pitch 14563094
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38μm Gold
(Au), 9 Circuits

	2.54mm Pitch	<u>14563095</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14563096</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14563097</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14563098</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14563099</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14563101</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563102</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	10 Circuits	

	2.54mm Pitch	<u>14563103</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563104</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563105</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563106</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563107</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563108</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563109</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14563111</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563112
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.76µm Gold (Au),
11 Circuits
2.54mm Pitch 14563113
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563114
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563115
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563116
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563117
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563118
SL Insulation
Displacement

Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563119
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 11 Circuits
2.54mm Pitch 14563121
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 12 Circuits
2.54mm Pitch 14563122
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.76µm Gold (Au),
12 Circuits
2.54mm Pitch 14563123
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 12 Circuits
2.54mm Pitch 14563124
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 12 Circuits
2.54mm Pitch 14563125
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 12 Circuits
2.54mm Pitch 14563126
SL Insulation
Displacement
Connector Assembly,

Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14563127</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14563128</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14563129</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14563131</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 13 Circuits 2.54mm Pitch	<u>14563132</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 13 Circuits 2.54mm Pitch	<u>14563133</u>
SL Insulation Displacement Connector Assembly, Female, Single Row,	<u>14563134</u>

	Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch14563135 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch14563136 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch14563137 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch14563138 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch14563139 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 13 Circuits 2.54mm Pitch14563141 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 14 Circuits 2.54mm Pitch14563142 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized,
--	--

	Wire Size 28 AWG, 0.76µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563143</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563144</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563145</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563146</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563147</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563148</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563149</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28
--	--

	AWG, 0.38μm Gold (Au), 14 Circuits 2.54mm Pitch <u>14563151</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563152</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563153</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563154</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563155</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563156</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563157</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26
--	--

	AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563158</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563159</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 15 Circuits 2.54mm Pitch <u>14563161</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563162</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563163</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563164</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563165</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24
--	--

	AWG, 0.38μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563166</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563167</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563168</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563169</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 16 Circuits 2.54mm Pitch <u>14563171</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14563172</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 17 Circuits 2.54mm Pitch <u>14563173</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28
--	--

AWG, 0.76µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563174
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563175
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563176
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563177
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563178
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563179
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 17 Circuits
2.54mm Pitch 14563181
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 18 Circuits

	2.54mm Pitch	<u>14563182</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76µm Gold (Au),	
	18 Circuits	
	2.54mm Pitch	<u>14563183</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 18 Circuits	
	2.54mm Pitch	<u>14563184</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 18 Circuits	
	2.54mm Pitch	<u>14563185</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 18 Circuits	
	2.54mm Pitch	<u>14563186</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 18 Circuits	
	2.54mm Pitch	<u>14563187</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 18 Circuits	
	2.54mm Pitch	<u>14563188</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 18 Circuits	

	2.54mm Pitch	<u>14563189</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 18 Circuits	
	2.54mm Pitch	<u>14563191</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563192</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	19 Circuits	
	2.54mm Pitch	<u>14563193</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563194</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563195</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563196</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 19 Circuits	

	2.54mm Pitch	<u>14563197</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563198</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563199</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38μm Gold	
	(Au), 19 Circuits	
	2.54mm Pitch	<u>14563201</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 26	
	AWG, 0.76μm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14563202</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single	
	Row, Version A,	
	Non-polarized,	
	Wire Size 28 AWG,	
	0.76μm Gold (Au),	
	20 Circuits	
	2.54mm Pitch	<u>14563203</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76μm Gold	
	(Au), 20 Circuits	
	2.54mm Pitch	<u>14563204</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38μm Gold	
	(Au), 20 Circuits	

	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 20 Circuits	<u>14563205</u>
	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 20 Circuits	<u>14563206</u>
	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 20 Circuits	<u>14563207</u>
	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 20 Circuits	<u>14563208</u>
	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 20 Circuits	<u>14563209</u>
	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 21 Circuits	<u>14563211</u>
	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 21 Circuits	<u>14563212</u>

	2.54mm Pitch	<u>14563213</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version G, Positive	
	Lock, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563214</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563215</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.38µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563216</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563217</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.38µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563218</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563219</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.38µm Gold	
	(Au), 21 Circuits	
	2.54mm Pitch	<u>14563221</u>
	SL Insulation	

Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563222</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563223</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563224</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563225</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563226</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563227</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 22 Circuits 2.54mm Pitch	<u>14563228</u>
SL Insulation Displacement	

Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 22 Circuits
2.54mm Pitch 14563229
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.38µm Gold
(Au), 22 Circuits
2.54mm Pitch 14563231
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 26
AWG, 0.76µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563232
SL Insulation
Displacement
Connector Assembly,
Female, Single
Row, Version A,
Non-polarized,
Wire Size 28 AWG,
0.76µm Gold (Au),
23 Circuits
2.54mm Pitch 14563233
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version G, Positive
Lock, Wire Size 28
AWG, 0.76µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563234
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563235
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.38µm Gold
(Au), 23 Circuits
2.54mm Pitch 14563236
SL Insulation
Displacement
Connector Assembly,

Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 23 Circuits 2.54mm Pitch	<u>14563237</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 23 Circuits 2.54mm Pitch	<u>14563238</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 23 Circuits 2.54mm Pitch	<u>14563239</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 23 Circuits 2.54mm Pitch	<u>14563241</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 0.76μm Gold (Au), 24 Circuits 2.54mm Pitch	<u>14563242</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 24 Circuits 2.54mm Pitch	<u>14563243</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76μm Gold (Au), 24 Circuits 2.54mm Pitch	<u>14563244</u>

	Version D, Back Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch14563245 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch14563246 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch14563247 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch14563248 SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch14563249 SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38μm Gold (Au), 24 Circuits 2.54mm Pitch14563251 SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.76μm Gold (Au), 25 Circuits 2.54mm Pitch14563252 SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized,
--	--

	Wire Size 28 AWG, 0.76µm Gold (Au), 25 Circuits 2.54mm Pitch <u>14563253</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 0.76µm Gold (Au), 25 Circuits 2.54mm Pitch <u>14563254</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.38µm Gold (Au), 25 Circuits 2.54mm Pitch <u>14563257</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.38µm Gold (Au), 25 Circuits 2.54mm Pitch <u>14563259</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.38µm Gold (Au), 25 Circuits 2.54mm Pitch <u>14564020</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 2 Circuits 2.54mm Pitch <u>14564021</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 2 Circuits 2.54mm Pitch <u>14564022</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26
--	---

AWG, 0.76μm Gold
(Au), 2 Circuits
2.54mm Pitch 14564023
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76μm Gold
(Au), 2 Circuits
2.54mm Pitch 14564024
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76μm Gold
(Au), 2 Circuits
2.54mm Pitch 14564025
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76μm Gold
(Au), 2 Circuits
2.54mm Pitch 14564030
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76μm Gold
(Au), 3 Circuits
2.54mm Pitch 14564031
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76μm Gold
(Au), 3 Circuits
2.54mm Pitch 14564032
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76μm Gold
(Au), 3 Circuits
2.54mm Pitch 14564033
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76μm Gold
(Au), 3 Circuits

	2.54mm Pitch	<u>14564034</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 3 Circuits	
	2.54mm Pitch	<u>14564035</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 3 Circuits	
	2.54mm Pitch	<u>14564040</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14564041</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14564042</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14564043</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14564044</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 4 Circuits	
	2.54mm Pitch	<u>14564045</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 4 Circuits
2.54mm Pitch 14564050
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14564051
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14564052
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14564053
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14564054
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14564055
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 5 Circuits
2.54mm Pitch 14564060
SL Insulation
Displacement
Connector Assembly,

Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14564061
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14564062
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14564063
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14564064
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14564065
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 6 Circuits
2.54mm Pitch 14564070
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 7 Circuits
2.54mm Pitch 14564071
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back

Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 7 Circuits 2.54mm Pitch	<u>14564072</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 7 Circuits 2.54mm Pitch	<u>14564073</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 7 Circuits 2.54mm Pitch	<u>14564074</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 7 Circuits 2.54mm Pitch	<u>14564075</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 7 Circuits 2.54mm Pitch	<u>14564080</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 8 Circuits 2.54mm Pitch	<u>14564081</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 8 Circuits 2.54mm Pitch	<u>14564082</u>

	AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch <u>14564083</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch <u>14564084</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch <u>14564085</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.76μm Gold (Au), 8 Circuits 2.54mm Pitch <u>14564090</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76μm Gold (Au), 9 Circuits 2.54mm Pitch <u>14564091</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.76μm Gold (Au), 9 Circuits 2.54mm Pitch <u>14564092</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.76μm Gold (Au), 9 Circuits 2.54mm Pitch <u>14564093</u> SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.76μm Gold (Au), 9 Circuits
--	---

	2.54mm Pitch	<u>14564094</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14564095</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 9 Circuits	
	2.54mm Pitch	<u>14564100</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14564101</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 24	
	AWG, 0.76µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14564102</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14564103</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version D, Back	
	Ribs, Wire Size 26	
	AWG, 0.76µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14564104</u>
	SL Insulation	
	Displacement	
	Connector Assembly,	
	Female, Single Row,	
	Version C, Front	
	Ribs, Wire Size 28	
	AWG, 0.76µm Gold	
	(Au), 10 Circuits	
	2.54mm Pitch	<u>14564105</u>
	SL Insulation	

Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 10 Circuits
2.54mm Pitch 14564110
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564111
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564112
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564113
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564114
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564115
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 11 Circuits
2.54mm Pitch 14564120
SL Insulation
Displacement
Connector Assembly,

Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14564121</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14564122</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14564123</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14564124</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14564125</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 12 Circuits 2.54mm Pitch	<u>14564130</u>
SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 0.76µm Gold (Au), 13 Circuits 2.54mm Pitch	<u>14564131</u>

Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 13 Circuits
2.54mm Pitch 14564132
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 13 Circuits
2.54mm Pitch 14564133
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 26
AWG, 0.76µm Gold
(Au), 13 Circuits
2.54mm Pitch 14564134
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 13 Circuits
2.54mm Pitch 14564135
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version D, Back
Ribs, Wire Size 28
AWG, 0.76µm Gold
(Au), 13 Circuits
2.54mm Pitch 14564140
SL Insulation
Displacement
Connector Assembly,
Female, Single Row,
Version C, Front
Ribs, Wire Size 24
AWG, 0.76µm Gold
(Au), 14 Circuits

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[62300-3000](#)