

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1552100025](#)
Status: **Active**
Overview: [Flamar Standard and Custom Cables for Industrial Automation](#)
Description: Flamar Sensor Cable, PVC Jacket, Unshielded, 5 Circuits, 0.25mm² / 24 AWG, 5.30mm (.209") Diameter, 600.0m (1968.50') Length, Black

Documents:

[Product Specification 1552100001-P1E \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Brochure \(PDF\)](#)

Agency Certification

UL E172949

General

Product Family Cable
Series [155210](#)
Comments 3 reels of 200.0m each
Crimp Quality Equipment Yes
Geographic Area Global
Overview [Flamar Standard and Custom Cables for Industrial Automation](#)
Product Name Flamar, Signal and Control
UPC 889056449038

Physical

Bending Radius - Minimum > 15xOD
Cable Length 600.0m
Circuits (Loaded) 5
Color - Cable Jacket Black
Insulation TPE
Material - Outer Jacket PVC
Net Weight 0.040/kg
Outer Jacket Diameter 5.30mm
Packaging Type Reel
Temperature Range - Operating +5° to +80°C
Wire Size AWG 24
Wire Size mm² 0.25
Wire/Cable Type UL AWM 2464 / CSA

Electrical


Current - Maximum per Contact Contact Molex
Voltage - Maximum 300V

Material Info

Engineering Number 3X200M

Reference - Drawing Numbers

Product Specification 1552100001-P1E



Series image - Reference only

EU ELV

Not Reviewed

EU RoHS

Not Reviewed

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

For more information, please visit [Contact US](#)

China ROHS	Not Reviewed
ELV	Not Reviewed
RoHS Phthalates	Not Reviewed

Search Parts in this Series

[155210](#) Series

Use With

Nano-Change (M8) [120091](#) , Micro-Change (M12) [120071](#) , Ultra-Lock (M12) [120085](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[155210-0025](#)