-	9 8	7	6	5		4	3	2	1	
E	NOTES: 1. MOUNTING TYPE: SCREW. 2. VOLTAGE: 600 V (UL). 3. CURRENT: Cu 380 A, AI 310 A (UL). 3. WIRE CROSS-SECTION RANGE, UL: Cu/AI 3/0 AWG - 500mm ² (85 - 500mm ²) 3X 1/0-2 AWG (3X 53-33.6mm ²) STRAN 2X 2/0-2 AWG (2X 67-33.6mm ²) STRAN 4. HEAD CAP SCREW WITH 8mm HEXAG	DED DED	97		67	-			2	E
D	SOCKET SIZE. 5. RECOMMENDED TIGHTENING TORQU 360 Lb-In (40 Nm). 6. ALL ELECTRICAL AND MECHANICAL SPECIFICATIONS ARE PER UL1059 AS NOTED IN MOLEX UL AGENCY APPROVAL.	JE:	<u>36</u> 130		¥ 2:0	3				D
c	 7. THE SUITABILITY OF THESE TERMINA SHALL BE DETERMINED IN THE END- INVESTIGATION. 8. AS ENVIRONMENTAL BARRIER DIELECTRIC GREASE MAY BE PRESENT IN THE WIRING CHAMBER. ENSURE TO USE THE RECOMMENDE TIGHTING TORQUE FOR ALL CONDUC 	USE			4	64				C
В			× (8)		THIS DRAWING CONT.	GENERAL	UCLP 1PLD GRN/YLW W/SCR 38 UCLP 1PLD GRY/BLU W/SCR 38 UCLP 1PLD GRY/GRY W/SCR 38 UCLP 1PLD GRY/GRY W/SCR 38 DESCRIPTION	DA BLUE DA GREY COVER COLO GIES, LLC AND SHOULD NOT B		B ON
	4 4 SCREW, SET ALUMINUM 3 1 CAGE, 1-P ALUMINIUM 2 1 COVER, 2-P, W-SNAP HOOKS POLYAMIDE 1 1 HOUSING, 2-P POLYAMIDE ITEM QTY DESCRIPTION MATERIAL RELEASE STATUS P1 RELEASE DATE 18.08.2017 19:46:49 WIT BROKA BONK 9 8 8	TOLERANCE >0.5=3 ISO 2768-m ±0.1	3 >3=6 >6=30 >30=120 ±0.1 ±0.2 ±0.3 6) >120=400 ≠0.5 5	RELEASE EC NO: 120665 DRWN: WLEUNG CHK'D: DNGUYEN62 CHK'D: DNGUYEN62 APPR: JFMURPHY Jo Jo	TOLERANCES INLESS SPECIFIED) IGULAR TOL ± °	mm 1:1 DRWN BY DATE WLEUNG 2017/08/14 CHK'D BY DATE DNGUYEN62 2017/08/15 APPR BY DATE JFMURPHY 2017/08/18 DRAWING SIZE THIRD ANGLE PROJECTION B 3	MX-K AL/CU 35 PRODUCT CUST MATERIAL NUMBER SEE CHART	COMER DRAWING CUSTOMER CUSTOMER PSD 000 1 OF 1	A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

201606-0693 201606-0692