

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0622018781

Status:

Active

Overview:

Application Tooling

Description:

Backplane Press-In Tool


Documents:

RoHS Certificate of Compliance (PDF)

General	
Product Family	Application Tooling
Series	207123
Comments	See Tooling Specification (PDF) Above
Function	Insertion
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Overview	Application Tooling
Product Name	Impact
Tool Type	Press-Fit Insertion Tool
UPC	884982282124
Warranty Disclaimer	CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Reference - Drawing Numbers	
Application Tooling Documents	ATS-622018781



Series image - Reference only

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per -ED/01/2018 (15 January 2018)	
Halogen-Free	
Status	
Not Relevant	
For more information, please visit Contact US	
China ROHS	Not Relevant
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

207123 Series

Use With

76165 Impact Backplane Signal Module Assembly, 3-Pair by 6 Column Assemblies

Application Tooling Description	FAQ Product #
Impact 100 Ohm 3 Pair Vertical Backplane Header, Unguided, Open Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free	1712921307
Impact 100 Ohm 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 6 Columns, 54 Circuits, Pin	1712921318

	Length 5.50mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free Impact 100 Ohm <u>1712921328</u> 3 Pair Vertical Backplane Header, Unguided, Dual Endwall, 6 Columns, 54 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Matte Tin, 0.254µm Gold Impact 100 Ohm <u>1712921338</u> 3 Pair Vertical Backplane Header, Unguided, Right Endwall, 6 Columns, 54 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free Impact 100 Ohm <u>1712923307</u> 3 Pair Vertical Backplane Header, Left Guided, Open Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free Impact 100 Ohm <u>1712925307</u> 3 Pair Vertical Backplane Header, Right Guided, Open Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free Impact 100 Ohm <u>761651304</u> 3 Pair Vertical Backplane Header, Unguided, Open Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm <u>761651307</u> 3 Pair Vertical Backplane Header, Unguided, Open Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free
--	--

Impact 100 Ohm	<u>761651308</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 5.50mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>761651316</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Left	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.50mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>761651317</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Left	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>761651318</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Left	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 5.50mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>761651323</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Dual	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.50mm,	
Plated Through Hole	
Dimension 0.46mm,	
Lead-Free	
Impact 100 Ohm	<u>761651324</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Dual	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.46mm,	
Lead-Free	
Impact 100 Ohm	<u>761651325</u>
3 Pair Vertical	
Backplane Header,	
Unguided, Dual	
Endwall, 6 Columns,	

54 Circuits, Pin
Length 5.50mm,
Plated Through Hole
Dimension 0.46mm,
Lead-Free
Impact 100 Ohm [761651326](#)
3 Pair Vertical
Backplane Header,
Unguided, Dual
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm [761651327](#)
3 Pair Vertical
Backplane Header,
Unguided, Dual
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead Free
Impact 100 Ohm [761651328](#)
3 Pair Vertical
Backplane Header,
Unguided, Dual
Endwall, 6 Columns,
54 Circuits, Pin
Length 5.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm [761651337](#)
3 Pair Vertical
Backplane Header,
Unguided, Right
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm [761651338](#)
3 Pair Vertical
Backplane Header,
Unguided, Right
Endwall, 6 Columns,
54 Circuits, Pin
Length 5.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm [761653304](#)
3 Pair Vertical
Backplane Header,
Left Guide, Open
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.46mm,
Lead-Free

	Impact 100 Ohm	<u>761653307</u>
	3 Pair Vertical	
	Backplane Header,	
	Left Guide, Open	
	Endwall, 6 Columns,	
	54 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>761653308</u>
	3 Pair Vertical	
	Backplane Header,	
	Left Guide, Open	
	Endwall, 6 Columns,	
	54 Circuits, Pin	
	Length 5.50mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Lead-Free	
	Impact 100 Ohm	<u>761653317</u>
	3 Pair Vertical	
	Backplane Header,	
	Left Guided, Open	
	Endwall, 6 Columns,	
	54 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Key Position A, Lead	
	Free	
	Impact 100 Ohm	<u>761653337</u>
	3 Pair Vertical	
	Backplane Header,	
	Left Guided, Open	
	Endwall, 6 Columns,	
	54 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Key Position C, Lead	
	Free	
	Impact 100 Ohm	<u>761653357</u>
	3 Pair Vertical	
	Backplane Header,	
	Left Guided, Open	
	Endwall, 6 Columns,	
	54 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Key Position E, Lead	
	Free	
	Impact 100 Ohm	<u>761653377</u>
	3 Pair Vertical	
	Backplane Header,	
	Left Guided, Open	
	Endwall, 6 Columns,	
	54 Circuits, Pin	
	Length 4.90mm,	
	Plated Through Hole	
	Dimension 0.39mm,	
	Key Position G, Lead	
	Free	

Impact 100 Ohm	<u>761655304</u>
3 Pair Vertical	
Backplane Header,	
Right Guide, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.46mm,	
Lead-Free	
Impact 100 Ohm	<u>761655307</u>
3 Pair Vertical	
Backplane Header,	
Right Guide, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>761655308</u>
3 Pair Vertical	
Backplane Header,	
Right Guide, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 5.50mm,	
Plated Through Hole	
Dimension 0.39mm,	
Lead-Free	
Impact 100 Ohm	<u>761655317</u>
3 Pair Vertical	
Backplane Header,	
Right Guided, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Key Position A, Lead	
Free	
Impact 100 Ohm	<u>761655337</u>
3 Pair Vertical	
Backplane Header,	
Right Guided, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Key Position C, Lead	
Free	
Impact 100 Ohm	<u>761655357</u>
3 Pair Vertical	
Backplane Header,	
Right Guided, Open	
Endwall, 6 Columns,	
54 Circuits, Pin	
Length 4.90mm,	
Plated Through Hole	
Dimension 0.39mm,	
Key Position E, Lead	
Free	
Impact 100 Ohm	<u>761655377</u>
3 Pair Vertical	

Backplane Header, Right Guided, Open Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Key Position G, Lead Free Impact 100 Ohm	<u>761657308</u>
3 Pair Vertical Backplane Header, Left Guide, Right Endwall, 6 Columns, 54 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free Impact 100 Ohm	<u>761657317</u>
3 Pair Vertical Backplane Header, Left Guided, Right Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Key Position A, Lead Free Impact 100 Ohm	<u>761657327</u>
3 Pair Vertical Backplane Header, Left Guided, Right Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Key Position B, Lead Free Impact 100 Ohm	<u>761657337</u>
3 Pair Vertical Backplane Header, Left Guided, Right Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Key Position C, Lead Free Impact 100 Ohm	<u>761659304</u>
3 Pair Vertical Backplane Header, Right Guide, Left Endwall, 6 Columns, 54 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free Impact 100 Ohm	<u>761659305</u>
3 Pair Vertical Backplane Header,	

Right Guide, Left
Endwall, 6 Columns,
54 Circuits, Pin
Length 5.50mm,
Plated Through Hole
Dimension 0.46mm,
Lead-Free
Impact 100 Ohm [761659307](#)
3 Pair Vertical
Backplane Header,
Right Guide, Left
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm [761659308](#)
3 Pair Vertical
Backplane Header,
Right Guide, Left
Endwall, 6 Columns,
54 Circuits, Pin
Length 5.50mm,
Plated Through Hole
Dimension 0.39mm,
Lead-Free
Impact 100 Ohm [761659317](#)
3 Pair Vertical
Backplane Header,
Right Guided, Left
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Key Position A, Lead
Free
Impact 100 Ohm [761659327](#)
3 Pair Vertical
Backplane Header,
Right Guided, Left
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Key Position B, Lead
Free
Impact 100 Ohm [761659337](#)
3 Pair Vertical
Backplane Header,
Right Guided, Left
Endwall, 6 Columns,
54 Circuits, Pin
Length 4.90mm,
Plated Through Hole
Dimension 0.39mm,
Key Position C, Lead
Free

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[62201-8781](#)