

EV3309-QG-00A 40mA, Synchronous Boost White LED Driver with I²C Interface Evaluation Board

DESCRIPTION

The EV3309-QG-00A is designed for the MP3309, a WLED driver. The device has a 2.7V to 5.5V input voltage range and uses peak current mode control to regulate the LED current sensed through an external, low-side resistor. Synchronous rectification and the 200mV feedback voltage reduce power loss and PCB size. To save driver losses, select non-synchronous mode by using an internal register to disable the rectifier MOSFET.

The MP3309 features a configurable switching frequency to optimize efficiency. It supports both analog and PWM dimming.

In addition, the MP3309 has LED open protection, cycle-by-cycle current limit protection, under-voltage protection (UVP), and thermal shutdown protection. The I²C interface can set the protection indication bits and the over-voltage protection (OVP) threshold.

The MP3309 is available in a QFN-10 (1.4mmx1.8mm) package

ELECTRICAL SPECIFICATIONS

Parameter	Symbol	Value	Units
Input voltage	Vin	2.7 to 5.5	V
Output voltage	VLED	<35	V
LED current	ILED	40	mA

FEATURES

- 2.7V to 5.5V Input Voltage Range
- Analog and PWM Dimming
- Selectable Synchronous or Non-Synchronous Mode
- 400kHz I²C-Compatible Interface
- Digitally Set LED Current
- Configurable Switching Frequency
- Configurable Over-Voltage Protection (OVP)
 Threshold
- Low 200mV Feedback Voltage with ±1% Accuracy
- Software or Hardware Enable Function
- Internal Soft Start
- Under-Voltage Lockout (UVLO), Thermal Shutdown, and Over-Current Protection (OCP)
- The MP3309 Supports Default Analog Dimming (PWMH) via the External PWM Signal Input
- The MP3309C Provides a Default I²C Interface
- Available in a QFN-10 (1.4mmx1.8mm) Package

APPLICATIONS

- Feature Phones and Smartphones
- Tablets
- <10inch Video Displays

All MPS parts are lead-free, halogen-free, and adhere to the RoHS directive. For MPS green status, please visit the MPS website under Quality Assurance. "MPS", the MPS logo, and "Simple, Easy Solutions" are registered trademarks of Monolithic Power Systems, Inc. or its subsidiaries.



EV3309-QG-00A - 40mA, SYNCHRONOUS WLED DRIVER EVAL BOARD

EV33309-QG-00A EVALUATION BOARD





LxWxH (5cmx4.6cmx1.0cm)

Board Number	MPS IC Number	
EV3309-QG-00A	MP3309GQG	



QUICK START GUIDE

- 1. Place a voltage source (2.7 to 5.5V) between the VIN terminal and GND.
- 2. Connect the LED strings between LED+ and LED-.
- 3. Set the dimming mode.

Analog Dimming

- 1. Pull the EN/PWML pin to logic high. To select analog dimming for different ICs, follow the instructions below:
 - a. MP3309: the default analog dimming is set by an external PWM input. For analog dimming, connect the SCL and SDA pins together to act as PWMH, then add a >20kHz PWM signal to PWMH.
 - b. MP3309C: the MP3309C can work with the I²C interface. Control the dimming via register 00h, bits[D0:D4]. Set the EN bit to 1 before dimming.

PWM Dimming

- 1. Connect the SCL and SDA pins together, then pull these pins to logic high.
- 2. Apply a 200Hz to 2kHz PWM signal to the EN/PWML pin.
- 3. To select the output current using a resistor on the FB pin, see the related IC datasheet for more details.



EV3309-QG-00A - 40mA, SYNCHRONOUS WLED DRIVER EVAL BOARD

EVALUATION BOARD SCHEMATIC



Figure 1: Evaluation Board Schematic



Qty	Ref	Value	Description	Package	Manufacturer	Manufacturer P/N
1	C1	10µF	Ceramic capacitor, 6.3V, X7R	0805	Murata	GCM21BR70J106KE2
1	C2	10nF	Ceramic capacitor, 50V, X7R	0603	Murata	GRM188R71H103KA0 1D
1	C3	1µF	Ceramic capacitor, 50V, X7R	1206	Murata	GRM31MR71H105KA8 8L
1	C4	1µF	Ceramic capacitor, 6.3V, X5R	0603	Murata	GRM188R60T105KA01 D
1	D1	NC				
1	L1	10µH	Inductor, 1.14A, DCR = 59mΩ	SMD	Toko	D63LCB-A921CY- 100M=P3
2	R1, R6	0Ω	Resistor, 0Ω, 5%	0603	Yageo	RC0603JR-070RL
1	R10	10Ω	Resistor, 10Ω, 1%	0603	Yageo	RC0603FR-0710RL
3	R2, R3, R9	NC				
2	R5, R7	200kΩ	Resistor, 200kΩ, 1%	0603	Yageo	RC0603FR-07200KL
1	R4	10kΩ	Resistor, 10kΩ, 1%	0603	Yageo	RC0603FR-0710KL
1	R8	4.99Ω	Resistor, 4.99Ω, 1%	0603	Yageo	RC0603FR-074R99L
1	U1	MP3309	White LED driver	QFN-10 (1.4mmx 1.8mm)	MPS	MP3309GQG

EV3309-RT-00A BILL OF MATERIALS



EVB TEST RESULTS

Performance waveforms are tested on the evaluation board. V_{IN} = 3.6V, 8 LEDs in series, I_{LED} = 40mA, L = 10µH, T_A = 25°C, unless otherwise noted.













EV3309-QG-00A Rev. 1.2 2/25/2021 MPS Pr



PCB LAYOUT



Figure 2: Top Layer



Figure 3: Bottom Layer



EV3309-QG-00A - 40mA, SYNCHRONOUS WLED DRIVER EVAL BOARD

Revision History

Revision #	Revision Date	Description	Pages Updated
1.0	06/19/2014	Initial Release	-
1.1	03/13/2015	EVB waveforms added	P6
1.2	02/24/2021	Grammar review	All

Notice: The information in this document is subject to change without notice. Please contact MPS for current specifications. Users should warrant and guarantee that third-party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Monolithic Power Systems (MPS):

EV3309-QG-00A