Note: This datasheet may be out of date Please download the latest datasheet of DLW5BTM142TQ2#from the official website of Murata Manufacturing

### DLW5BTM142TQ2#

"#" indicates a package specification code.







< List of part numbers with package codes > DLW5BTM142TQ2K DLW5BTM142TQ2L DLW5BTM142TQ2B




# Appearance & Shape



# Packaging Information





Packaging	Specifications	Minimum Order Quantity
К	330mm Embossed Tape	2500
L	180mm Embossed Tape	700
В	Bulk(Bag)	100



Other Usage

For general

1 of 4

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



#### Note: This datasheet may be out of date. Please download the latest datasheet of DLW5BTM142TQ2#from the official website of Murata Manufacturing Co., Ltd.

### DLW5BTM142TQ2#

"#" indicates a package specification code.



#### Features

- 1. Low profile (h=2.5mm)
- 2. Small size (5.0x5.0mm) and high rated current
- 3. High common mode Impedance (max. 1400 ohm, at 100MHz)
- 4 ·Operating Temperature Range -40°C to +105°C

### **Applications**

Noise suppression for power line

- 1. Power line equipment
  - -DC-DC converters
  - -Battery chargers
- 2. Portable equipment
  - -PDAs (Personal Digital Assistants)
  - -Note PCs
  - -Printers

2 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



#### Note: This datasheet may be out of date ${\bf Please\ download\ the\ latest\ data sheet\ of\ DLW5BTM142TQ2\# from\ the\ official\ website\ of\ Murata\ Manufacturing}$ Co., Ltd.

### DLW5BTM142TQ2#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	5050
Size Code (in inch)	2020
Length	5.0mm
Length Tolerance	±0.3mm
Width	5.0mm
Width Tolerance	±0.3mm
Thickness	2.35mm
Thickness Tolerance	±0.15mm
Common Mode Impedance (at 100MHz)	1400Ω
Common Mode Impedance (at 100MHz) Tolerance	(Тур.)
Common Mode Impedance (at 10MHz)	100Ω
Common Mode Impedance (at 10MHz) Tolerance	min.
Rated Current	2A
Derating of Rated Current	Yes(Over 85°C) *For details, please check the derating diagram.
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
DC Resistance(max.)	0.056Ω
DC Resistance	0.056Ω max.
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 105°C

Mass(typ.)	0.21g
Number of Circuit	1
Operating Temperature Range(Self-temperature rise is included)	No

3 of 4

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





muRata URL : https://www.murata.com/

### DLW5BTM142TQ2#

"#" indicates a package specification code.









Impedance-Frequency Characteristics

In operating temperature exceeding +85°C, derating of current is necessary for DLW5BT series (105 degree C available type). Please apply the derating curve shown in chart according to the operating temperature.

Derating of Rated Current



Impedance-Frequency Characteristics (Main Items)



**Derating of Rated Current** 

**Equivalent Circuit** 

4 of 4

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

### Murata:

DLW5BTM142TQ2L DLW5BTM142TQ2K