
Product Search Data Sheet



LFB182G45SG9A293

In Production Recommended RoHS REACH





(in mm)



Note: This datasheet may be out of date

Co., Ltd.

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Please download the latest datasheet of LFB182G45SG9A293 from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=LFB182G45SG9A293

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Available in the 2400MHz to 2500MHz frequency range.

## Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Paper Tape	4000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

LFB182G45SG9A293

Note: This datasheet may be out of date

Please download the latest datasheet of LFB182G45SG9A293 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=LFB182G45SG9A293

# Specifications

Applications	WLAN BT	
Nominal Center Frequency(fo)	2450.00MHz	
Bandwidth(BW)	fo±50.00MHz	
Insertion Loss in BW I)	2.40dB max. (at 25°C)	
Insertion Loss in BW II)	2.70dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	24.5dB min. at 880.00 to 960.00MHz	
Attenuation(Absolute Value) II)	20.0dB min. at 1710.00 to 1990.00MHz	
Attenuation(Absolute Value) III)	8.5dB min. at 2170.00MHz	
Attenuation(Absolute Value) IV)	15.5dB min. at 4800.00 to 5000.00MHz	
Attenuation(Absolute Value) V)	20.0dB min. at 7200.00 to 7500.00MHz	
Ripple(max.)	1.5dB	
VSWR(max.)	2.1	
Characteristic Impedance(Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40℃ to 85℃	
L x W (size)	1.60x0.80mm	
Thickness(max.)	0.7mm	

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




# LFB182G45SG9A293


Note: This datasheet may be out of date.

Please download the latest datasheet of LFB182G45SG9A293 from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=LFB182G45SG9A293







**Frequency Characteristics** 

Spurious Response

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: LFB182G45SG9A293