


Product Search Data Sheet


Note: This datasheet may be out of date Please download the latest datasheet of LFD21892MDP1A141 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=LFD21892MDP1A141

LFD21892MDP1A141

In Production Recommended RoHS REACH







Adiplexer branching low and high band.

- 1. Low insertion loss.
- 2. Small size, low-profiled and light weight.
- 3. Absolutely no adjustment required.
- 4. Reflow solderable.



Packaging	Specifications	Minimum Order Quantity
-	180mm Embossed Tape	4000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

LFD21892MDP1A141

Note: This datasheet may be out of date

Please download the latest datasheet of LFD21892MDP1A141 from the official website of Murata Manufacturing Co., Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=LFD21892MDP1A141

Specifications

Applications	GSM	Thickness(max
Center Frequency{P1}(f1)	1850.00MHz	
Frequency Range{P1}(f1)	1710.00MHz to 1990.00MHz	
Center Frequency{P2}(f2)	892.00MHz	
Frequency Range{P2}(f2)	824.00MHz to 960.00MHz	
Insertion Loss I)(P1-P3 in f1)	0.60dB max. (at 25°C)	
Insertion Loss II)(P1-P3 in f1)	0.70dB max. (-40 to +85°C)	
Insertion Loss I)(P2-P3 in f2)	0.40dB max. (at 25°C)	
Insertion Loss II)(P2-P3 in f2)	0.50dB max. (-40 to +85°C)	
Attenuation{P1-P3}(in f2)	19.0dB min.	
Attenuation{P2-P3}(in f1)	17.0dB min.	
VSWR{P1}(in f1)	2.00 max.	
VSWR{P2}(in f2)	1.70 max.	
VSWR{P3}(in f1,f2)	2.00 max.	
Power Capacity	3W	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	2.00x1.25mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




LFD21892MDP1A141


Note: This datasheet may be out of date.

Please download the latest datasheet of LFD21892MDP1A141 from the official website of Murata Manufacturing Co., Ltd.


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=LFD21892MDP1A141








Attenuation(P2-P3), VSWR(P3)





Attenuation(P1-P3), VSWR(P3)





Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



3 of 3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: LFD21892MDP1A141