

Note: This datasheet may be out of date. Please download the latest datasheet of BLM21PG220SH1# from the official website of Murata Manufacturing Co., Ltd. com/en/products/productdetail?partno=BLM21PG220SH1%23


BLM21PG220SH1#

"#" indicates a package specification code.



< List of part numbers with package codes > BLM21PG220SH1D BLM21PG220SH1J BLM21PG220SH1B







Packaging Information

Packaging	Specifications	Minimum Order Quantity
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000
В	Bulk(Bag)	1000

Applications

Automotive Usage

Powertrain/Safety

1 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention



Note: This datasheet may be out of date. Please download the latest datasheet of BLM21PG220SH1# from the official website of Murata Manufacturing Co., Ltd. com/en/products/productdetail?partno=BLM21PG220SH1%23

BLM21PG220SH1#

"#" indicates a package specification code.



The chip ferrite beads BLM series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground. The nickel barrier structure of the external electrodes provides excellent solder heat resistance. BLM_P series can be used in high current circuits due

to its low DC resistance.

2 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention



Note: This datasheet may be out of date. Please download the latest datasheet of BLM21PG220SH1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLM21PG220SH1%23

BLM21PG220SH1#

"#" indicates a package specification code.

Specifications

Shape	SMD	
Size Code (in mm)	2012	
Size Code (in inch)	0805	
Length	2.0mm	
Length Tolerance	±0.2mm	
Width	1.25mm	
Width Tolerance	±0.2mm	
Thickness	0.85mm	
Thickness Tolerance	±0.2mm	
Impedance (at 100MHz)	22Ω	
Impedance (at 100MHz) Tolerance	±25%	
Rated Current (at 85°C)	6A	
Rated Current (at 125°C)	3.3A	
DC Resistance(max.)	0.009Ω	
Operating Temperature Range	-55°C to 125°C	
Mass(typ.)	0.01g	
Number of Circuit	1	

3 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention




Note: This datasheet may be out of date. Please download the latest datasheet of BLM21PG220SH1# from the official website of Murata Manufacturing Co., Ltd. m/en/products/productdetail?partno=BLM21PG220SH1%23

"#" indicates a package specification code.

Product Data


BLM21PG220SH1#




Impedance-Frequency Characteristics

In operating temperature exceeding +85°C, derating of current is necessary for BLM21PG series. Please apply the derating curve shown in chart according to the operating temperature.

Derating of Rated Current







Equivalent Circuit

4 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: BLM21PG220SH1D