Note: This datasheet may be out of date

Please download the latest datasheet of NXRT15XV302FA5B030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NXRT15XV302FA5B030

NXRT15XV302FA5B030












Appearance & Shape







Applications

Limited Usage	Consumer Grade
Other Usage	Secondary battry 2. Temperature
	detection for charging 3. Temperature
	detection for DC fan motor 4.
	Temperature sensing for appliance 5.
	Selfstanding temperature sensing for
	fire detector



Packaging Information

Packaging		Standard Packing Quantity
В	Bulk(Bag)	500



Features

- 1. NXR series can accurately detect temperature with NCP15 series on the head of parts.
- 2. The insulation coat with polyulethane on the surface of lead wire : 100VDC.
- 3. You can choose NTC characteristics from NCP15 series.
- 4. The resistance drift is small in the reliability test.
- 5. The production capacity is bigger and NXR is produced in almost all automation line.
- 6. Adopt to Sb regulation

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of NXRT15XV302FA5B030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NXRT15XV302FA5B030

NXRT15XV302FA5B030



Specifications

	I	
Resistance (25°C)	3kΩ	
Resistance Value Tolerance	±1%	
(at 25°C)		
B-Constant (25/50°C)	3936K	
B-Constant (25/50°C)	±1%	
Tolerance	170	
B-Constant(25/80°C)	3971K	
(Reference Value)	007 IIX	
B-Constant(25/85°C)	3977K	
(Reference Value)		
B-Constant(25/100°C)	3989K	
(Reference Value)		
Maximum Operating Current	0.29mA	
(25°C)		
Rated Electric Power (25°C)	13.0mW	
Typical Dissipation Constant (25°C)	2.6mW/°C	
Thermal Time Constant	4s	
Operating Temperature Range	-40°C to 125°C	
Lead Shape	Insulation type	
Size Code (in mm)	030 = 30mm	
Size Code (in inch)	030 = 30mm	
Shape	Lead	
Mass	0.098g	

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XV302FA5B030 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=NXRT15XV302FA5B030

NXRT15XV302FA5B030



Product Data





Resistance-Temperature Characteristics

Temperature Tolenrance VS. Temp.

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

NXRT15XV302FA5B030