

DLW43MH201XK2#

Note: This datasheet may be out of date. Please download the latest datasheet of DLW43MH201XK2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DLW43MH201XK2%23

"#" indicates a package specification code.

For 100Base-T1




< List of part numbers with package codes > DLW43MH201XK2B DLW43MH201XK2K

DLW43MH201XK2L



Appearance & Shape





: Electrode (in mm)

3.2±0.2

Applications

Automotive Usage

Powertrain/Safety

Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	100
К	330mm Embossed Tape	2500
L	180mm Embossed Tape	500



Features

- 1. Small size: L4.5xW3.2xT2.7mm (EIAcode: 1812) Tolerance: 0.2mm
- 2. It realized common mode inductance of 200microH (at 0.1MHz) though it is small size.
- 3. Transfer mode conversion characteristics is properly improved.

Applications

Noise countermeasures for the automotive market, in particular for the vehicle LAN BroadR-Reach®

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

muKata OVATOR IN ELECTRONICS



DLW43MH201XK2#

Note: This datasheet may be out of date. Please download the latest datasheet of DLW43MH201XK2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DLW43MH201XK2%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in mm)	4532
Size Code (in inch)	1812
Length	4.5mm
Length Tolerance	±0.2mm
Width	3.2mm
Width Tolerance	±0.2mm
Thickness	2.7mm
Thickness Tolerance	±0.2mm
Rated Current	110mA
Derating of Rated Current	No
Rated Voltage	20Vdc
Withstanding Voltage	50Vdc
DC Resistance(max.)	4.5Ω
DC Resistance	4.5Ω max.
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 105°C
Mass(typ.)	0.16g
Number of Circuit	1
Common Mode Inductance	200µH-25%/+50% (at 0.1MHz)
Operating Temperature Range(Self-temperature rise is included)	No

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.








DLW43MH201XK2#


Note: This datasheet may be out of date. Please download the latest datasheet of DLW43MH201XK2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DLW43MH201XK2%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: DLW43MH201XK2L