

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of LFL15620MTC1C037 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFL15620MTC1C037

LFL15620MTC1C037












Appearance & Shape





A: Directional Input Mark

All the technical data and information contained herein are subject to change without prior notice



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Paper Tape	10000



Features

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Offering stable high selectivity up to very high frequency.

- 1. Low loss
- 2. Ultra-small, low-profiled, lightweight low-pass filters.
- 3. Ideal for removing high-frequency harmonics at power amplifier and IF stage.
- 4. Available in tape and reel packings for automatic mounting.
- 5. Absolutely no adjustment required.
- 6. Reflow solderable.
- 7. Center frequencies and responses are ready for customization. Samples are available in a short lead time.

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





LFL15620MTC1C037

Note: This datasheet may be out of date.

Please download the latest datasheet of LFL15620MTC1C037 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=LFL15620MTC1C037



Specifications

Applications	CDMA	
Nominal Center Frequency (fo)	620.00MHz	
Bandwidth(BW)	fo±150.00MHz	
Insertion Loss in BW I)	0.40dB max. (at 25°C)	
Insertion Loss in BW II)	0.50dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	28.0dB min. at 1920.00 to 1980.00MHz	
VSWR(max.)	1.7	
Characteristic Impedance (Nom.)	50Ω	
Power Capacity	3W	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	1.00x0.50mm	
Thickness(max.)	0.4mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of LFL15620MTC1C037 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=LFL15620MTC1C037

LFL15620MTC1C037



Product Data





Frequency Characteristics

Spurious Response

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

LFL15620MTC1C037