




RC5FR
le mate right-... XLS... bl... ne
REAN®




Article Variations

		Packaging
	Black plated housing, Silver plated contacts	Plastic bag [®]
	Black plated housing, Silver plated contacts	BULK
	RC5FR-BAG	Plastic bag
	RC5FR-B-D	BULK
	RC5FR-BAG-D	BULK

Technical Information

Product	
Title	RC5FR
Connection Type	XLR
Gender	female

Electrical	
Insulation Resistance	> 1.5 GΩ
Contact Resistance	≤ 5 mΩ
Rated Current	7.5 A

	
<div> <div></div> <div>REAN®</div> </div>	
Max. Tension	≤ 20 N
Cable Colour	4 - 7 mm
Wiresize	1.5 mm ²
Wiresize	16 AWG



REAN®

Ground Contact	Steel
Housing	Zinc
Button	Zinc
Rubber Ring	Rubber
Front Body	Zinc
Push Tube	PP
Cover	Zinc
Chuck	POM
Bushing	PA6+30%GF
Push Ring	POM
Boot	PVC
Jack	Sliver Plating
Ground Contact	Tin and Cer
Housing	Nickel Plating
Button	Nickel Plating
Front Body	Nickel Plating
Cover	Nickel Plating

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Neutrik:](#)

[RC5FR](#) [RC5FR-B](#) [RC5FR-BAG](#) [RC5FR-BAG-D](#) [RC5FR-B-D](#) [RC5FR-D](#)