



Snap-in Terminal Type


- Excellent in voltage holding property.
- Suitable for quick charge and discharge.
- Wide temperature range (−25°C to +60°C).
- Compliant to the RoHS directive (2011/65/EU, (EU)2015/863).




Specifications

Item	Performance Characteristics		
Category Temperature Range	− 25 to +60°C		
Rated Voltage Range	2.5V		
Rated Capacitance Range	56 to 200F See Note		
Capacitance Tolerance	± 20% (20°C)		
Stability at Low Temperature	Capacitance (− 25°C) / Capacitance (+20°C) ×100 ≥ 70% ESR (− 25°C) / ESR (+20°C) ≤ 7		
ESR, DCR*	Refer to the table below (20°C). *DC internal resistance		
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 60°C.	Capacitance change	Within ±30% of the initial capacitance value
		ESR	300% or less than the initial specified value
Shelf Life	The specifications listed at right shall be met when the capacitors are restored to 20°C after storing the capacitors under no load for 2000 hours at 60°C.	Capacitance change	Within ±30% of the initial capacitance value
		ESR	300% or less than the initial specified value
Humidity Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 500 hours at 40°C 90%RH.	Capacitance change	Within ±30% of the initial capacitance value
		ESR	300% or less than the initial specified value
Marking	Printed with white color letter on black sleeve.		

Drawing



Type numbering system (Example : 2.5V 150F)



Dimensions

Rated Voltage (code)	Cap. (F)	Cap. code	ESR(mΩ) (at 1kHz)	DCR* Typical (mΩ)	Case size φD × L (mm)		
					φ 25 (A)	φ 30 (B)	φ 35 (C)
2.5V (0E)	56	566	70	50	25 × 40	30 × 30	
	68	686	60	45			35 × 30
	82	826	60	35	25 × 50	30 × 40	
	100	107	50	30			35 × 35
	120	127	50	25		30 × 50	35 × 40
	150	157	40	22			35 × 50
	200	207	30	16			35 × 50

Note :

The capacitance calculated from discharge time (ΔT) with constant current (i) after 30minute charge with rated voltage (2.5V).

The discharge current (i) is 0.01 × rated capacitance (F).
The discharge time (ΔT) measured between 2V and 1V with constant current.

The capacitance calculated bellow.

$$\text{Capacitance (F)} = i \times \Delta T$$

* The listed DCR value is typical and therefore not a guaranteed value.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

[JJC0E476MELA](#) [JJC0E826MELB](#) [JJC0E826MELA](#) [JJC0E686MELC](#) [JJC0E566MELB](#) [JJC0E566MELA](#)
[JJC0E476MELZ](#) [JJC0E396MELZ](#) [JJC0E396MELC](#) [JJC0E396MELA](#) [JJC0E338MSEJBN](#) [JJC0E336MELC](#)
[JJC0E336MELA](#) [JJC0E477MSECBN](#) [JJC0E157MELC](#) [JJC0E278MSEHBN](#) [JJC0E186MELA](#) [JJC0E108MSEFBN](#)
[JJC0E276MELB](#) [JJC0E228MSEHBN](#) [JJC0E226MELB](#) [JJC0E188MSEGBN](#) [JJC0E158MSEGBN](#) [JJC0E156MELZ](#)
[JJC0E128MSEFBN](#) [JJC0E127MELB](#) [JJC0E107MELC](#) [JJC0E127MELC](#) [JJC0E276MELZ](#) [JJC0E108MSEFBB](#)
[JJC0E128MSEFBB](#) [JJC0E158MSEGBB](#) [JJC0E188MSEGBB](#) [JJC0E228MSEHBB](#) [JJC0E278MSEHBB](#)
[JJC0E338MSEJBB](#) [JJC0E477MSEC](#)