



MALE

A04	A05	A08	D04	B05

NOTE:

MATERIAL

M12 INSULATOR
CONTACT
NUT

PA66, UL94V-0, BLACK
GOLD FLASH PLATED BRASS
NICKEL PLATED BRASS

ELECTRICAL

RATED CURRENT
VOLTAGE
INSULATOR RESISTANCE
CONTACT RESISTANCE
MATING CYCLES

2A(8P) / 4A(4/5P)
30V(8P) / 60V(5P) / 250V(4P)
100 MOhms MIN.
10 mOhms MAX.
100 CYCLES MIN

ENVIRONMENT

OPERATION TEMPERATURE
IP RATING

-40°C TO +85°C
IP66

RECOMMENDED TORQUE

0.4Nm TO 0.8Nm

SERIES 858FYYY-103RBU1
 858F' = M12 FIELD INSTALLABLE
 CONTACT ARRANGEMENT
 A04 = 4P A-CODE
 A05 = 5P A-CODE
 A08 = 8P A-CODE
 D04 = 4P D-CODE
 B05 = 5P B-CODE
 GENDER
 1 = MALE
 CABLE OD
 B = 6mm-8mm OD
 CONTACT PLATING
 1 = GOLD FLASH

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

02/04/2022

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE:

NTS

SHEET

OF

1

1

REV

1

DWG NO.

858FYYY-103RBU1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NorComp:

[858FA04-103RBU1](#) [858FA05-103RBU1](#) [858FA08-103RBU1](#) [858FB05-103RBU1](#) [858FD04-103RBU1](#)