


NΠΤΕ: MATERIAL HOUSING: PBT UL94V-0, BLACK CONTACT: BRASS NUT: BRASS □-RING: EPDM, BLACK SHELL: BRASS FINISH CONTACT: GOLD PLATED □VER 504" NICKEL NUT: NICKEL PLATED SHELL: BRIGHT TIN PLATED ELECTRICAL RATED CURRENT: 4A RATED VOLTAGE: 60V INSULATION RESISTANCE: 100 MOhms MIN. CONTACT RESISTANCE: 10 mOhms MAX. IP67 WATER PROOF: **ENVIRONMENT** -40°C TD +85°C OPERATION TEMPERATURE: MAX WIRE AWG: 22

#### 858-005-103RSSY

3 = BRASS/TIN (B/T) SHELL & BRASS/NICKEL NUT—— S = STAINLESS STEEL (SS) SHELL & NUT

T = B/T SHELL / SS NUT

1 = GOLD FLASH — 4 = 10u″ GOLD



# RoHS COMPLIANT

UNITS = INCHES [MM]

#### DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: M. SIGMON	DATE: 03-07-16

NorComp
---------

SCALE:	SHEET OF	REV			
NTS	1 1	3			
DWG NO.	358-005-103RSSY				

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

### NorComp:

858-005-103RSS1 858-005-103RSS4