

# **Engineering/Process Change Notice**

**ECN/PCN No.: R0053** 

For Manufacturer							
Product Description:	Abracon Part Numbe	r / Part Series:	☐ Documentation only ☐ Series				
SMD 418.0MHz SAW FILTER	AFS41	8S3	□ ECN	☑ Part Number			
			⊠ EOL				
Affected Revision:	New Revision:		Application:	☐ Safety			
Rev A	EO	L		⋈ Non-Safety			
Prior to Change:							
N/A							
After Change:							
EOL							
Cause/Reason for Change:  Due to low demand this part is discontinue	rd						
Due to low demand this part is discontinued.							
Change Plan							
Effective Date:	Additional Remarks:						
06/28/2021	N/A						
Change Declaration: EOL							
Issued Date:	Issued By:		Issued Department:				
06/28/2021	Nicholas El-Takach		Engineering				
Approval:	Approval:		Approval:				
Syed Raza	Reuben Quintanilla		Ying Huang				
Engineering VP	Quality Director Purchasing Director		ector				
For Abracon EOL only							
Last Time Buy (if applicable):  Alternate Part Number / Part Series:							
No last time buy.			N/A				
Additional Approval:	Additional Approval:		Additional Approval:				
	Customer Approv	val (If Applicable)					
Qualification Status:							
	☐ Approved ☐	Not accepted					
Note: It is considered approved if there is no feedback from the customer 1 month after ECN/PCN is released.							
Customer Part Number:		<b>Customer Project:</b>					
Company Name:	Company Representative:		Representative Signature:				
Customer Remarks:							

Form #7020 | Rev. G | Effective: 02/22/2021 |













## SMD 418.0MHz SAW FILTER



**APPLICATION:** Automotive Electronics/Remote Control



#### > STANDARD SPECIFICATIONS:

CHARACTERISTICS	UNIT	MIN.	TYP.	MAX.
Center Frequency Fc	MHz	-	418	-
Bandwidth	MHz	-	Fc + 2.0	-
Insertion Loss @ Passband	dB	-	-	4.5
Ripple @ Passband	dB	-	-	2
Relative Attenuation				
Fc-100 ~ Fc-40.8 MHz	dB	55		-
Fc+40.8 ~ Fc+100 MHz	dB	55		-
DC Voltage	V		10	
Source Power	dBm	0		
Operating Temperature	°C	-10°C to +50°C		
Storage Temperature	°C	-45°C to +85°C		
Terminating Impedance	-	150Ω/0 pF		


Electrostatic Sensitive Device. Handle with precaution.


#### > MARKING:


- -418.00
- (418.0 Frequency in MHz) - AF ZYX (ZY: Date code Z for month from A to L; Y for year, I.e. 4 for 2004 X: Traceability code)

PIN NO.	CONNECTIONS		
2	Input		
5	Output		
All Others	Ground		

### > OUTLINE DRAWING: 0.15±.008







Please refer to ABRACON's Chip Inductor Series AISC-0603 for Test Inductors





## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

AFS868.35S3 AFS418S3