SMD ONE PORT 303.825 MHz SAW RESONATOR

ASR303.825E




> STANDARD SPECIFICATIONS:


CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.
Center Frequency Fo			MHz	303.75	303.825	303.9
Tolerance from Fo		KHz		±75		
Insertion Loss		dB	-	1.3	2.5	
Quality Factor	Unloaded		-		12,000	
	50 Ω loaded				2,000	
Temperature Stability	Turnover Temperature		°C		39.0	
	Turnover Frequency		KHz		Fo	
	Freq. Temp. Coefficient		ppm/°C ²		0.032	
Frequency Aging			ppm/year		<±10	
DC Insulation Resistance			MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁		Ω		12	19
	Motional Inductance L ₁		μH		94.0	
	Motional Capacitance C1		fF		2.9	
	Shunt Capacitance C ₀		рF	2.7	3.0	3.3
Operating temp.		°C		-40°C to +85°C		
Storage temp.		°C		-45°C to +85°C		
Max. Rating	DC voltage	V ±10				
RF Power Dissipation		dBm	0			


Data measured with: Source Impedance: $Zs=50\Omega$, Load Impedance: $ZL=50\Omega$, TA=25°C Electrostatic Sensitive Device. Handle with precaution.


▷ MARKING:




X: Traceability code)







> OUTLINE DRAWING:



ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.





30332 Esperanza, Rancho Santa Margarita, California 92688 tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

ASR303.875A01-SD02 ASR303.875A01-SD01 ASR304.50A01-SD02 ASR303.875B01-SD02 ASR303.825E-T