SMD ONE PORT 433.92 MHz SAW RESONATOR

ASR433.92E





> STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.
Center Frequency Fo			MHz	433.845	433.920	433.995
Tolerance from Fo			KHz		±75	
Insertion Loss			dB	-	1.3	2.0
Quality Factor	Unloaded		-		10,500	
	50Ω loaded				1,450	
Temperature Stability	Turnover Temperature		°C	25	40	55
	Turnover Frequency		KHz		Fc	
	Freq. Temp. Coefficient		ppm/°C ²		0.037	
Frequency Aging			ppm/year		±10	
DC Insulation Resistance			MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁		Ω		16	26
	Motional Inductance L ₁		μΗ		61.724	
	Motional Capacitance C ₁		fF		2.1817	
	Shunt Capacitance C ₀		pF	1.9	2.2	2.5
Operating temp.		°C	-40°C to +85°C			
Storage temp.		°C	-45°C to +85°C			
Max. Rating	DC voltage V		±10			
RF Power Dissipation		dBm	10			

Data measured with: Source Impedance: Zs= 50Ω , Load Impedance: ZL= 50Ω , TA= 25° C Electrostatic Sensitive Device. Handle with precaution.

> MARKING:


- 433.92 - AR ZYX (433.92 Frequency in MHz) (ZY: Date code Z for month from A to L; Y for year,

I.e. 4 for 2004


X: Traceability code)

PIN NO.	CONNECTIONS		
2	Input/Output		
6	Output/Input		
4 & 8	Case Ground		
1,3,5,7	N/C		


> FREQUENCY RESPONSE:



> TEST CIRCUIT:



> OUTLINE DRAWING:



ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:
ASR433.92E-T