

Features

- HCMOS Output
- Stabilities to ± 20 PPM
- Temperature Ranges to -40°C to $+85^{\circ}\text{C}$
- Supply Voltage: 1.8V, 2.5V, 3.3V

1.8V ELECTRICAL CHARACTERISTICS	
PARAMETERS	MAX (Unless otherwise noted)
Frequency Range (F_0)	0.012 ~ 160.000MHz
Storage Temperature Range (T_{STG})	$-55 \sim +125^{\circ}\text{C}$
Supply Voltage (V_{DD})	$1.8\text{V} \pm 5\%$
Input Current (I_{DD})	
0.012 ~ 32.000MHz	5 mA
>32.000 ~ 70.000MHz	10 mA
>70.000 ~ 120.000MHz	15 mA
>120.000 ~ 160.000MHz	30 mA
Standby Current	10 μA
Output Symmetry (50% V_{DD})	40% ~ 60%
Rise/Fall Time (20%/80% V_{DD} Levels) (T_R/T_F)	
0.012 ~ 32.000MHz	5.0 nS
>32.000 ~ 120.000MHz	3.5 nS
>120.000 ~ 160.000MHz	3.0 nS
Output Voltage (V_{OL})	20% V_{DD}
(V_{OH})	80% V_{DD} Min
Output Load (HCMOS)	15pF
Start-up Time (T_S)	10 mS
Output Disable Time 1	300 nS
Output Enable Time 1	10 mS

ENABLE / DISABLE FUNCTION	
Pin ¹	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{IH} \geq 70\%V_{DD}$	Active
'0' Level $V_{IL} \leq 30\%V_{DD}$	High Z

Available Options by Stability & Operating Temp for 1.8V		
Frequency Stability	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM ²	-10 ~ +70	0.012 ~ 160.000
±100PPM ²	-20 ~ +70	0.012 ~ 160.000
±100PPM ²	-40 ~ +85	0.012 ~ 160.000
±50PPM ²	-10 ~ +70	0.012 ~ 160.000
±50PPM ²	-20 ~ +70	0.012 ~ 160.000
±50PPM ²	-40 ~ +85	0.012 ~ 160.000
±25PPM ²	-10 ~ +70	0.012 ~ 160.000
±25PPM ²	-20 ~ +70	0.012 ~ 160.000
±25PPM ³	-40 ~ +85	0.012 ~ 160.000
±20PPM ³	-10 ~ +70	0.012 ~ 160.000
±20PPM ³	-20 ~ +70	0.012 ~ 160.000

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, Reflow, and one-year aging.

³ Inclusive of 25°C tolerance and operating temperature rang.

2.5V ELECTRICAL CHARACTERISTICS	
PARAMETERS	MAX (Unless otherwise noted)
Frequency Range (F_0)	0.012 ~ 170.000MHz
Storage Temperature Range (T_{STG})	-55 ~ +125°C
Supply Voltage (V_{DD})	2.5V±5%
Input Current (I_{DD})	
0.012 ~ 32.000MHz	7 mA
>32.000 ~ 50.000MHz	12 mA
>50.000 ~ 125.000MHz	26 mA
>125.000 ~ 160.000MHz	35 mA
>160.000 ~ 170.000MHz	40 mA
Standby Current	10 μ A
Output Symmetry (50% V_{DD})	
0.012 ~ 50.000MHz	45% ~ 55%
>50.000 ~ 200.000MHz	40% ~ 60%
Rise/Fall Time (10%/90% V_{DD} Levels) (T_R/T_F)	5 nS
Output Voltage (V_{OL})	10% V_{DD}
(V_{OH})	90% V_{DD} Min
Output Load (HCMOS)	15pF
Start-up Time (T_S)	10 mS
Output Disable Time 1	150 nS
Output Enable Time 1	10 mS

ENABLE / DISABLE FUNCTION	
Pin ¹	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{IH} \geq 70\%V_{DD}$	Active
'0' Level $V_{IL} \leq 30\%V_{DD}$	High Z

Available Options by Stability & Operating Temp for 2.5V		
Frequency Stability	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM ²	-10 ~ +70	0.012 ~ 170.000
±100PPM ²	-20 ~ +70	0.012 ~ 170.000
±100PPM ²	-40 ~ +85	0.012 ~ 170.000
±50PPM ²	-10 ~ +70	0.012 ~ 170.000
±50PPM ²	-20 ~ +70	0.012 ~ 170.000
±50PPM ²	-40 ~ +85	0.012 ~ 170.000
±25PPM ²	-10 ~ +70	0.012 ~ 170.000
±25PPM ²	-20 ~ +70	0.012 ~ 170.000
±25PPM ³	-40 ~ +85	0.012 ~ 170.000
±20PPM ³	-10 ~ +70	0.012 ~ 170.000
±20PPM ³	-20 ~ +70	0.012 ~ 170.000

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, Reflow, and one-year aging.

³ Inclusive of 25°C tolerance and operating temperature rang.

3.3V ELECTRICAL CHARACTERISTICS	
PARAMETERS	MAX (Unless otherwise noted)
Frequency Range (F_0)	0.012 ~ 170.000MHz
Storage Temperature Range (T_{STG})	-55 ~ +125°C
Supply Voltage (V_{DD})	3.3V±10%
Input Current (I_{DD})	
0.012 ~ 0.040MHz	3 mA
>0.040 ~ 1.500MHz	6 mA
>1.500 ~ 32.000MHz	15 mA
>32.000 ~ 50.000MHz	20 mA
>50.000 ~ 67.000MHz	25 mA
>67.000 ~ 170.000MHz	40 mA
Standby Current	10 μ A
Output Symmetry (50% V_{DD})	
0.012 ~ 50.000MHz	45% ~ 55%
>50.000 ~ 170.000MHz	40% ~ 60%
Rise/Fall Time (10%/90% V_{DD} Levels) (T_R/T_F)	
0.012 ~ 80.000MHz	6 nS
>80.000 ~ 125.000MHz	4 nS
>125.000 ~ 170.000MHz	3 nS
Output Voltage (V_{OL})	10% V_{DD}
(V_{OH})	90% V_{DD} Min
Output Load (HCMOS)	15pF
Start-up Time (T_S)	10 mS
Output Disable Time 1	150 nS
Output Enable Time 1	10 mS


ENABLE / DISABLE FUNCTION	
Pin ¹	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{IH} \geq 70\%V_{DD}$	Active
'0' Level $V_{IL} \leq 30\%V_{DD}$	High Z

Available Options by Stability & Operating Temp for 3.3V		
Frequency Stability	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM ²	-10 ~ +70	0.012 ~ 170.000
±100PPM ²	-20 ~ +70	0.012 ~ 170.000
±100PPM ²	-40 ~ +85	0.012 ~ 170.000
±50PPM ²	-10 ~ +70	0.012 ~ 170.000
±50PPM ²	-20 ~ +70	0.012 ~ 170.000
±50PPM ²	-40 ~ +85	0.012 ~ 170.000
±25PPM ²	-10 ~ +70	0.012 ~ 170.000
±25PPM ²	-20 ~ +70	0.012 ~ 170.000
±25PPM ³	-40 ~ +85	0.012 ~ 170.000
±20PPM ³	-10 ~ +70	0.012 ~ 170.000
±20PPM ³	-20 ~ +70	0.012 ~ 170.000

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, Reflow, and one-year aging.

³ Inclusive of 25°C tolerance and operating temperature rang.



STANDARD SPECIFICATIONS	
PARAMETERS	MAX (Unless otherwise noted)
Maximum Soldering Temp / Time	260°C / 10 Seconds x 2
Moisture Sensitivity Level (MSL) per J-STD-033	N/A
Termination Finish	Au (0.3~1μm) over Ni (1.27~8.89μm)
Seal Method	Seam
Lead (Pb) Free	Yes
RoHS Compliant	Yes, no exemptions
RERACH Compliant (latest version)	Yes


FO7HS

(Former F4500, F4400, F4100 Series)

7mm x 5mm
HCMOS SMD Oscillator



TAPE SPECIFICATIONS (mm)							REEL SPECIFICATIONS (mm)						
A	B	C	D	E	F	REEL QTY	G	H	I	J	K	L	M
ø1.5	4.0	8.0	7.5	16.0	2.15	-T1 = 1,000	2.0	ø13	ø21	ø80	ø255	17.5	2.0



* Not all frequencies in the frequency range, or every combination of stability, temp range, and voltage available.
See stabilities and op temps for each V_{DD} .

Available Options & Part Identification for HCMOS SMD Oscillator FO7HS*						
Sample PN: <u>FO7HSCBM25.0-T1</u>						
F	O7HS	C	B	M	25.0	-T1
<u>Fox</u>	<u>Model Number</u>	<u>Voltage</u> B = 3.3V±5% C = 3.3V±10% H = 2.5V±5% K = 1.8V±5%	<u>Stability</u> A = ±100PPM B = ±50PPM D = ±25PPM E = ±20PPM	<u>Operating Temperature</u> E = -10 to +70°C F = -20 to +70°C M = -40 to +85°C	<u>Frequency (MHz)</u>	<u>Values Added Options</u> Blank = Bulk T1 = 1,000 pcs

Reliability Test Conditions
Please contact Abracon Quality Assurance department

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

[FO7HSBFM16.0](#) [FO7HSCAE20.0-T1](#) [FO7HSCDE16.384-BULK](#) [FO7HSCDF18.432-BULK](#) [FO7HSCDM102.4-BULK](#)
[FO7HSCDM25.6-BULK](#) [FO7HSCDM37.056-BULK](#) [FO7HSCEE24.0-BULK](#) [FO7HSBFM16.0-T1](#) [FO7HSCAE16.0-](#)
[BULK](#) [FO7HSCAF60.0-BULK](#) [FO7HSCAM23.79021-T1](#) [FO7HSCBE0.057-BULK](#) [FO7HSCBE3.6864-BULK](#)
[FO7HSCBE60.0-T1](#) [FO7HSCBF20.0-BULK](#) [FO7HSCBF41.667-BULK](#) [FO7HSCBF75.0-BULK](#) [FO7HSCBF75.0-T2](#)
[FO7HSCBM15.0-BULK](#) [FO7HSCBM41.5-T2](#) [FO7HSCDM125.0-BULK](#) [FO7HSCDM3.6864-BULK](#)
[FO7HSCDM33.3333-BULK](#) [FO7HSCDM74.1758-BULK](#) [FO7HSBFM16.0-BULK](#) [FO7HSBFM16.0-T2](#) [FO7HSCAE16.0-](#)
[T1](#) [FO7HSCBE0.057-T1](#) [FO7HSCBE60.0-T2](#) [FO7HSCBF20.0-T1](#) [FO7HSCBE106.25-BULK](#) [FO7HSCBE32.768-](#)
[BULK](#) [FO7HSCBE60.0-BULK](#) [FO7HSCBM22.4-BULK](#) [FO7HSCBM24.5454-BULK](#) [FO7HSCBM32.74-T1](#)
[FO7HSCBM41.0-T1](#) [FO7HSCDE32.768-BULK](#) [FO7HSCDM32.768-BULK](#) [FO7HSCDM75.0-T1](#) [FO7HSCBM75.0-](#)
[BULK](#) [FO7HSCDE32.0-T1](#) [FO7HSCDE32.74-BULK](#) [FO7HSCDE58.9824-BULK](#) [FO7HSCDM148.5-T1](#)
[FO7HSCDM66.666-BULK](#) [FO7HSCEF4.604-BULK](#) [FO7HSCDM19.44-BULK](#) [FO7HSCEE40.0-BULK](#)
[FO7HSCEE44.736-BULK](#) [FO7HSCAE14.31818-T1](#) [FO7HSCAE3.6864-BULK](#) [FO7HSCBM41.5-BULK](#)
[FO7HSCBM72.0-BULK](#) [FO7HSCDE2.048-BULK](#) [FO7HSCDE32.0-T2](#) [FO7HSCEE19.44-BULK](#) [FO7HSCBE10.0-](#)
[BULK](#) [FO7HSCBE10.0-T2](#) [FO7HSCBF20.0-T2](#) [FO7HSCBM0.25-T1](#) [FO7HSCBM12.288-BULK](#) [FO7HSCBM32.74-](#)
[BULK](#) [FO7HSCBM32.74-T2](#) [FO7HSCBM32.768-BULK](#) [FO7HSCBM41.0-BULK](#) [FO7HSCBM41.0-T2](#)
[FO7HSCAE8.192-T1](#) [FO7HSCBE128.0-BULK](#) [FO7HSCBF125.0-T2](#) [FO7HSCBF48.0-T2](#) [FO7HSCBM25.000625-T1](#)
[FO7HSCBM36.72-BULK](#) [FO7HSCBM66.6667-BULK](#) [FO7HSCBM7.3728-BULK](#) [FO7HSCDE2.048-T1](#)
[FO7HSCDE66.666-BULK](#) [FO7HSCDE75.0-1-BULK](#) [FO7HSCDM12.288-BULK](#) [FO7HSCDE12.288-BULK](#)
[FO7HSCDF41.667-BULK](#) [FO7HSCDF9.376-BULK](#) [FO7HSCEE50.0-T1](#) [FO7HSCAE18.432-BULK](#) [FO7HSCAE24.75-](#)
[T1](#) [FO7HSCBM0.25-BULK](#) [FO7HSCBM0.25-T2](#) [FO7HSCDF62.5-BULK](#) [FO7HSCDM148.5-T2](#) [FO7HSCAM12.288-](#)
[BULK](#) [FO7HSCAM44.2368-BULK](#) [FO7HSCAM49.0908-BULK](#) [FO7HSCBE14.31818-T1](#) [FO7HSCBF125.0-T1](#)
[FO7HSCBF48.0-BULK](#) [FO7HSCBF48.0-T1](#) [FO7HSCBF50.0-T1](#) [FO7HSCBM25.000625-T2](#) [FO7HSCBM66.666-BULK](#)