

Features

- VCXO
- Supply Voltage: 3.3V

3.3V SPECIFICATIONS	
PARAMETERS	MAX (Unless otherwise noted)
Frequency Range	1.000~ 96.000 MHz
Temperature Range	
Operating (T _{OPR})	See Table
Storage (T _{STG})	-40°C ~ +85°C
Frequency Stability	(See options below)
Pull ability (V _C = 1.65V ± 1.5V)	(See options below)
Supply Voltage (V _{DD})	3.3V ± 5%
Control Voltage (V _C) ²	1.65V ± 1.5V
Input Current (I _{DD})	
1.0 ~ 30MHz	15 mA
>30.0 ~ 45MHz	25 mA
>45.0 ~ 96MHz	50 mA
Output Symmetry (50% V _{DD})	40% ~ 60%
Rise/Fall Time (10% ~ 90% V _{DD}) (T _R /T _F)	5 nS
Output Voltage (V _{OL})	10%V _{DD}
(V _{OH})	90%V _{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T _S)	10 mS
Enable/Disable Time ³	150 nS
Frequency Linearity	± 10%
Modulation Bandwidth	20 kHz Min

ENABLE / DISABLE FUNCTION	
Pin ¹	Output
OPEN ¹	Active
'1' Level V _{IH} ≥ 70%V _{DD}	Active
'0' Level V _{IL} ≤ 30%V _{DD}	High Z


Available Options by Stability & Operating Temp		
Frequency Stability	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM ²	-10 ~ +70	1.0 ~ 96.0
±100PPM ²	-40 ~ +85	1.0 ~ 96.0
±50PPM ²	-10 ~ +70	1.0 ~ 96.0
±50PPM ²	-40 ~ +85	1.0 ~ 96.0
±25PPM ²	-10 ~ +70	1.0 ~ 96.0
±25PPM ³	-40 ~ +85	1.0 ~ 96.0

¹ An internal pull-up resistor from pin 2 to pin 4 allows active output if pin 2 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, Vibration, reflow, and one-year aging and V_C=1.65V.

³ Inclusive of 25°C tolerance, operating temperature range and V_C=1.65V.

DIMENSIONS / MECHANICAL SPECIFICATIONS



Dimensions are in millimeters.

Pin Connections

#1 VC #4 Output
#2 E/D #5 N.C.
#3 GND #6 V_{DD}

Note:


*A 0.01μF capacitor should be placed between V_{DD} (Pin 6) and GND (Pin3) to minimize power supply line noise.

*Dimensional drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary.

STANDARD SPECIFICATIONS

PARAMETERS	MAX (Unless otherwise noted)
Maximum Soldering Temp / Time	260°C / 10 Seconds x 2
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au over Ni
Seal Method	Seam
Lead (Pb) Free	Yes
ROHS/REACH Compliant	Yes

TAPE SPECIFICATIONS (mm)							REEL SPECIFICATIONS (mm)						
A	B	C	D	E	F	REEL QTY	G	H	I	J	K	L	M
ø1.55	4.0	8.0	7.5	16.0	2.15	-T2 = 2,000 -T1 = 1,000	2.0	ø13	ø21	ø80	ø255	17.5	2.0



Available Options & Part Identification for HCMOS VCXO FY7H*
Sample PN: FY7HCJM27.0-T2

F	Y7H	C	J	M	27.0	-T2
Fox	Model Number	Voltage C = 3.3V±10%	Stability/Pullability E = ±25PPM/±50PPM F = ±50PPM/±50PPM H = ±25PPM/±100PPM J = ±50PPM/±100PPM K = ±100PPM/±100PPM	Operating Temperature E = -10 to +70°C M = -40 to +85°C	Frequency (MHz)	Values Added Options Blank = Bulk T1 = 1,000 pcs T2 = 2,000 pcs

* Not all frequencies in the frequency range, or every combination of stability, temp range, and voltage available.

Reliability Test Conditions

Please contact Abracon Quality Assurance department

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

[FY7HCJE35.328-T2](#) [FY7HCHE24.576-T2](#) [FY7HCJE12.288-T1](#) [FY7HCJE35.328-T1](#) [FY7HCJE27.0-T1](#)
[FY7HCJE3.584-T1](#) [FY7HCJE36.864-T1](#) [FY7HCJE36.864-T2](#) [FY7HCJE44.736-T1](#) [FY7HCJE10.0-T1](#) [FY7HCJE10.0-T2](#) [FY7HCJE44.736-BULK](#) [FY7HCJE3.584-BULK](#) [FY7HCJE3.584-T2](#) [FY7HCHE24.576-BULK](#) [FY7HCJE36.864-BULK](#) [FY7HCJE8.192-T1](#) [FY7HCHE24.576-T1](#) [FY7HCJE12.288-BULK](#) [FY7HCJE12.288-T2](#) [FY7HCJE8.192-BULK](#) [FY7HCJE10.0-BULK](#) [FY7HCJE27.0-T2](#) [FY7HCHM8.448-BULK](#) [FY7HCHM8.448-T1](#) [FY7HCHM32.768-T1](#) [FY7HCHM45.1584-BULK](#) [FY7HCJM45.1584-BULK](#) [FY7HCJM45.1584-T2](#) [FY7HCJM49.152-T1](#) [FY7HCJM45.1584-T1](#) [FY7HCJM49.152-BULK](#) [FY7HCJE24.576-BULK](#) [FY7HCJE24.576-T2](#) [FY7HCHM49.152-T2](#) [FY7HCJE24.576-T1](#) [FY7HCJE74.25-BULK](#) [FY7HCHM30.72-T1](#) [FY7HCHM32.768-BULK](#) [FY7HCJE74.25-T1](#) [FY7HCKM27.0-BULK](#) [FY7HCHM32.768-T2](#) [FY7HCHM30.72-T2](#) [FY7HCHM49.152-BULK](#) [FY7HCHM49.152-T1](#) [FY7HCHM30.72-BULK](#) [FY7HCJM49.152-T2](#) [FY7HCKM27.0-T2](#) [FY7HCHM8.448-T2](#)