

**Product Discontinuation
Notices**

December 1, 2010

RFID Systems

No. 2010297E

**Discontinuation Notice of Handy Terminal
model V680-A-7527S-G2 series****Product Discontinuation**

V680-A-7527S-G2-JP
V680-A-7527S-G2-JP-S
V680-A-7527S-G2-EG
V680-A-7527S-G2-EG-S

Recommended Replacement

V680-A-7527S-G3-JP
V680-A-7527S-G3-JP-S
V680-A-7527S-G3-EG
V680-A-7527S-G3-EG-S
(Release on January 2011)

Discontinuation date : The end of March, 2011**Caution on recommended replacement**

There is no change as follows;

- The brand of these products is PSION Teklogix.
- The software (Easy Access and CB Access) is preinstalled.
- The following products are compatible with V680-A-7527S-G3 series.
 - model V680-A-CA1053
 - model V680-A-WA3006
 - model V680-A-WA4003
 - model V680-A-WA6197

Difference from discontinued product

Model	Body Color	Dimensions	Wire connection	Mounting Dimensions	Characteristics	Operation ratings	Operation methods
V680-A-7527S-G3 series	*	**	**	-	*	-	*

** : Fully compatible

* : The change is a little/Almost compatible



-- : Not compatible

- : No corresponding specification

Product Discontinuation and recommended replacement

Product discontinuation	Recommended replacement
Model V680-A-7527S-G2-JP	Model V680-A-7527S-G3-JP
Model V680-A-7527S-G2-JP-S	Model V680-A-7527S-G3-JP-S
Model V680-A-7527S-G2-EG	Model V680-A-7527S-G3-EG
Model V680-A-7527S-G2-EG-S	Model V680-A-7527S-G3-EG-S

Body color

Product discontinuation	Recommendable replacement
 <p>The picture is Handy Terminal only. (The serial end-cap is not connected.)</p>	 <p>The picture is Handy Terminal only. (The serial end-cap is not connected.)</p>

Dimensions

Product discontinuation	Recommendable replacement
Height : 200mm Width : 100mm Depth : 42mm (The serial end-cap is not connected.)	Same as on the left

Wire Connection

Product discontinuation	Recommendable replacement
<p data-bbox="225 775 341 797">Top View</p>  <p data-bbox="225 1050 384 1075">Bottom View</p> 	<p data-bbox="839 770 1078 792">Same as on the left</p>

Characteristics

Product discontinuation	Recommendable replacement
OS : Windows CE 5.0	OS : Windows CE 5.0
Processor : Xscale PXA270 520MHz	Processor : Xscale PXA270 624MHz
Display : FullVGA 480×640 3.6inch	Display : FullVGA 480×640 3.7inch
Battery : standard battery 3.7V 3300mA/h	Battery : standard battery 3.7V 3300mA/h
Ambient operating temperature : -20 °C to +50 °C	Ambient operating temperature : -20 °C to +50 °C
Ambient storage temperature : -40 °C to +60 °C	Ambient storage temperature : -40 °C to +60 °C
Ambient operating humidity : 5% to 95%	Ambient operating humidity : 5% to 95%
Degree of protection : IP65	Degree of protection : IP65

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

[V680-A-7527S-G3-EG](#) [V680-A-WA3006](#) [V680-A-WA4003](#) [V680-A-WA6197](#) [V680 DEMO KIT 1.0](#) [V680-A-7527S-G3-EG-S](#) [V680-A-WA6181](#) [V680S-HMD66-PNT](#) [V680S-HMD66-EIP](#) [V680-A-CA1053](#) [V680-A-IMMEG-P01](#) [V680S-HMD64-PNT](#) [V680-A-WA3025](#) [V680S-HMD64-EIP](#) [V680S-HMD63-PNT](#)