



Solid-state Timer

English ▼



H3YN-2 AC200-230

Analog Timer, AC200 to 230V

Rated supply voltage	200 to 230VAC 50/60 Hz
Control output (Type)	Time-limit: DPDT
External connection method	Plug-in terminal

No Image
Available

Image

Series

Solid-state Timer
H3YN[Catalog](#)[about this Product](#)[Inquiry of this Product](#)[Item list of H3YN](#)[Ratings/Performance](#)[Dimensions](#)[Time ranges](#)[Operating chart](#)[Electrical life](#)

As of November 11, 2015

Rated supply voltage	200 to 230VAC 50/60 Hz
Operating voltage range	85% to 110% of rated supply voltage
Power consumption (Relay ON)	Approx. 2.2VA 1.8W (at 230 VAC, 60 Hz)
Power consumption (Relay OFF)	Approx. 1.5VA 1.1W (at 230 VAC, 60 Hz)
Reset voltage	10% max. of rated supply voltage
Number of time ranges	4
Time ranges	0.1s~1s / 1s~10s / 0.1min~1min / 1min~10min
Operating mode	ON delay, Interval, Flicker OFF start, Flicker ON start, Pulse Operation (use in interval mode, connect power supply terminals as pulse operation)
Control output (Type)	Time-limit: DPDT
Control output (Contact output)	Switching capacities (resistive load (cos (phi) = 1)): 250VAC 5A Minimum applicable load: 1 mA at 5 VDC (failure level: P)
Ambient temperature	Operating: -10 to 50°C Storage: -25 to 65°C
Ambient humidity	使用時: 35~85%
Accuracy of operating time	+/- 1% max.(FS) (+/- 1% +/- 10 ms max. in a range of 1 s)
Setting error	-10 to 10% +/- 50 ms max. (FS)
Reset time	0.1 s max. (including halfway reset)
Influence of voltage	+/- 2% FS max.
Influence of temperature	+/- 2% FS max.
Insulation resistance	100 MΩ (at 500 VDC)
Dielectric strength	between current carrying terminals and exposed non-current carrying metal parts: 2000 VAC, 50/60 Hz for 1 min (Terminal screw sections are not excluded) between control output terminals and operating circuit: 2000 VAC, 50/60 Hz for 1 min between contacts of different poles: 2000 VAC, 50/60 Hz for 1 min between non-continuous contacts: 1000 VAC, 50/60 Hz for 1 min
Impulse withstand voltage	between power terminals: 3 kV between exposed non-current-carrying metal parts: 4.5 kV
Noise immunity	+/- 1.5 kV square-wave noise by noise simulator (pulse width: 100 ns/1 μs, 1-ns rise)
Static immunity	Multifunction: 4 kV Destruction: 8 kV
Vibration resistance (Destruction)	10 to 55 Hz, 0.75 mm single amplitude each in X, Y, and Z directions for 1 hours
Vibration resistance	10 to 55 Hz, 0.5 mm single amplitude each in X, Y, and Z directions for 10 min

(Malfunction)	
Shock resistance (Destruction)	1000 m/s**2, 3 times each 6 directions
Shock resistance (Malfunction)	100 m/s**2, 3 times each 6 directions
Mechanical life expectancy (relayoutput)	10000000 operations min. (under no load at 1800 operations/h)
Electrical life expectancy (relay output)	500000 operations min. (5 A at 250 VAC, resistive load at 1800 operations/h)
Degree of protection	IP40
External connection method	Plug-in terminal
Case color	Munsell 5Y7/1 (Light gray)
Weight (Main)	Approx. 50 g

As of November 11, 2015

[▲ Top of page](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

[H3YN-2-AC200-230](#) [H3YN-2AC200-230](#)