# EVBUM2344/D

# **KAC CMOS Evaluation** Hardware

# Description

The KAC CMOS Evaluation Hardware supports evaluation of ON Semiconductor 4.7 micron CMOS products, enabling rapid turn-around for customer evaluations without the need to develop a full camera design. When combined with Sensor Studio II software, this hardware allows full control of the CMOS Image Sensor's register settings and enables both still capture and video recording. With this level of programmability, CMOS functionality such as global shutter, rolling shutter, very fast frame rate, high NIR sensitivity, multiple regions of interest, and interspersed video streams can be evaluated.

## Features

- Compatible with ON Semiconductor 4.7 micron CMOS Image Sensors
- Operates Device using 2 or 4 LVDS Output Banks
- Compatible with Sensor Studio II Software
- Flexible Readout Architecture
- High Frame Rate
- Full Access to Image Sensor Register Settings
- User Selectable Interfaces for Sensor Control, Image Capture and Firmware Download:
  - USB 3.0 (2 m Cable Included)
  - USB 2.0
  - Camera Link (Medium)
- Active Sensor Cooling
- Includes C/CS Lens Mount
- Integrated 1/4–20 Thread Tripod Mount
- Engineering Grade Image Sensor Included



# **ON Semiconductor®**

www.onsemi.com



**Figure 1. Evaluation Board Picture** 

Parameter	Typical Value
Hardware Interface	USB 3.0, USB 2.0, Camera Link (Medium)
Typical Data Rate USB 3.0 Camera Link	86 MB/s to 300 MB/s 256 MB/s
Power Required	12 VDA, 2 A
Control Software	Sensor Studio II, ver 6.2.0 or newer
On Board DDR2 Memory	4 GB
Optics	Includes C/CS lens mount. Compatible with optional Lens Mount Kit
FPGA	Xilinx Spartan-6

### **ORDERING INFORMATION**

Product Name	Description
KAC-06040-CB-A-GEVK	Evaluation Hardware for KAC-06040 Image Sensor (color). Includes Image Sensor.
KAC-06040-AB-A-GEVK	Evaluation Hardware for KAC-06040 Image Sensor (monochrome). Includes Image Sensor.
KAC-12040-CB-A-GEVK	Evaluation Hardware for KAC-12040 Image Sensor (color). Includes Image Sensor.
KAC-12040-AB-A-GEVK	Evaluation Hardware for KAC-12040 Image Sensor (monochrome). Includes Image Sensor.
LENS-MOUNT-KIT-C-GEVK	Lens Mount Kit that supports C, CS, and F mount lenses. Includes IR cut-filter for color imaging.

1

# EVBUM2344/D

# **REQUIRED HARDWARE AND SOFTWARE**

# **Host Computer**

- 2+ GHz processor, 2+ GB RAM, USB 2.0
- Windows XP, Vista 32 bit, or Windows 7 32 bit Operating System. 64 bit Operating Systems are not currently supported.

## For Maximum Speed

- Desktop PC: Native USB 3.0, or PCIe x1 Gen 2 slot. Tested PCIe x1 Gen 2 Slot Adapters: Startech PEXUSB3S2 – 133 MB/s, SilverStone SST–EC04–P – 189 MB/s
- Laptop PC: Native USB 3.0, or Express 54 slot. Tested Express 54 Card Adapters: Imperx FrameLink Express54 (Camera Link) Startech ECUSB3S2 – 86 MB/s (USB 3.0)

## Other

- +12 VDC, 2 A, power supply with 2.1 mm center positive DC jack
- Camera lens
- Sensor Studio II software
- IR Cut Filter (optional)
- Table-top tripod (optional)

ON Semiconductor and the intervent and the intervent of patients, trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specificatily disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC as a negligent the subsidiaries, affiliates, and listibutors harmless against all claims, costs, damages, and expenses, and

#### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Depage 421 92 700 9010

Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81–3–5817–1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

onsemi:

KAC-12040-CB-A-GEVK KAC-12040-AB-A-GEVK KAC-06040-AB-A-GEVK KAC-06040-CB-A-GEVK