

AR0230CS

CMOS Image Sensor, 2 MP, 1/2.7"

Product Overview

For complete documentation, see the data sheet.

The AR0230CS is a 1/2.7-inch CMOS digital image sensor with an active-pixel array of 1928 (H) x1088 (V). It captures images in either linear or high dynamic range modes, with rolling-shutter readout. It includes sophisticated camera functions such as in-pixel binning, windowing and both video and single frame modes. It is designed for both low light and high dynamic range scene performance. It is programmable through a simple two wire serial interface. The AR0230CS produces extraordinarily clear, sharp digital pictures, and its ability to capture both continuous video and single frames makes it the perfect choice for a wide range of applications, including surveillance and HD video.

Features

- High Dynamic Range

Applications

- Security

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Type	Megapixels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
AR0230CSSC00 SUEA0-DRBR		<div><div>Pb</div><div>H</div></div>	Active	CMOS	2.1	60	1/2.7 inch	Electronic Rolling and Global Reset Release	3.0 x 3.0		RGB	IBGA-80
AR0230CSSC00 SUEA0-DRBR1		<div><div>Pb</div><div>H</div></div>	Active	CMOS	2.1	60	1/2.7 inch	Electronic Rolling and Global Reset Release	3.0 x 3.0		RGB	IBGA-80
AR0230CSSC12 SUEA0-DR		<div><div>Pb</div><div>H</div></div>	Active	CMOS	2.1	60	1/2.7 inch	Electronic Rolling and Global Reset Release	3.0 x 3.0		RGB	IBGA-80
AR0230CSSC12 SUEA0-DR1		<div><div>Pb</div><div>H</div></div>	Active									IBGA-80

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[onsemi:](#)

[AR0230CSSC00SUEA0-DRBR](#) [AR0230CSSC12SUEA0-DR](#) [AR0230CSSC12SUEA0-DR1](#) [AR0230CSSC00SUEA0-DRBR1](#) [AR0230CSSC00SUEA0-DPBR2](#) [AR0230CSSC12SUEA0-DP](#)