

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild guestions@onsemi.com.


ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



BSS79C

NPN General Purpose Amplifier

- This device is for use as a medium power amplifier and swith requiring collector currents up to 500mA.
- Sourced from process 19.
- See BCW65C for characteristics.



Absolute Maximum Ratings * T_a =25°C unless otherwise noted

Symbol	Parameter	Value	Units
V _{CEO}	Collector-Emitter Voltage	40	V
V _{CBO}	Collector-Base Voltage	75	V
V _{EBO}	Emitter-Base Voltage	6.0	V
I _C	Collector Current - Continuous	800	mA
T _J , T _{STG}	Operating and Storage Junction Temperature Range	-55 ~ +150	°C

^{*} These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

- These ratings are based on a maximum junction temperature of 150 degrees C.
 These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Electrical Characteristics T_a=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Max.	Units
Off Charac	cteristics		•	•	•
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 10mA, I _B = 0	75		V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	$I_C = 10\mu A, I_E = 0$	40		V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	$I_E = 10\mu A, I_C = 0$	6.0		V
I _{CBO}	Collector-Cutoff Current	V _{CB} = 60V		10	nA
		$V_{CB} = 60V, T_a = 150^{\circ}C$		10	μΑ
I _{EBO}	Emitter-Cutoff Current	$V_{EB} = 3.0V, I_{C} = 0$		10	nA
On Charac	eteristics *				
h _{FE}	DC Current Gain	I _C = 150mA, V _{CE} = 10V	100	300	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 150mA, I _B = 15mA		0.3	V
` ,		$I_C = 500 \text{mA}, I_B = 50 \text{mA}$		1.0	V
Small Sign	nal Characteristics				
f _T	Current Gain - Bandwidth Product	$I_C = 20 \text{mA}, V_{CE} = 20 \text{V}, f = 100 \text{MHz}$		250	MHz
C _{CB}	Collector-Base Capacitance	$V_{CB} = 10V, I_E = 0, f = 1.0MHz$		8.0	pF
Switching	Characteristics				
t _d	Delay Time	V _{CC} = 30V, V _{BE(OFF)} = 0.5V, I _C = 150mA, I _{B1} = 15mA		10	ns
t _r	Rise Time			10	ns
t _s	Storage Time	V _{CC} = 30V, I _C = 150mA,		265	ns
t _f	Fall Time	$I_{B1} = I_{B2} = 15mA$		60	ns


Thermal (Characteristics	T _a =25°C unles	s otherwise noted


Symbol	Parameter	Max.	Units
P _D	Total Device Dissipation	350	mW
	Derate above 25°C	2.8	mW/°C
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	357	°C/W


^{*} Device mounted on FR-4 PCB 400mm × 40mm × 1.5mm

Package Dimensions

SOT-23







Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

FAST[®] $ACEx^{TM}$ ISOPLANAR™ Power247™ SuperFET™ $\mathsf{FASTr}^{\mathsf{TM}}$ ActiveArrav™ LittleFET™ PowerSaver™ SuperSOT™-3 FPS™ MICROCOUPLER™ $\mathsf{PowerTrench}^{\mathbb{R}}$ SuperSOT™-6 Bottomless™ QFET® $\mathsf{CoolFET}^{\mathsf{TM}}$ FRFET™ MicroFET™ SuperSOT™-8 QS™ SyncFET™ GlobalOptoisolator™ MicroPak™ $CROSSVOLT^{TM}$ MICROWIRE™ TinyLogic[®] GTO™ QT Optoelectronics™ $\mathsf{DOME}^\mathsf{TM}$ HiSeC™ TINYOPTO™ MSX^{TM} EcoSPARK™ Quiet Series™ $I^2C^{\scriptscriptstyle\mathsf{TM}}$ $MSXPro^{TM}$ RapidConfigure™ TruTranslation™ E²CMOS™ OCX^{TM} EnSigna™ i-Lo™ RapidConnect™ UHC™ $\mathsf{UltraFET}^{\circledR}$ ImpliedDisconnect™ FACT™ OCXPro™ uSerDes™ OPTOLOGIC® VCX^{TM} SILENT SWITCHER® FACT Quiet Series™ OPTOPLANAR™ SMART START™ Across the board. Around the world.™ PACMAN™

The Power Franchise® РОР™ Programmable Active Droop™

SPM™ Stealth™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdt/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81–3–5817–1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{onsemi:}}{\text{BSS79C}}$