



Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



ON Semiconductor®

November 2016

FSA646

2:1 MIPI D-PHY (2.5Gbps) 4-Data Lane Switch

Features

- Switch Type: SPDT(10x)
- Signal Types:
 - MIPI, D-PHY
- V_{CC} : 1.5 to 5.0 V
- Input Signals: 0 to 1.3 V
- R_{ON} :
 - 6 Ω Typical HS MIPI
 - 6 Ω Typical LP MIPI
- ΔR_{ON} : 0.1 Ω Typical LP & HS MIPI
- R_{ON_FLAT} : 0.9 Ω Typical LP & HS MIPI
- I_{CCZ} : 1 μ A Maximum
- I_{CC} : 32 μ A Typical
- O_{IRR} : -24 dB Typical
- Bandwidth: 2500 MHz Minimum
- Xtalk: -30 dB Typical
- C_{ON} : 1.5 pF Typical
- Skew of Opposite Transitions of the Same Output: 6 ps Typical

Description

The FSA646 is a four-data-lane MIPI, D-PHY switch. This single-pole, double-throw (SPDT) switch is optimized for switching between two high-speed or low-power MIPI sources. The FSA646 is designed for the MIPI specification and allows connection to a CSI or DSI module.

Applications

- Cellular Phones, Smart phones
- Tablets
- Laptops
- Displays

Ordering Information

Part Number	Operating Temperature Range	Package	Top Mark
FSA646UCX	-40 to +85°C	36-Ball WLCSP, Non-JEDEC 2.43 mm x 2.43 mm, 0.4 mm Pitch	GS

Typical Application




Figure 1. Typical Application

Pin Descriptions




Figure 2. Analog Symbol

Pin Name	Description		
CLKBP/N	B Side Clock Path		
DB1P/N	B Side Data Path 1		
DB2P/N	B Side Data Path 2		
DB3P/N	B Side Data Path 3		
DB4P/N	B Side Data Path 4		
CLKAP/N	A Side Clock Path		
DA1P/N	A Side Data Path 1		
DA2P/N	A Side Data Path 2		
DA3P/N	A Side Data Path 3		
DA4P/N	A Side Data Path 4		
CLKP/N	Common Clock Path		
D1P/N	Common Data Path 1		
D2P/N	Common Data Path 2		
D3P/N	Common Data Path 3		
D4P/N	Common Data Path 4		
/OE	Output Enable		
SEL	Control Pin	SEL=0	CLKP/N=CLKAP/N, DnP/N=DAnP/N
		SEL=1	CLKP/N=CLKBP/N, DnP/N=DBnP/N
VCC	Power		
GND	Ground		
NC	No Connect		

Pin Definitions




Figure 3. Top Through View

Ball	Pin Name
A1	V _{CC}
A2	GND
A3	DA4N
A4	DA4P
A5	/OE
A6	SEL
B1	DB4N
B2	DB4P
B3	DA3N
B4	DA3P
B5	D4N
B6	D4P
C1	DB3N
C2	DB3P
C3	NC
C4	NC
C5	D3N
C6	D3P
D1	DB2N
D2	DB2P
D3	DA2N
D4	DA2P
D5	D2N
D6	D2P
E1	DB1N
E2	DB1P
E3	DA1N
E4	DA1P
E5	D1N
E6	D1P
F1	CLKBN
F2	CLKBP
F3	CLKAN
F4	CLKAP
F5	CLKN
F6	CLKP

Table 1. Ball-to-Pin Mappings

Truth Table

SEL	/OE	Function
LOW	LOW	CLK _P =CLKA _P , CLK _N =CLKA _N , Dn(P/N)=DA _n (P/N)
HIGH	LOW	CLK _P =CLKB _P , CLK _N =CLKB _N , Dn(P/N)=DB _n (P/N)
X	HIGH	Clock and Data Ports High Impedance

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter		Min.	Max.	Unit
V_{CC}	Supply Voltage		-0.5	6.0	V
V_{CNTRL}	DC Input Voltage (/OE, SEL) ⁽¹⁾		-0.5	V_{CC}	V
V_{SW}	DC Switch I/O Voltage ^(1,2)		-0.3	1.8	V
I_{IK}	DC Input Diode Current		-50		mA
I_{OUT}	DC Output Current			25	mA
T_{STG}	Storage Temperature		-65	+150	°C
ESD	Human Body Model, JEDEC: JESD22-A114	All Pins	2.0		kV
	Charged Device Model, JEDEC: JESD22-C101		1.0		
	IEC 61000-4-2 System	Contact	8.0		
		Air Gap	15.0		

Notes:

- The input and output negative ratings may be exceeded if the input and output diode current ratings are observed.
- V_{SW} refers to analog data switch paths.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. ON does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter		Min.	Max.	Unit
V_{CC}	Supply Voltage		1.5	5.0	V
V_{CNTRL}	Control Input Voltage (SEL, /OE) ⁽³⁾		0	V_{CC}	V
V_{SW}	Switch I/O Voltage (CLKn, Dn, CLKA _n , CLKB _n , DAn, DB _n)	– HS Mode	0	0.3	V
		– LP Mode	0	1.3	V
T_A	Operating Temperature		-40	+85	°C

Note:

- The control inputs must be held HIGH or LOW; they must not float.

DC and Transient Characteristics

All typical values are at $T_A=25^{\circ}\text{C}$ unless otherwise specified.

Symbol	Parameter	Conditions	V_{CC} (V)	$T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$			Unit
				Min.	Typ.	Max.	
V_{IK}	Clamp Diode Voltage (/OE, SEL)	$I_{IN} = -18\text{ mA}$	1.5	-1.2		-0.6	V
V_{IH}	Input Voltage High	SEL, /OE	1.5 to 5	1.3			V
V_{IL}	Input Voltage Low	SEL, /OE	1.5 to 5			0.5	V
I_{IN}	Control Input Leakage (SEL, /OE)	$V_{CNTRL} = 0$ to V_{CC}	5	-0.5		0.5	μA
$I_{NO(OFF)}$ $I_{NC(OFF)}$	Off Leakage Current of Port CLKAn, DAn, CLKBn and DBn	$V_{SW} = 0.0 \leq \text{DATA} \leq 1.3\text{ V}$	5	-0.5		0.5	μA
$I_{A(ON)}$	On Leakage Current of Common Ports (CLKn, Dn)	$V_{SW} = 0.0 \leq \text{DATA} \leq 1.3\text{ V}$	5	-0.5		0.5	μA
I_{OFF}	Power-Off Leakage Current (All I/O Ports)	$V_{SW} = -0.0$ or 1.3 V	0	-0.5		0.5	μA
I_{OZ}	Off-State Leakage	$V_{SW} = 0.0 \leq \text{DATA} \leq 1.3\text{ V}$, /OE = High	5	-0.5		0.5	μA
$R_{ON_MIPI_HS}$	Switch On Resistance for HS MIPI Applications ⁽⁴⁾	$I_{ON} = -8\text{ mA}$, /OE = 0 V, SEL = V_{CC} or 0 V, CLKA,CLKB, DB _N or DA _N = 0.2 V	1.5		6		Ω
			2.5				
			3.3				
			5				
$R_{ON_MIPI_LP}$	Switch On Resistance for LP MIPI Applications ⁽⁴⁾	$I_{ON} = -8\text{ mA}$, /OE = 0 V, SEL = V_{CC} or 0 V, CLKA,CLKB, DB _N or DA _N = 1.2 V	1.5		6		Ω
			2.5				
			3.3				
			5				
$\Delta R_{ON_MIPI_HS}$	On Resistance Matching Between HS MIPI Channels ⁽⁴⁾	$I_{ON} = -8\text{ mA}$, /OE = 0 V, SEL = V_{CC} or 0 V, CLKA,CLKB, DB _N or DA _N = 0.2 V	1.5		0.1		Ω
			2.5				
			3.3				
			5				
$\Delta R_{ON_MIPI_LP}$	On Resistance Matching Between LP MIPI Channels ⁽⁴⁾	$I_{ON} = -8\text{ mA}$, /OE = 0 V, SEL = V_{CC} or 0 V, CLKA,CLKB, DB _N or DA _N = 1.2 V	1.5		0.1		Ω
			2.5				
			3.3				
			5				
$R_{ON_FLAT_MIPI_HS}$	On Resistance Flatness for HS MIPI Signals ⁽⁴⁾	$I_{ON} = -8\text{ mA}$, /OE = 0 V, SEL = V_{CC} or 0 V, CLKA,CLKB, DB _N or DA _N = 0 to 0.3 V	1.5		0.9		Ω
			2.5				
			3.3				
			5				

Continued on the following page...

DC and Transient Characteristics (Continued)

Symbol	Parameter	Conditions	V _{CC} (V)	T _A =- 40°C to +85°C			Unit
				Min.	Typ.	Max.	
R _{ON_FLAT_MIPI_LP}	On Resistance Flatness for LP MIPI Signals ⁽⁴⁾	I _{ON} = -8 mA, /OE = 0 V, SEL = V _{CC} or 0 V, CLKA, CLKB, DB _N or DA _N = 0 to 1.3 V	1.5		0.9		Ω
			2.5				
			3.3				
			5				
I _{CC}	Quiescent Supply Current (Includes Charge Pump)	V _{SEL} = 0 or V _{CC} , I _{OUT} = 0, /OE = 0 V	5			30	μA
I _{CCZ}	Quiescent Supply Current (High Impedance)	V _{SEL} = 0 or V _{CC} , I _{OUT} = 0, OE = V _{CC}	5			1	μA
I _{CCT}	Increase in I _{CC} Current Per Control Voltage and V _{CC}	V _{SEL} = 0 or V _{CC} , /OE = 1.5 V	5		1		μA

Note:

4. Measured by the voltage drop between A and B pins at the indicated current through the switch. On resistance is determined by the lower of the voltage on the two (A or B ports).

AC Electrical Characteristics

All typical value are for V_{CC} = 3.3 V and T_A = 25°C unless otherwise specified.

Symbol	Parameter	Conditions	V _{CC} (V)	T _A =- 40°C to +85°C			Units
				Min.	Typ.	Max.	
t _{INIT}	Initialization Time V _{CC} to Output ⁽⁵⁾	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.6 V	1.5 to 5		60		μs
t _{EN}	Enable Time /OE to Output	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.6 V	1.5 to 5		60	150	μs
t _{DIS}	Disable Time /OE to Output	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.6 V	1.5 to 5		35	250	ns
t _{ON}	Turn-On Time SEL to Output	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.6 V	1.5 to 5		350	1100	ns
t _{OFF}	Turn-Off Time SEL to Output	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.6 V	1.5 to 5		125	800	ns
t _{BBM}	Break-Before-Make Time	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.6 V	1.5 to 5	50		450	ns
t _{PD}	Propagation Delay ⁽⁵⁾	C _L = 0 pF, R _L = 50 Ω	1.5 to 5		0.25		ns
O _{IRR}	Off Isolation for MIPI ⁽⁵⁾	R _L = 50 Ω, f = 1250 MHz, /OE = HIGH, V _{SW} = 0.2 V _{PP}	1.5 to 5		-24		dB
X _{TALK}	Crosstalk for MIPI ⁽⁵⁾	R _L = 50 Ω, f = 1250 MHz, SEL = High, V _{SW} = 0.2 V _{PP}	1.5 to 5		-30	-25	dB
		R _L = 50 Ω, f = 1250 MHz, SEL = Low, V _{SW} = 0.2 V _{PP}			-30	-25	
BW (Insertion Loss)	-3db Bandwidth ⁽⁵⁾	R _L = 50 Ω, C _L = 0 pF, V _{SW} = 0.2 V _{PP}	1.5 to 5	2500			MHz

Note:

5. Guaranteed by characterization.

High-Speed-Related AC Electrical Characteristics

Symbol	Parameter	Conditions	V _{CC} (V)	T _A =- 40°C to +85°C			Unit
				Min.	Typ.	Max.	
t _{SK(P)}	HS Mode Skew of Opposite Transitions of the Same Output ⁽⁶⁾	R _L =50 Ω, C _L = 0 pF, V _{SW} = 0.3 V	1.5 to 5		6		ps

Notes:

6. Guaranteed by characterization.

Capacitance

Symbol	Parameter	Conditions	T _A =- 40°C to +85°C			Unit
			Min.	Typ.	Max.	
C _{IN}	Control Pin Input Capacitance ⁽⁷⁾	V _{CC} = 0 V, f = 1 MHz		2.1		pF
C _{ON}	On Capacitance ⁽⁷⁾	V _{CC} = 3.3 V, /OE = 0 V, f = 1250 MHz (In HS common value)		1.5		
C _{OFF}	Off Capacitance ⁽⁷⁾	V _{CC} and /OE = 3.3 V, f = 1250 MHz (Both sides in HS common value)		0.9		



Note:

7. Guaranteed by characterization.




The table below pertains to the Packaging information on the following page.

Product Specific Dimensions

D	E	X	Y
2.43 mm	2.43 mm	0.215 mm	0.215 mm



RECOMMENDED LAND PATTERN
(NSMD PAD TYPE)



ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[FSA646UCX](#)