

SURFACE MOUNT LED LAMP SUPER BRIGHT 0603 (0.8 mm Height)

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange



QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

PACKAGE DIMENSIONS



NOTE:

Dimensions for all drawings are in inches (mm).

APPLICATIONS

- Keypad backlighting
- Push-button backlighting
- LCD backlighting

DESCRIPTION

These surface mount chip LEDs are designed to fit industry standard footprint. Small size, low profile and wide viewing angle make these LEDs ideal choices for backlighting applications and panel illumination.

FEATURES

- Small footprint - 1.6(L) X 0.8(W) X 0.8(H) mm
- AlInGaP technology for -R, -E, -O, -Y and -AG
- InGaN/SiC technology for -IG and -IB
- Wide viewing angle of 100°
- Water clear optics
- Moisture-proof packaging
- Available in 0.315" (8mm) width tape on 7" (178mm) diameter reel; 2,000 units per reel

SURFACE MOUNT LED LAMP

SUPER BRIGHT 0603 (0.8 mm Height)

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange

QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

ABSOLUTE MAXIMUM RATINGS (T_A =25°C Unless otherwise specified)

Parameter	Symbol	QTLP600C					Units
		-R	-E	-O	-Y	-AG	
Continuous Forward Current	I _F	30	30	30	25	30	mA
Peak Forward Current (f = 1.0 KHz, Duty Factor = 1/10)	I _{FM}	160	160	160	120	160	mA
Reverse Voltage	V _R	5	5	5	5	5	V
Power Dissipation	P _D	72	72	72	60	72	mW
Operating Temperature	T _{OPR}	-40 to +85					°C
Storage Temperature	T _{STG}	-40 to +90					°C
Lead Soldering Time	T _{SOL}	260 for 5 sec					°C

ABSOLUTE MAXIMUM RATINGS (T_A =25°C Unless otherwise specified)

Parameter	Symbol	QTLP600C		Units
		-IB	-IG	
Continuous Forward Current	I _F	30	30	mA
Peak Forward Current (f = 1.0 KHz, Duty Factor = 1/10)	I _{FM}	100	100	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _D	120	120	mW
Operating Temperature	T _{OPR}	-40 to +85		°C
Storage Temperature	T _{STG}	-40 to +90		°C
Lead Soldering Time	T _{SOL}	260 for 5 sec		°C

SURFACE MOUNT LED LAMP

SUPER BRIGHT 0603 (0.8 mm Height)

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange

QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

ELECTRICAL / OPTICAL CHARACTERISTICS (T_A = 25°C)

Part Number	Symbol	QTLP600C					Condition
		-R	-E	-O	-Y	-AG	
Luminous Intensity (mcd)	I _V						I _F = 20mA
Minimum		15	15	15	15	10	
Typical		35	35	35	35	15	
Forward Voltage (V)	V _F						I _F = 20mA
Maximum		2.4	2.4	2.4	2.4	2.4	
Typical		2.0	2.0	2.0	2.0	2.0	
Wavelength (nm)	λ _P						I _F = 20mA
Peak		630	620	610	590	575	
Dominant	λ _D	624	615	605	589	573	
Spectral Line Half Width (nm)	Δλ	20	18	18	15	20	I _F = 20mA
Viewing Angle (°)	2Θ _{1/2}	100	100	100	100	100	I _F = 20mA

ELECTRICAL / OPTICAL CHARACTERISTICS (T_A = 25°C)

Part Number	Symbol	QTLP600C		Condition
		-IB	-IG	
Luminous Intensity (mcd)	I _V			I _F = 20mA
Minimum		15	70	
Typical		25	110	
Forward Voltage (V)	V _F			I _F = 20mA
Maximum		4.0	4.0	
Typical		3.5	3.5	
Wavelength (nm)	λ _P			I _F = 20mA
Peak		465	520	
Dominant	λ _D	470	525	
Spectral Line Half Width (nm)	Δλ	25	35	I _F = 20mA
Viewing Angle (°)	2Θ _{1/2}	100	100	I _F = 20mA

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange

QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

TYPICAL PERFORMANCE CURVES (QTLP600C-R, -E, -O, -Y and -AG)

Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Relative Luminous Intensity vs. DC Forward Current




Fig. 3 Relative Intensity vs. Peak Wavelength




Fig.4 Radiation Diagram





Fig.5 Maximum Forward Current vs. Ambient Temperature



QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange

QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

TYPICAL PERFORMANCE CURVES (QTLP600C-IG and IB)

Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Relative Luminous Intensity vs. DC Forward Current




Fig. 3 Relative Intensity vs. Peak Wavelength




Fig. 4 Radiation Diagram





Fig. 5 Maximum Forward Current vs. Ambient Temperature



SURFACE MOUNT LED LAMP SUPER BRIGHT 0603 (0.8 mm Height)

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange


QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green


QTLP600C-IG True Green

QTLP600C-IB Blue

RECOMMENDED PRINTED CIRCUIT BOARD PATTERN



RECOMMENDED IR REFLOW SOLDERING PROFILE



SURFACE MOUNT LED LAMP SUPER BRIGHT 0603 (0.8 mm Height)

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange


QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

TAPE AND REEL DIMENSIONS



Dimensional tolerance is ± 0.1 mm unless otherwise specified

Angle: ± 0.5

Unit: mm

QTLP600C-R Red

QTLP600C-E Orange

QTLP600C-O Yellow-Orange

QTLP600C-Y Yellow

QTLP600C-AG Yellow-Green

QTLP600C-IG True Green

QTLP600C-IB Blue

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[onsemi:](#)

[QTL600CETR](#) [QTL600CIGTR](#) [QTL600CRTR](#) [QTL600CYTR](#) [QTL600COTR](#) [QTL600CAGTR](#)
[QTL600CIBTR](#) [QTL600CIGTR_Q](#) [QTL600CAGTR_Q](#)