Spot Cooling

DIN rail

Complete Kit

Spot Cooler Only

VOLTAGE INPUT

INPUT POWER

DC Nominal Current

DC Locked Current

Rated Speed (RPM)

Noise Level (dB)

Fan ID

Airflow

OD1232-SPOT / DIN

Part Number - 124141794

Includes: 120x32mm Fan *

Power adaptor with 6' cord

Automotive grade, double-sided, mount

DIN mount fan bracket

Mounting screws

2 fan guards

anywhere tape

1 fan guard

OD1232-SPOT

OD1232-12HB-03 *

120VAC / 60Hz

3750 Max. (40C)

65CFM @ 25C / 120CFM @ 40C

19 Watts

0.60 A

0.05 A

20~47

Part Number - 124141794

Includes: 120x32mm Fan *

Power adaptor with 6' cord



Extend the Life of Your Equipment

Thermal Speed Control Airflow Range

> 65 CFM at 25C 120 CFM at 40C

Energy Saving Solution for your Green Initiative

Clips to standard DIN rail



115VAC power source

OD1232-SPOT / DIN

Part Number - 124141794 120x32mm Thermally controlled Fan * 6' Cord with adaptor 2 guards (1 installed) DIN rail DIN mount fan bracket Mounting screws Automotive grade, double-sided, mount anywhere tape

OD1232-SPOT

Part Number - 124141794 120x32mm Thermally controlled Fan * 6' Cord with adaptor 1 guard installed



OD9225-SPOT - Instant smart cooling for small spaces is also available in a

smaller package

Part Number - 193141791 92x25mm thermally controlled fan. [50CFM (3100RPM) at 34C to < 30CFM (1600RPM) at 22C] 6' cord with adaptor 1 guard installed



0.43" H₂O Max. Static Pressure Dual Ball **Bearing System** Frame & Impeller PBT, UL94V-O plastic Brushless DC, auto restart, polarity pro-Motor tected. Thermal Control. Dual ball bearing **Bearing System** 10M ohm between leadwire and frame **Insulation Resistance** (500VDC) 5mA max at 1500VAC for 1 minute **Dielectric Strength** between the leadwire and frame Operation -10C ~ +70C Temperature Life (L10) 60,000 hours

Patent Pending

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Orion Fans: OD1232-SPOT OD1232-SPOT/DIN