





Features

- 2660 μm x 2660 μm active area
- Low dark current
- Fast response time
- High speed epitaxy
- Fully depleted at 3.5 V
- Optimized for blue light

Description

High speed epitaxy PIN photodiode with 7.1 mm² square active area. Metal can type hermetic TO5 package with UV clear window. Other packaging options available upon special request.

Application

- Pulsed light detection
- High speed photometry
- High speed optical communications
- Laser monitoring

RoHS


2002/95/EC




Absolute maximum ratings

Symbol	Parameter	Min	Max	Unit
T _{STG}	Storage temp	-55	125	°C
T _{OP}	Operating temp	-40	100	°C
V _{max}	Max reverse voltage		30	V
I _{PEAK}	Peak DC current		10	mA

Schematic



Spectral response (23 °C)



Electro-optical characteristics @ 23 °C

Symbol	Characteristic	Test Condition	Min	Typ	Max	Unit
	Active area		2660 x 2660			μm
	Active area		7.1			mm ²
I _D	Dark current	V _R = 0 V		0.020	0.1	nA
		V _R = 3.5 V		0.040	0.2	nA
C	Capacitance	V _R = 0 V		120	150	pF
		V _R = 3.5 V		50	65	pF
	Responsivity	λ = 355 nm		0.16		A/W
		λ = 405 nm		0.23		A/W
t _R	Rise time	V _R = 3.5 V; λ = 405 nm; R _L = 50 Ω		5		ns
		V _R = 20 V; λ = 405 nm; R _L = 50 Ω		4		ns
V _{BR}	Breakdown voltage	I _R = 2 μA	30			V
	Shunt resistance	V _R = 10 mV		2500		M Ω
	N.E.P.	V _R = 3.5 V; λ = 405 nm		1.6 E-14		W/ $\sqrt{\text{Hz}}$

European, International Sales:







First Sensor AG
Peter-Behrens-Strasse 15
12459 Berlin
Germany
T +49 30 6399 2399
F +49 30 639923-752
sales.opto@first-sensor.com

USA:



First Sensor Inc.
5700 Corsa Avenue #105
Westlake Village
CA 91362 USA
T +1 818 706 3400
F +1 818 889 7053
sales.us@first-sensor.com

Quantum efficiency (23 °C)

Capacitance as fct of reverse bias (23 °C)

Dark current as fct of bias (23 °C)

Rise time as fct of bias (23 °C)


Application hints:

Please refer to document "Instructions for handling and processing"

European, International Sales:



First Sensor AG
Peter-Behrens-Strasse 15
12459 Berlin
Germany
T +49 30 6399 2399
F +49 30 639923-752
sales.opto@first-sensor.com

USA:



First Sensor Inc.
5700 Corsa Avenue #105
Westlake Village
CA 91362 USA
T +1 818 706 3400
F +1 818 889 7053
sales.us@first-sensor.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

First Sensor:

[PS7-5B-T05](#)