

NOTES:

- 1. ANTI-OXIDANT JOINT COMPOUND RECOMMENDED FOR ALL ALUMINUM CONNECTORS
- 2. SPLICER REDUCER AND SCREWS ARE TIN PLATED ALUMINUM
- 3. MADE IN U.S.A.
- 4. LISTED PER UL486B
- 5. CSA CERTIFIED (NOTE: DOES NOT APPLY TO SR-4/0-XY)
- 6. THIS PART IS ROHS COMPLIANT

PANDUIT		WIRE RANGE	INSTALLATION	WIRE	DIMENSIONS - IN		
PART NUMBER	FIGURE	CU AND AL	TOOL	STRIP LENGTH	Α	В	С
SR-2-XY	1	2 - 14 AWG STRANDED 10 - 14 AWG SOLID	SINGLE BLADE SCREWDRIVER	0.63	0.50	1.38	0.56
SR-0-XY		1/0 - 14 AWG STRANDED 10 - 14 AWG SOLID		0.88	0.75	1.91	0.75
*SR-4/0-XY		4/0 - 6 AWG STRANDED		1.08	1.00	2.31	1.13
SR-250-XY		250 kcmil - 6 AWG STRANDED	5/16" HEX ALLEN WRENCH	1.90	1.00	3.94	1.13
SR-350-XY	,	350 kcmil - 6 AWG STRANDED		2.00	1.13	4.19	1.19
SR-500-3Y	2	500 kcmil - 3/0 AWG STRANDED	3/8" HEX ALLEN WRENCH	2.44	1.37	5.00	1.40
SR-750-1Y		750 kcmil - 250 kcmil STRANDED	1/2" HEX ALLEN WRENCH	3.06	1.63	6.25	1.75
SR-1000-1Y	3	1000 kcmil - 500 kcmil STRANDED	9/16" HEX ALLEN WRENCH	4.38	1.72	8.69	1.88





							ALUMINUM SPLICER REDUCER SR SERIES CUSTOMER DRAWING		
							DATASET FILE NAME C41540/03.SLDDRW C41540/03.SLDDRW		
03	7/15	JHNU	JHNU	RGB	REVISED PART NUMBER: SR-0-XY WAS SR-0-SY	N41540BA- C41540	UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]		
02	9/14	JHNU	JHNU	RGB	ADDED NOTE TO SPECIFY SR-4/0-XY IS NOT CSA CERTFIED CONVERTED TO SOLIDWORKS REVISED DWG SIZE: WAS A SIZE	N41540BA- C41540	.X ± .XXX ± SEE NOTES .XX ± .02 ANGLES ± THIRD ANGLE PROJECTION C41540		
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE JHNU 10/05 LEM N/A SHEET 1 OF 1 B		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

SR-2-XY SR-0-XY SR-4/0-XY SR-350-XY SR-250-XY SR-500-3Y SR-750-1Y SR-1000-1Y