grey handle В -black handles grey handle CT-1160 TOOL SHOWN

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES, UNLESS OTHERWISE SPECIFIED:

SPECIFICATIONS:

PANDUIT TOOL NO: CT-1160 and CT-1170

- CT-1160 Controlled Cycle Ferrule Crimp Tool
 Crimps ferrule with Hexagon profile for 28-5 AWG (0,08 16 mm2) insulated and non-insulated single wire ferrules and 23-10 AWG (2 x 0.25mm2 2x 6mm2) insulated twin ferrules. CT-1160 uses a grey locator as identifier for hex profile terminations.
- CT-1170 Controlled Cycle Ferrule Crimp Tool
 Crimps ferrule with Square profile for 28-5 AWG (0,08 16 mm2) insulated and non-insulated single wire ferrules and 23-10 AWG (2 x 0.25mm2 2x 6mm2) insulated twin ferrules. CT-1170 uses a black locator as identifier for square profile terminations.

TOOL WEIGHT: (WITHOUT FERRULES) 17.6 oz (0,50kg)

THIS TOOL'S FEATURES INCLUDE:

- Easy handling
- Integrated, releasable ratchet guarantees complete crimping
- Ergonomically developed soft-grips with slip-off protection
- Integral (and reversible) ferrule locator for easy crimping

Fully recyclable

RoHS Directive 2011/65/EU compliant

DIMENSIONS SHOWN ARE FOR BOTH THE CT-1160 and CT-1170 TOOLS; AND ARE FOR REFERENCE ONLY. DIMENSIONS IN PARENTHESES ARE (MM) METRIC.

A = 8.50 (215) OVERALL LENGTH B = 2.95 (75) OVERALL HEIGHT C = 0.75 (19) OVERALL DEPTH

File Location: Teamcenter

							CT-1160 and CT-1170 TOOL
							TF28186B01_00
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± (.xxx) ± (.xx) ± ANGLES ±
00	9-07-16	BLR	BJPU	JADE	RELEASED	10218	THIRD ANGLE DRAWING NUMBER: PROJECTION TF28186B01
REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	BLR 9-07-16 BJPU NONE SHT 1 OF 1 B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

CT-1160 CT-1170