| 2 | | | | | | | | | | | | | | 1 | | | |
|------------|-----|--|---|-------------------------------------|------------------------------------|--|--|------------------|---|-------------------|---------------|---|----------------|---------------------|----------------------|-------|--|
| | | THIS CO | PY IS | S PROV | IDED | ON A F | RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DE | | | | | TRIMENTAL | TO THE | INTERESTS | OF PANDUIT CORP. | | |
| | | PANDUIT | | STUD SIZE | | | DIMENSIONS in. [mm] | | | | | | | ▼ ₩ - | - | | |
| | | PART # | | NGLISH | н ме | TRIC | L ± [0,76] | W ± .01 [0,25] | C ± .015 [0,38] | M ± .02 [0,51] | H± .02 [0,51] | _ | <u> </u> | | H DIA | | |
| | F | PMN2-3F | | | | М3 | .78 [19,8] | .23 [5,9] | .19 [4,8] | .64 [16,3] | .15 [3,8] | | 1 - | | STAME. | 1.1.0 | |
| | F | N14-6FN | | #6 | ľ | M3, 5 | .78 [19,8] | .24 [6,2] | .19 [4,8] | .64 [16,3] | .15 [3,8] | | | | STAMP | ING | |
| | F | PN14-6F | | #6 | ľ | M3, 5 | .78 [19,8] | .28 [7,1] | .19 [4,8] | .64 [16,3] | .15 [3,8] | | | | C RAD | | |
| | F | PN14-8F | | #8 | | M4 | .84 [21,3] | .31 [7,9] | .23 [5,9] | .68 [17,3] | .17 [4,3] | | | - Jr - | - - | | |
| В | F | PN14-10F | | #10 | | | .86 [21,8] | .34 [8,6] | .24 [6,2] | .70 [17,8] | .20 [5,0] | | Ĺ | 8, 1 | | В | |
| | - | PN14-10FN | ١ | #10 | | | .86 [21,8] | .31 [7,9] | .24 [6,2] | .70 [17,8] | .20 [5,0] | | М | | HOUSIN | NG | |
| | - | PMN2-5F | | | | M5 | .86 [21,8] | .34 [8,6] | .25 [6,4] | .70 [17,8] | .21 [5,3] | | | | | | |
| | F | PN14-14F | | 1/4" | | M6 | 1.03 [26.2] | .44 [11,2] | .32 [8,1] | .78 [19,8] | .27 [6,9] | | | | SLEEVE | = | |
| | | NOTES: 1. USE | | | | | 2,5 mm²] (| | | | | | | | | _ | |
| | | C. INS A. B. C. | 600 TALL PRES APPL DIE | V.N ATIC SES: ICAT INSE | MAX. ON TO CP OR: ERTS | VOLT DOLS: -871 CD-8 : CD- | OPERATIAGE RATINO OOEZ, CAS 800-2, CE 7/32" *1/32 | NG))9-2A | | | (C C | RRIER STE DNFIGUAR/ Y VARY) | RIP — Ation | ∫ ⊸ | MAX. WIRE INSUL. DIA | | |
| | [| 4. MATERIAL: A. STAMPING: .03" [0,76] THK COPPER, TIN PLATED B. HOUSING: NYLON, BLUE C. SLEEVE: BRASS, TIN PLATED 5. SEE www.panduit.com FOR PACKAGE QUANTITIES INDICATED BY PART NUMBER SUFFIX 6. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT LISTED CERTIFIED 587H E52164 | | | | | | | | | | | | | | | |
| | | | | | | | | | | | TITLE | FORK TI | | 1 C 2 DC A | IVI ON INCLUATED | | |
| A | | | | | | | | | | | | FORK TERMINALS, 3 PC. NYLON INSULATED, #16-14 | | | | A | |
| | | | | | | | | | | | ITEM REV | CUSTOMER DRAWING | | | | | |
| | | | | | | | | | | | DATASET | N41095BA/05 DATASET FILE NAME | | | PANDU | AUT | |
| | | | | | | | | N41093BA_DC/03A | | | | | | | | | |
| | | | | | | | | | | | .x | UNLESS OTHER ENSIONAL TOLE ± .1 [2.54] | .xxx : | .005 [.13] | SEE NOTES | | |
| 14/15 | 05 | 09.07.12 | 0.07.12 JBN LCA VMB ADDED METRIC EQUIVALENT. REVISED NOTES. UPDATED DRAWING TO CURRENT STANDARDS. | | | | A410 | | .XX ± .01 [.25] ANGLES ± 5 ° THIRD ANGLE PROJECTION A 4 | | | DRAWING NUMBER: | | | | | |
| 10100DA/1 | REV | DATE | BY | СНК | APR | | DE | SCRIPTION | | EC | DRAWN BY | | снк FS | SCALE N.T.S. | SHT 1 0F 1 | SIZE | |
| □ L | 2 | | | | | | | | | | 1 | | | | | | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:
PN14-6FN-3K