

NOTES, UNLESS OTHERWISE SPECIFIED:

PANDUIT CT-1700 TOOL:

TOOL WEIGHT: 20 oz. [0,56] kg

Crimps Panduit #8 - #1 AWG copper lugs and splices, #6 - #4 AWG aluminum lugs and splices, #8 - #2 AWG non-insulated S series tubular terminals; and #16 AWG - #3 AWG copper CTAPF taps.

Provides UL Listed and CSA Certified terminations with applicable Panduit terminals.

DIMENSIONS SHOWN IN BRACKETS [] ARE METRIC [MM], AND ARE FOR REFERENCE ONLY.

	DIE COLOR/ INDEX NUMBER		LISH AGE MEMBERS	METRIC GO / NO GO GAGE MEMBERS			
		"G" Dia. (GO)	"NG" Dia. (NO GO)	"G" Dia. (GO)	"NG" Dia. (NO GO)		
	RED P21	0.177″	0.201″	4,49 mm	5,10 mm		
	BLUE P24	0.219"	0.239"	5,56 mm	6,07 mm		
	GREY P29	0.255″	0.276"	6,47 mm	7,01 mm		
	BROWN P33	0.324"	0.348"	8,22 mm	8,83 mm		
)	GREEN P37	0.347"	0.368"	8,81 mm	9,34 mm		

		CT-1700 Contour Crimp™ Crimping Tool CUSTOMER DRAWING							
		ITEM REVISION				Pand	UIT		
			OTHERWISE	MATERIAL:					
DBAL LOGO FROM GRIP ADE IN GERMANY FROM E; ADDED GO-NO GO	4857/ 02	(.x) ± (.xx) ±	(.xxx) ANGL						
D BRANDING	4857				DRAWING NUMBER: TP23621C01				
DESCRIPTION	ECN	DRAWN BY : BLR	DATE: 5-08-15	CHK BJPU	SCALE NONE	SHT 1 OF 1	SIZE C		

1.0" [24.5]

GRIP SPAN 1.5" [38.1] FULLY CLOSED 8.8" [222.3] FULLY OPEN

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit: <u>CT-1700</u>