	2									$\overline{1}$							
	THIS CO	OPY IS	PRO	V I DED	ON A RESTR	RICTED BASIS AN	D IS NOT TO	O BE USED IN	any wa	Y DETRIME	ental to t	HE INTE	ERESTS OF I	PANDUIT CC	DRP.		
	DANDLIT WIRE RANGE TAB SIZE MA							MAY WIRE		DIMENSIONS in. [mm]							
		ANDUIT Part #			AWG [mm²]	INCH [mm]	COLOR	MAX. WIRE INSULATION DIAMETER	L±	.03 [0,8]		01	H± .01				
	ED	V10-2	250	; [4	£12-10 ,0-6,0]	.250 X .032 [6,3 X 0,8]	YELLOW	.23 [5,8]	1.0	3 [26,2]	.30 [7	7,6]	.13 [3,3	3]			
В																В	
	B. C. 2. MA: A. B. C. 3. IN: A. B.	ED FO STR/ 194 600 TERI/ STAN HOU! SLEE STALL UL I CT-2 PANI	ANDE °F [9 V. AL: MPING EVE: _ATI _IST 2500 DUIT TRIP	G: E BRA ON T ED APP LEN	VOLTAGE RASS, TII INYL SS, TIN OOLS: ND CSA CI -600A ROVED: C GTH: 9/3	ERATING TEMF RATING N PLATED PLATED ERTIFIED: CT T-100A, CT-1 2" +1/32 [7,1r	DIA. HART) - 1550, C 60, CT-2	HOUSING ————————————————————————————————————	RE STOR		AMPING —	RECO		w w EERTIFIED LR31212	H ►		
A	INI	D I C A 1	TED	BY P	ART NUMBI	R PACKAGE QU ER SUFFIX ARE METRIC			STRONGHOLD FEMALE DISCONNECTS (250 SERIES) VINYL INSULATED, METAL SLEEVE #12-10 AWG CUSTOMER DRAWING								
										ITEM REVISION NAM	00123SHI/	00		DANI	niii	тм	
										UNLESS	00123SHL_DO		ED, MATER	RIAL:	JUI		
			TMR							.x ± .1 [.xx ± .01	2.54]	.xxx : .005 [.127] angles : 5 ° THIRD ANGLE PROJECTION		SEE NOTES	IOTES		
00	2/18	JHNU		RGB	RELEASED			00123						SH41199			
00 REV	DATE	ВҮ	CHK	APR		DESCRIPTIO	NC	EC	I	JHNU DATE	2/18 T	MR SCALE	N.T.S.	SHEET 1 0	F 1	SIZE	
					2				'		•	1					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

EDV10-250M-Q EDV10-250-Q EDV10-250FIB-Q EDV10-250P-Q