	2										1								
		THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT C														JIT CORF			
				1/\	WIRE	RANGE	TAB SIZE		MANY WIDE	DIMENSIONS in. [mm			[mm]						
		PAND PAR			A	NWG mm²]	INCH [mm]	HOUS I NG COLOR	MAX. WIRE INSULATION DIA.		03	W± .01	1 1 1 +	.02 0,51			ļ		
		EDV18-1	. 88B		#2 [O,5	22-18 5-1,0]	.187 X .020 [4,8 X 0,5]	RED	.136 [3,45]	.7 [20,		.23 [5,8]	[2,	10			H		
		EDV14-1	. 88B *	÷		16-14 5-2,5]	.187 X .020 [4,8 X 0,5]	BLUE	.162	.7		.23 [5,8]	[2]	10 5 1	-	- W			
В		*UL RE	COGN	NI ZED	ONI	LY											В		
	NOTES: 1. UL LISTED AND CSA CERTIFIED FOR: A. STRANDED COPPER WIRE ONLY B. 221°F (105°C) MAX TEMP RATING C. 600V MAX VOLTAGE										Terminal Stamping								
	2	MATER A. ST. B. HO	AMP I	NG:			1) THK BRASS	G, TIN P	PLATED					Butted Seam			Ĺ		
4	3.		LIS	STED	AND	CSA CE	RTIFIED: CT- O, CT-1525	520, CT	- 1525					Housing	y		V_		
	4	, WIRE !	STRI	P LE	ENGTH	1/4**	+1/32 -0 [6.	3mm +0.8 -o]	((II)	(SP	®		® •		-Max. Wi Insul. Dia		
	5	FIRST FIRST				FORCE:	12 LB (53N) 12 LB (53N) 6 LB (27N)	MAX		2	® 5 7 I STED 20H3 78522	LR312.		RECOGNIZI E78522					
A	6. SEE WWW.PANDUIT.COM FOR PACKAGE QUANTITIES INDICATED BY PART NUMBER SUFFIX 7. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT										TITLE	STRONGHOL							
			VINYL INSULATED, BUTTED S CUSTOMER DRAW										722 17	/\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					
									O0123STL/00 DATASET FILE NAME O0423STL/00										
											0012351L/00					FIEL L	JUII		
			UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .x ± .1 [2.54] .xxx ± .005 [.127] .xx ± .01 [.25] ANGLES ± 5°									SEE NOTES							
)A/20	00	2/18	JHNU TMR RGB RELEASED						00123SH			THIR	O ANGLE ECTION	DRAWING NUMB	BER: 5H415	554			
010100DA	REV	DATE	BY	CHK	APR		DESCRIPT	ION		ECN	JHNU	DATE 2/18	CHK SC	NTS		SHT 1 0F 1		ZE	
□ ['	2							1				L		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

EDV14-188B-L EDV18-188B-L EDV14-188B-Q EDV18-188B-Q