



- 1. Material: Body - Aluminum, tin Plated Screw - Aluminum, tin Plated
- 2. UL LISTED & CSA CERTIFIED FOR USE UP TO 600V & TEMPERATURE RATED 90 °C (AL9CU)
- 3. DUAL RATED FOR USE WITH COPPER OR ALUMINUM STRANDED CODE CONDUCTOR
- 4. THESE PARTS ARE ROHS COMPLIANT
- 5. USE OF OXIDE INHIBITING JOINT COMPOUND LIKE PANDUIT CMP-100 RECOMMENDED FOR PAD TO PAD AND CONDUCTOR SURFACES
- 6. SEE PACKAGING LABEL FOR TIGHTENING TORQUE INFORMATION
- 7. PKG QTY: 1 =1





	PART NUMBER	STUD SIZE	DIMENSIONS - IN [mm]											WIRE	HEX KEY*	
			Α	В	C1	C2	D	E	F	G	Н	J	K	L	RANGE	HEX KET
ĉ	LAM2SB600-38-1Y	3/8	.38	1.38	1.38	1.19	4.91	.75	3.00	1.50	.58	2.08	.78	1.88	600kcmil-2	3/8
			[9.5]	[35.1]	[35.1]	[30.2]	[124.7]	[19.1]	[76.2]	[38.1]	[14.7]	[52.8]	[19.81]	[47.8]		
B	LAM2SB750-38-1Y	3/8	.38	1.38	1.38	1.19	4.91	.75	3.00	1.50	.58	2.08	.78	1.88	750kcmil-1/0	3/8
			[9.5]	[35.1]	[35.1]	[30.2]	[124.7]	[19.1]	[76.2]	[38.1]	[14.7]	[52.8]	[19.81]	[47.8]		

<sup>\*</sup> HEX SIZE MAY DIFFER FROM CHART. DIFFERENCE IN SIZE WILL NOT AFFECT FIT, FORM, OR FUNCTION OF PART

								PANDUIT CORP. 1	INLEY PARK, ILLINOIS
				C. REVISED DIMENSIONS FOR LAM2SB600-38-1Y				LAM2SB SERIES ALUMINUM MI CUSTOMER DRAN	
03	9/10	JHNU	JHNU	B. REVISED DIMENSIONS FOR LAM2SB750-38-1Y A. REMOVED TIGHTENING TORQUE & WEIGHT COLUMN	N41559BA-C41559	FLD	FLD	UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE:	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN
02	1/07	JHNU	JHNU	ADDED PART WEIGHT COLUMN TO TABLE				(.XXX) ± (.XXX) ± (.XXX) ± ANGLES ±	INCHES, THIRD ANGLE PROJECTION
01	3/06	JHNU	LEM	REVISED ROHS NOTE				DRAWN BY MAT'L: JHNU	SCALE NONE
00	2/06	JHNU	LEM	DRAWING RELEASED - ROHS COMPLIANT				<b>DATE</b> 2/06	C41559 03 B
REV	DATE	BY	СНК	DESCRIPTION	ECN	-R	SUP	СНК'D	C41559_03   <b>B</b>

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Panduit:

LAM2SB600-38-1Y LAM2SB750-38-1Y