UNITED STATES [CHANGE] ENGLISH REGISTER / LOG IN

FOLLOW US



SOLUTIONS PRODUCTS AND SERVICES

SUPPORT

ABOUT US

Q Search Panduit.com



Search within category

BUY NOW

DESIGN / INSTALL



FXURPENENXNF068

OM3 24-fiber, Interconnect, Plenum, 24F MPO Female to 24F MPO Female, Method A, Optimized IL, 68 ft, Aqua.

Specs Packaging Details D	ocuments	Add to Favorites	Add to BOM
Application	Data centers requiring quick infrastructure to maintain bandwidth throughout the infr		d reach that want
Assembly Length Range	20-29 m (66-98 ft)		
Cable Color	Aqua		
Connector 1 Type	24F MPO		
Connector 2 Type	24F MPO		
Fiber Count	24		
Fiber Type	OM3		
Flammability Rating	Plenum (OFNP)		
Length (ft.)	68		
Length (m)	20.73		
Standards	TIA/EIA-598-C.3, NFPA-262, RoHS Comp	oliant	
RoHS Compliancy Status	Compliant		
Min. Order Qty.	1.0000		
No. of Fibers	24		

LEGAL INFORMATION | PRIVACY POLICY | CONTACT US | SITE MAP | WHERE TO BUY | JOBS | UNSUBSCRIBE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

FXURPENENXNF068