FOLLOW US

UNITED STATES [CHANGE] ENGLISH REGISTER / LOG IN

SOLUTIONS PRODUCTS AND SERVICES

SUPPORT

ABOUT US

Q Search Panduit.com

Search within category

**BUY NOW** 

**DESIGN / INSTALL** 



## **FXURPENENXNF036**

OM3 24-fiber, Interconnect, Plenum, 24F MPO Female to 24F MPO Female, Method A, Optimized IL, 36 ft, Aqua.

Specs Packaging Details D	ocuments	Add to Favorites	Add to BOM
Application	Data centers requiring quick infrastructure to maintain bandwidth throughout the infra		d reach that want
Assembly Length Range	10-19 m (33-65 ft)		
Cable Color	Aqua		
Connector 1 Type	24F MPO		
Connector 2 Type	24F MPO		
Fiber Count	24		
Fiber Type	OM3		
Flammability Rating	Plenum (OFNP)		
Length (ft.)	36		
Length (m)	10.98		
Standards	TIA/EIA-598-C.3, NFPA-262, RoHS Comp	liant	
RoHS Compliancy Status	Compliant		
Min. Order Qty.	1.0000		
No. of Fibers	24		

LEGAL INFORMATION | PRIVACY POLICY | CONTACT US | SITE MAP | WHERE TO BUY | JOBS | UNSUBSCRIBE

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

FXURPENENXNF036