		ED ON	A RESTRICTED BASIS AND IS NOT TO BE U	SED IN A	ANY WAY DET	RIMENTAL	то тн	E INTE	ERESTS OF PANDUIT CORP.
Material			High Conductivity Seamless Copper Tube						
Plating			Electro-Tin						
Wire Size			2 AWG			≝⊜∕	¬	⊃¦⊂	window
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric		.75±.04	PANDUIT		2 STR CU	
Wire Strip	Wire Strip Length		15/16 in.						
Stud Size			1/2 in.		.47±.04				
UL Listed Wire Connector Voltage stress relief instructions with applications greater than 2000 volts.									
UL Temp Rating	perature		90° C			◄ 1.07±	7±.04	. ———	-
	C.S.A Certified Wire Connector		Yes		.01			1	
	Panduit Color Code on Barrel		BROWN	.08±					1.35 REF PANDUIT
	Panduit Die Index No. on Barrel		P33			90°±5°			
Die Inde	Alternate Industry Die Index No. () on Barrel		(10)						.88±.04
	C	ERTIFIE	B USTED Wire Connector				.42	1±.01 2±.01 67 RE	Beveled wire entry EF
									ANDUIT CORP. TINLEY PARK, ILLINOIS
01 6/15	5 JHNU	JHNU	ADDED PART NUMBER TO TONGUE MARKING		N10881IE-LCA	A2-12F-CUST	RGB	RGB	LCA2-12F-Q Connecting One Hole Standard Barrol 90° Angle Tengue
EV DATE		снк	DESCRIPTION		EC				SCALE N/A DRAWING NO / CAD FILE LCA2-12F-CUST

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit: LCA2-12F-Q