

ISFX5502ARD-LED Share

Oty Add to Born

Specifications	Packaging Detail	Resources	Related Products	Top of Page 🔨

Overall Length (ft.)	1640
Overall Length (m)	500
Jacket Material	Polyvinyl chloride
Conductor Gauge (AWG)	24
Cable Type	SF/UTP
Nominal Diameter (In.)	0.252
Nominal Diameter (mm)	6.4
Insulation Diameter (In.)	0.05
Insulation Diameter (mm)	1.3
Number of Pairs	2
Sub Brand	IndustrialNet TM
Maximum Operating Temperature (°C)	80
Maximum Operating Temperature (°F)	176
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Maximum Installation Temperature (°C)	80
Maximum Installation Temperature (°F)	176
Minimum Installation Temperature (°C)	-40
Minimum Installation Temperature (°F)	-40
Package Type	Reel
Color	Red
Flammability Rating	LSZH-1 (60332-1)
Length (ft.)	1640
Application	Industrial
Note	Available in all regions
Part Features	Third party tested, Ethernet/IP Compliant, Descending length cable markings, Packaged on a reel.
Performance Level	Category Se

ackaging Detail

UPC	07498361561
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	1.6526
Std. Ctn. Qty.	12
Std. Ctn. Volume (cf)	19.8315

Technology Briefs	Power Over Ethernet With Panduit Copper Cabling	US English	View PDF (562.9893)	Downtood POF	Share FOF
Specification Sheets	IndustrialNet [™] Category 5e SF/UTP Copper Cable	US English	View PDF (223.2768)	Download PCF	S litera POF
Case Studies	Automotive Manufacturer Case Study: CPCS62WW-ENG	US English	View PDF (5.42HB)	Download FOF	Stare FOF
Certifications	Declaration of Perfomance: PAN-DOP-CL001	US English	View POF (126,8948)	Download PDF	S Stare
Certifications	ETL Report of Test Certificate (ISFX5502A-LED)	US English	View POF (80 78KB)	Downtood POF	Stare FOF

Related Products









0 0 0 0



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

ISFX5502ARD-LED