Opti-Core® LC Uniboot Push-Pull Duplex Fiber Optic Patch Cords



technical information

Panduit's Duplex LC Uniboot Push-Pull connector gives you the option to change polarity with ease, it also has no loose pieces that could be dropped or lost when changing polarity. The LC Uniboot Push-Pull Duplex fiber optic patch cords are constructed with a 2.0mm 2-fiber round unitary cable available in plenum (OFNP) or low smoke zero halogen (LSZH) rated jacket materials to meet local ordinances. By using the 2.0mm cable which reduces cable volume by 50% the LC Uniboot Push-Pull fiber optic patch cords are ideal for reducing cabling congestion in extremely high density patch fields. These LC Uniboot patch cords are available in OM5+, OM4+, OM4, OM3, and OS2 fiber types with high performance insertion loss essential for today's high speed systems requiring very low connector insertion loss. This series is available with the following end faces; standard PC (physical contact) for multimode, UPC (ultra physical contact) for singlemode.



application

Provide interconnect and cross-connect of applications in entrance facilities, telecommunication rooms, data centers, at the desk and network applications to interconnect pre-terminated cassettes in main distribution, horizontal distribution, and equipment distribution areas.

construction

| 2 - Fiber Round | | |
|--|--|--|
| Plenum (OFNP) Low Smoke Zero Halogen (LSZH) | | |
| Singlemode: OS2 9/125µm Multimode: OM3 50/125µm OM4/4+ 50/125µm OM5+ 50/125µm | | |
| Duplex LC Uniboot | | |
| Duplex LC Uniboot | | |
| OS1/OS2: Yellow OM3: Aqua OM4: Aqua OM4+: Aqua OM5+: Lime Green | | |
| | | |

physical properties

| Cable outside diameter (OD): | 2.0mm |
|-------------------------------------|---|
| Bend Radius, (min): | 40mm |
| Connector cable retention: | 50N (11.24 lbs.) @ 0° 19.4N (4.4 lbs.) @ 90° |
| Connector durability: | 500 cycles |
| Bend Radius, (min), (Long-Term): | 20mm (40mm) |

optical properties

| Connector | | |
|-----------------|-----|---------------------------|
| insertion loss: | MM: | 0.15dB max (Optimized IL) |
| | | 0.10dB max (Ultra-Low IL) |
| | SM: | 0.25dB max (Optimized IL) |
| Connector | | 26dB min (MM) |
| return loss: | | 55dB min (SM) |
| | | 65dB min (SM/APC) |

environmental properties

| Storage and shipping temperature: | -40°C to 70°C |
|---|---------------|
| Operating and installation temperature: | -10°C to 60°C |

standards

Meets or exceeds ISO/IEC 11801, TIA/EIA-568-D.3, TIA-604-10 (FOCIS-10)

2011/65/EU

| Restriction of Hazardous | All patch cord |
|--------------------------|-----------------|
| Substances (RoHS) | components meet |
| Compliance: | the requirement |
| | of Directive |

Opti-Core® LC Uniboot Push-Pull Duplex Fiber Optic Patch Cords

part number configurator


Example: FX2RLUNUNONM005 = Fiber, OM3, 2-fiber, 2mm Round, LSZH, LC Uniboot to LC Uniboot, Optimized IL, 5 Meters

| Character123ExampleFX2 | 4 5 6 7 8 9 10 R L U N U N 0 | 11 12 13 14 15 N M 0 0 5 | |
|---|---|---|--|
| 1 - Fiber Product 5 - Jacket Type F = Fiber L = LSZH IEC 60332 (Low Smoke Zero Halogen) 2 - Fiber Type P = OFNP (Plenum) X = OM3 50/125µm 6 - Connector Type S = OM4 50/125µm U = LC Duplex Uniboot | 10 - Performance/Construction O = Optimized IL - Straight thru (A-B) N = Ultra-Low IL - Straight thru (A-B) - Multimode Only 11 - Connector Variant | | |
| $W = OM4 + 30,720 \mu m$ $W = OM4 + 30,720 \mu m$ $9 = OS2 9/125 \mu m$ 3 - Fiber Count $2 = 2 \text{-fiber}$ 4 - Cable Type $R = Round 2.0 mm$ | 7 - Connector Variant A = APC (SM only and Optimized) N = No variant 8 - Connector Type U = LC Duplex Uniboot 9 - Connector Variant A = APC (SM only and Optimized) N = No variant | N = No variant 12 – Unit of Length M = Meters F = Feet 13, 14, 15 – Length 001 - 050 | |

changing polarity: Ic duplex uniboot fiber optic patch cords



CHANGING POLARITY



PANDUIT US/CANADA Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK Phone: 44.20.8601.7200 PANDUIT SINGAPORE PTE. LTD. **Republic of Singapore** Phone: 65.6305.7575

PANDUIT JAPAN Tokvo, Japan Phone: 81.3.6863.6000

COLÓRS

PANDUIT LATIN AMERICA Guadalaiara. Mexico Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

For more information



Visit us at www.panduit.com Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300

© 2019 Panduit Corp. ALL RIGHTS RESERVED. FBSP154--WW-ENG 9/2019

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

| F92RLUAUAONM00 | 1 F92RLUAUAONM002 | 592RLUAUAONM003 | B F92RLUAUAONM004 | F92RLUAUAONM005 |
|-----------------|-------------------|-----------------|-------------------|-----------------|
| F92RLUAUAONM006 | F92RLUAUAONM007 | F92RLUAUAONM008 | F92RLUAUAONM009 | F92RLUAUAONM010 |
| F92RLUAUAONM011 | F92RLUAUAONM012 | F92RLUAUAONM013 | F92RLUAUAONM014 | F92RLUAUAONM015 |
| F92RLUAUAONM016 | F92RLUAUAONM017 | F92RLUAUAONM018 | F92RLUAUAONM019 | F92RLUAUAONM020 |
| F92RLUAUAONM021 | F92RLUAUAONM022 | F92RLUAUAONM023 | F92RLUAUAONM024 | F92RLUAUAONM025 |
| F92RLUAUAONM026 | F92RLUAUAONM027 | F92RLUAUAONM028 | F92RLUAUAONM029 | F92RLUAUAONM030 |
| F92RLUAUAONM031 | F92RLUAUAONM032 | F92RLUAUAONM033 | F92RLUAUAONM034 | F92RLUAUAONM035 |
| F92RLUAUAONM036 | F92RLUAUAONM037 | F92RLUAUAONM038 | F92RLUAUAONM039 | F92RLUAUAONM040 |
| F92RLUAUAONM041 | F92RLUAUAONM042 | F92RLUAUAONM043 | F92RLUAUAONM044 | F92RLUAUAONM045 |
| F92RLUAUAONM046 | F92RLUAUAONM047 | F92RLUAUAONM048 | F92RLUAUAONM049 | F92RLUAUAONM050 |
| F92RLUNUNONM001 | F92RLUNUNONM002 | F92RLUNUNONM003 | F92RLUNUNONM004 | F92RLUNUNONM005 |
| F92RLUNUNONM006 | F92RLUNUNONM007 | F92RLUNUNONM008 | F92RLUNUNONM009 | F92RLUNUNONM010 |
| F92RLUNUNONM011 | F92RLUNUNONM012 | F92RLUNUNONM013 | F92RLUNUNONM014 | F92RLUNUNONM015 |
| F92RLUNUNONM016 | F92RLUNUNONM017 | F92RLUNUNONM018 | F92RLUNUNONM019 | F92RLUNUNONM020 |
| F92RLUNUNONM021 | F92RLUNUNONM022 | F92RLUNUNONM023 | F92RLUNUNONM024 | F92RLUNUNONM025 |
| F92RLUNUNONM026 | F92RLUNUNONM027 | F92RLUNUNONM028 | F92RLUNUNONM029 | F92RLUNUNONM030 |
| F92RLUNUNONM031 | F92RLUNUNONM032 | F92RLUNUNONM033 | F92RLUNUNONM034 | F92RLUNUNONM035 |
| F92RLUNUNONM036 | F92RLUNUNONM037 | F92RLUNUNONM038 | F92RLUNUNONM039 | F92RLUNUNONM040 |
| F92RLUNUNONM041 | F92RLUNUNONM042 | F92RLUNUNONM043 | F92RLUNUNONM044 | F92RLUNUNONM045 |
| F92RLUNUNONM046 | F92RLUNUNONM047 | F92RLUNUNONM048 | F92RLUNUNONM049 | F92RLUNUNONM050 |