




Tubular Ring Terminal, Non-Insulated

Type S-R

- Seamless tubular barrel provides a consistent high performance quality crimp
- Round double thick tongue for reliable power applications
- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Inspection window allows visual inspection of proper wire insertion
- Maximum recommended operating temperature 302°F (150°C)
- UL and CSA rated up to 2000 V per UL 486A – 486B



Min. Tensile Strength of Tubular Ring Terminals

#8	#6	#4	#2
90	100	140	180

			Tongue Width (In.)	Figure Dimensions (In.)				Recommended Installation Tool	Std. Pkg. Qty.**	Std. Ctn. Qty.
Part Number	Wire Range	Stud Hole Size	W	L	B	T				
S8-10R-Q	8 AWG	#10	0.41	1.10	0.40	0.08	CT-1700, CT-720, CT-930, CT-930CH, CT-940CH, CT-2001, CT-2002, CT-2931, CT-2940	25	250	
S8-14R-Q		1/4"	0.48	1.20	0.40	0.07		25	—	
S8-56R-Q		5/16"	0.60	1.30	0.40	0.05		25	250	
S8-38R-Q		3/8"	0.60	1.40	0.40	0.05		25	250	
S6-10R-E	6 AWG	#10	0.45	1.20	0.48	0.09		20	200	
S6-14R-E		1/4"	0.48	1.30	0.48	0.08		20	—	
S6-56R-E		5/16"	0.56	1.40	0.48	0.07		20	200	
S6-38R-E		3/8"	0.62	1.50	0.48	0.06		20	200	
S4-10R-E	4 AWG	#10	0.55	1.20	0.48	0.09		20	200	
S4-14R-E		1/4"	0.55	1.30	0.48	0.09		20	200	
S4-56R-E		5/16"	0.55	1.40	0.48	0.09		20	200	
S4-38R-E		3/8"	0.62	1.50	0.48	0.07		20	200	
S2-10R-X	1 – 2 AWG	#10	0.70	1.60	0.59	0.11		10	100	
S2-14R-X		1/4"	0.70	1.60	0.59	0.11		10	100	
S2-56R-X		5/16"	0.70	1.70	0.59	0.11		10	100	
S2-38R-X		3/8"	0.70	1.70	0.59	0.11		10	100	
S2-12R-X		1/2"	0.79	1.90	0.59	0.09	10	100		
S1/0-14R-X	1/0 AWG	1/4"	0.76	1.60	0.58	0.12	CT-720, CT-930, CT-930CH, CT-940CH, CT-2001, CT-2002, CT-980, CT-2980, CT-980CH, CT-2931, CT-2940	10	100	
S1/0-56R-X		5/16"	0.76	1.70	0.58	0.12		10	100	
S1/0-38R-X		3/8"	0.76	1.70	0.58	0.12		10	100	
S1/0-12R-X		1/2"	0.82	1.90	0.58	0.12		10	100	
S2/0-14R-X	2/0 AWG	1/4"	0.85	1.90	0.66	0.13		10	100	
S2/0-56R-X		5/16"	0.85	1.90	0.66	0.13		10	100	
S2/0-38R-X		3/8"	0.85	1.90	0.66	0.13		10	100	
S2/0-76R-X		7/16"	0.85	2.10	0.66	0.13		10	100	
S2/0-12R-X		1/2"	0.85	2.10	0.66	0.13		10	100	
S3/0-14R-5	3/0 AWG	1/4"	0.96	2.10	0.83	0.13		5	50	
S3/0-56R-5		5/16"	0.96	2.10	0.83	0.13		5	50	
S3/0-38R-5		3/8"	0.96	2.10	0.83	0.13		5	50	
S3/0-76R-5		7/16"	0.96	2.30	0.83	0.13		5	50	
S3/0-12R-5		1/2"	0.96	2.30	0.83	0.13		5	50	
S4/0-56R-5	4/0 AWG	5/16"	1.06	2.30	0.91	0.14		5	50	
S4/0-38R-5		3/8"	1.06	2.30	0.91	0.14		5	50	
S4/0-76R-5		7/16"	1.06	2.50	0.91	0.14	5	50		
S4/0-12R-5		1/2"	1.06	2.50	0.91	0.14	5	50		
S250-56R-5	250 kcmil	5/16"	1.17	2.50	1.01	0.14	5	50		
S250-38R-5		3/8"	1.17	2.50	1.01	0.14	5	50		
S250-76R-5		7/16"	1.17	2.60	1.01	0.14	5	50		
S250-12R-5		1/2"	1.17	2.60	1.01	0.14	5	50		

For crimping tool information, see pages D1.84, D1.87, D3.37 – D3.46.

**Bulk packaging may be available, contact Panduit Customer Service for additional information.

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[S6-38R-E](#) [S2-38R-X](#) [S1/0-38R-X](#) [S2/0-38R-X](#) [S2-10R-X](#) [S6-10R-E](#) [S6-56R-E](#) [S2-56R-X](#) [S6-14R-E](#) [S2-14R-X](#)
[S4-10R-E](#) [S4-14R-E](#) [S8-10R-Q](#) [S8-14R-Q](#) [S8-38R-Q](#) [S1/0-12R-X](#) [S1/0-56R-X](#) [S3/0-12R-5](#) [S4/0-12R-5](#) [S4/0-56R-](#)
[5](#) [S250-12R-5](#) [S2-12R-X](#) [S2/0-76R-X](#)