

## Feed-through header - GMSTB 2,5/10-G-7,62 BK AU - 1710029

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB headers, nominal current: 12 A, rated voltage (III/2): 630 V, number of positions: 10, pitch: 7.62 mm, color: black, contact surface: Gold, mounting: Soldering



The figure shows a 10-position version of the product

### Your advantages

- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- Well-known mounting principle allows worldwide use
- ✓ Larger pitch for increased voltage requirements
- ☑ Plug-in direction parallel to the PCB



## **Key Commercial Data**

Packing unit	50 pc
GTIN	4 055626 139630
GTIN	4055626139630

### Technical data

#### **Dimensions**

Pitch	7.62 mm
Length of the solder pin	3.5 mm
Pin dimensions	1 x 1 mm

### General

Range of articles	GMSTB 2,5/G
Insulating material group	I
Rated voltage (III/2)	630 V
Nominal current I <sub>N</sub>	12 A
Flammability rating according to UL 94	V0
Color	black



# Feed-through header - GMSTB 2,5/10-G-7,62 BK AU - 1710029

## Technical data

General	
Number of positions	10
Standards and Regulations	
Flammability rating according to UL 94	V0
Environmental Product Compliance	
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values
Approvals  Approvals	
Approvals	
EAC	
Ex Approvals	

Approval details

EAC B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg

Tel. +49 5235 300 Fax +49 5235 3 41200

Germany

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1710029