

## PCB terminal block - FFKDSA1/V1-5,08- 3 BD:I-C3 - 1711267

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block, nominal current: 15 A, nom. voltage: 320 V, pitch: 5.08 mm, number of positions: 3, connection method: Push-in spring connection, mounting: Wave soldering, color: green. The article can be aligned to create different nos. of positions!

The figure shows a 1-pos. version of the product

#### Your advantages

- Time saving push-in connection, tools not required
- ${\ensuremath{\,^{\scriptsize \Box}}}$  Defined contact force ensures that contact remains stable over the long term
- ☑ Intuitive use through colour coded actuation lever
- ☑ Operation and conductor connection from one direction enable integration into front of device
- ☑ Two solder pins reduce the mechanical strain on the soldering spots
- The latching on the side enables various numbers of positions to be combined
- ☑ Vertical connection enables multi-row arrangement on the PCB



#### Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 255224
GTIN	4055626255224

### Technical data

#### Dimensions

Length [1]	12.7 mm
Pitch	5.08 mm
Dimension a	10.16 mm
Width [ w ]	17.74 mm
Height	13.6 mm
Height [ h ]	17 mm
Solder pin [P]	3.4 mm
Hole diameter	1.3 mm



## PCB terminal block - FFKDSA1/V1-5,08- 3 BD:I-C3 - 1711267

### Technical data

#### General

Range of articles	FFKDS(A)/V1	
Insulating material group	1	
Rated voltage (III/2)	320 V	
Nominal current I <sub>N</sub>	15 A	
Nominal cross section	1.5 mm <sup>2</sup>	
Flammability rating according to UL 94	V0	
Number of positions	3	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: <u>1711267</u>