

## Fuse plug - ST 1-SI - 0920326

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, nominal current: 10 A, length: 45.4 mm, width: 9.9 mm, color: black

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                   |
| GTIN         | <br>4 017918 010195 |
| GTIN         | 4017918010195                                                                                           |

### Technical data

#### General

|                                        |       |
|----------------------------------------|-------|
| Color                                  | black |
| Insulating material                    | PA    |
| Flammability rating according to UL 94 | V2    |

#### Dimensions

|        |         |
|--------|---------|
| Width  | 9.9 mm  |
| Length | 45.4 mm |

#### General

|                                                                         |              |
|-------------------------------------------------------------------------|--------------|
| Fuse                                                                    | G / 6,3 x 32 |
| Insulating material group                                               | CTI 600      |
| Nominal current $I_N$                                                   | 10 A         |
| Nominal voltage $U_N$                                                   | 400 V        |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C       |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C       |
| Static insulating material application in cold                          | -60 °C       |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed       |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed       |

# Fuse plug - ST 1-SI - 0920326

## Technical data

### General

|                                                        |             |
|--------------------------------------------------------|-------------|
| Smoke gas toxicity NFPA 130 (SMP 800C)                 | passed      |
| Calorimetric heat release NFPA 130 (ASTM E 1354)       | 28 MJ/kg    |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |

### Connection data

|                   |                 |
|-------------------|-----------------|
| Connection method | Plug connection |
|-------------------|-----------------|

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V2 |
|----------------------------------------|----|

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27142001 |
| eCl@ss 4.0    | 27142000 |
| eCl@ss 4.1    | 27142000 |
| eCl@ss 5.0    | 27142000 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27142000 |
| eCl@ss 7.0    | 27142001 |
| eCl@ss 8.0    | 27142001 |
| eCl@ss 9.0    | 27142001 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC002018 |
| ETIM 5.0 | EC000036 |
| ETIM 6.0 | EC000035 |
| ETIM 7.0 | EC000035 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |

## Fuse plug - ST 1-SI - 0920326

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39121629 |
| UNSPSC 18.0 | 39121629 |
| UNSPSC 19.0 | 39121629 |
| UNSPSC 20.0 | 39121629 |
| UNSPSC 21.0 | 39121629 |

### Approvals

#### Approvals

#### Approvals

#### EAC

#### Ex Approvals

#### Approval details

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.BL08.B.00714 |
|-----|-------------------------------------------------------------------------------------|--------------------------|

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[0920326](#)