

## Fuse plug - ST 1-SILED 24 - 0920384

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, nominal current: 10 A, length: 45.4 mm, width: 9.9 mm, color: black

The figure shows a similar product

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                   |
| GTIN         | <br>4 017918 010218 |
| GTIN         | 4017918010218                                                                                           |

### Technical data

#### General

|                                        |       |
|----------------------------------------|-------|
| Color                                  | black |
| Insulating material                    | PA    |
| Flammability rating according to UL 94 | V2    |

#### Dimensions

|        |         |
|--------|---------|
| Width  | 9.9 mm  |
| Length | 45.4 mm |

#### General

|                                                                         |                                                                                       |
|-------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Fuse                                                                    | G / 6,3 x 32                                                                          |
| Insulating material group                                               | CTI 600                                                                               |
| Nominal current $I_N$                                                   | 10 A                                                                                  |
| Nominal voltage $U_N$                                                   | 400 V (In the event of a defective fuse, the downstream circuit is not disconnected.) |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C                                                                                |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C                                                                                |
| Static insulating material application in cold                          | -60 °C                                                                                |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed                                                                                |

# Fuse plug - ST 1-SILED 24 - 0920384

## Technical data

### General

|                                                         |             |
|---------------------------------------------------------|-------------|
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                  | passed      |
| Calorimetric heat release NFPA 130 (ASTM E 1354)        | 28 MJ/kg    |
| Fire protection for rail vehicles (DIN EN 45545-2) R22  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26  | HL 1 - HL 3 |

### Connection data

|                   |                 |
|-------------------|-----------------|
| Connection method | Plug connection |
|-------------------|-----------------|

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V2 |
|----------------------------------------|----|

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27142001 |
| eCl@ss 4.0    | 27142000 |
| eCl@ss 4.1    | 27142000 |
| eCl@ss 5.0    | 27142000 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27142000 |
| eCl@ss 7.0    | 27142001 |
| eCl@ss 8.0    | 27142001 |
| eCl@ss 9.0    | 27142001 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC002018 |
| ETIM 5.0 | EC000036 |
| ETIM 6.0 | EC000035 |
| ETIM 7.0 | EC000035 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121629 |
| UNSPSC 18.0   | 39121629 |

## Fuse plug - ST 1-SILED 24 - 0920384

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 19.0 | 39121629 |
| UNSPSC 20.0 | 39121629 |
| UNSPSC 21.0 | 39121629 |

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

#### Approval details

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.BL08.B.00714 |
|-----|-------------------------------------------------------------------------------------|--------------------------|

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

0920384